



Risk Evaluation Determining Whether Environmental Emergency Planning is Required Under the *Environmental Emergency Regulations set under the Canadian Environmental Protection Act, 1999* (CEPA 1999)

This report is a consolidation of two substances listed under Schedule 1 of the *Environmental Emergency Regulations* set under CEPA 1999. The substances inherent hazardous properties are virtually the same.

Sodium Arsenate, Dibasic (CAS #: 7778-43-0)
AND Sodium Arsenate, Dibasic, Heptahydrate (CAS #: 10048-95-0)
(Inorganic Arsenic Compounds)
(CEPA, 1999 – Schedule 1, #28)

Summary of Risk Evaluation Analysis

The Risk Evaluation Framework (REF), developed by Environment Canada, is applied to chemical substances in order to determine whether or not an environmental emergency (E2) plan should be required. For those substances that are evaluated as requiring an E2 plan, the next step is to determine a threshold quantity for the total quantity of the substance and the maximum storage container size on site. Within the REF, three categories are used to evaluate chemicals and assign threshold quantities. Shown below are the details within the three categories for *sodium arsenate, dibasic*:

1. Environment Hazard

(Persistence, Bioaccumulation and Aquatic Toxicity Analysis)

- According to Mackay *et al.* (2003), nickel, chromium, arsenic, and cadmium are classified as indefinitely persistent. As a result, *sodium arsenate, dibasic* is also classified as indefinitely persistent in the environment.
- No data are available to determine the bioaccumulation potential.

- For aquatic toxicity, it was determined that *sodium arsenate, dibasic* is slightly toxic (LC₅₀ at 96 hrs between 10 and 100 mg/L) based on the most sensitive species, Arctic grayling (Buhl *et al.*, 1990).

2. Human Hazard

(Inhalation Toxicity and Carcinogenicity Analysis)

- Since *sodium arsenate, dibasic* has a vapour pressure below 1.33 kPa at 20°C (Mallinckrodt Baker Inc., 2009), there is insufficient vapour from the substance to cause an inhalation problem.
- Sodium arsenate, dibasic* is categorized as a United States Environmental Protection Agency (US EPA) carcinogen with a classification rating of 'A' (IRIS, 1988) and as an International Agency for Research on Cancer (IARC) carcinogen classification rating of '1' (HSDB, 2003; IARC, 1990).

3. Physical Hazard

(Flammability and Combustibility Analysis)

- Sodium arsenate, dibasic* is a substance stable under ordinary conditions of use and storage. *Sodium arsenate, dibasic* emits toxic fumes of arsenic when heated to decomposition. Hazardous polymerization will not occur. *Sodium arsenate, dibasic* is not considered to be a fire hazard (Mallinckrodt Baker Inc., 2009).

Flammability and Combustibility Analysis Table

	Value	Vapour Cloud Explosion (Yes/No)	Combustible (Yes/No)	References
Boiling point (°C)	150 Decomposes	No	No	(Mallinckrodt Baker Inc., 2009)
Flash point (°C)	Non-flammable			

Threshold

The data from the above mentioned categories were used to determine the various environmental/human thresholds. The threshold quantities relate to: carcinogenicity, aquatic toxicity, inhalation toxicity, vapour cloud explosion, combustibility, and reactivity.

The threshold quantity for carcinogenicity is defaulted to 0.22 tonnes, if it meets the following criteria:

- 1) have an IARC rating of 1, 2A or 2B, or have a US EPA rating of A, B1, or B2;
- 2) be persistent in any media for greater than 5 years.

Threshold quantities assigned as a result of aquatic toxicity are based on the following table:

Threshold Quantities Assigned as a Result of Aquatic Toxicity

Criteria	Extremely Toxic	Highly Toxic	Moderately Toxic	Slightly Toxic
Persistence (water)	≥ 6 months	≥ 2 months to < 6 months	N/A	N/A
Bioaccumulation	BCF ≥ 5000 or Log Kow ≥ 5	BCF ≥ 500 to < 5000 or Log Kow ≥ 4 to < 5 (unless BCF < 500)	N/A	N/A
Acute Aquatic Toxicity (96 hrs LC₅₀ – mg/L)	≤ 0.1	> 0.1 to ≤ 1	> 1 to ≤ 10	> 10 to ≤ 100
Threshold Quantity Tonnes (lbs)	0.22 (500 lbs)	1.13 (2 500 lbs)	4.50 (10 000 lbs)	9.10 (20 000 lbs)

A substance is a candidate for a vapour cloud explosion if its flash point is < 23°C and its boiling point is < 35°C. A substance is considered combustible if its flash point is < 23°C or its boiling point is < 35°C. In accordance with the precautionary principle, the category with the lowest threshold will be used. For further explanation, please refer to the *Implementation Guidelines for Part 8 of the Canadian Environmental Protection Act, 1999 – Environmental Emergency Plans* (<http://www.ec.gc.ca/ee-ue/>).

Conclusion

For *sodium arsenate, dibasic* # 28, the E2 hazard threshold was triggered by:

- 1) Aquatic toxicity at 0.22 tonnes;
- 2) Carcinogenicity at 0.22 tonnes.

Therefore, *sodium arsenate, dibasic* # 28 is recommended for addition to Schedule 1 of the *Environmental Emergency Regulations* under Part 3 with a threshold quantity of 0.22 tonnes.

References

Buhl, K.J., and S.J. Hamilton. "Comparative Toxicity of Inorganic Contaminants Released by Placer Mining to Early Life Stages of Salmonids." 1990. *Ecotoxicology and Environmental Safety*. 20(3): 325-342.

HSDB (Hazardous Substances Data Bank). *Sodium Arsenate*. Canadian Centre for Occupational Health and Safety. U.S. National Library of Medicine. 2003. World Wide Web accessed October 2004. <http://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?HSDB>

IARC (International Agency for Research on Cancer). *Arsenic and Arsenic Compounds*. World Health Organization. 1987. World Wide Web accessed October 2004. <http://monographs.iarc.fr/ENG/Monographs/suppl7/suppl7.pdf>

IRIS (Integrated Risk Information Systems). *Inorganic Arsenic*. U.S. Environmental Protection Agency. 1988. World Wide Web accessed October 2004. <http://www.epa.gov/iris/subst/0278.htm>

Mackay, D., E. Webster, D. Woodfine, T.M. Cahill, P. Doyle, Y. Couillard, and D. Gutzman. "Contributed Articles Towards Consistent Evaluation of the Persistence of Organic, Inorganic and Metallic Substances". 2003. ASP. Canadian Environmental Modelling Centre and Environment Canada. *Human and Ecological Risk Assessment*. 9: 1445-1474. ISSN: 1080-7039.

Mallinckrodt Baker Inc. "Material Safety Data Sheet – Sodium Arsenate Heptahydrate". MSDS Number S2858. Mallinckrodt Chemicals. Phillipsburg, NJ. 2009. World Wide Web accessed November 2011. <http://ccinfoweb.ccohs.ca/msds/pdf/mb/6270369.pdf>

Cat. No.: En14-55/24-2011E-PDF
ISBN: 978-1-100-19713-5

For information regarding reproduction rights, please contact Public Works and Government Services Canada at 613-996-6886 or at droitdauteur.copyright@tpsgc-pwgsc.gc.ca

© Her Majesty the Queen in Right of Canada, represented by the Minister of the Environment, 2011

Aussi disponible en français

Sodium Arsenate, Dibasic (CAS #: 7778-43-0)
AND Sodium Arsenate, Dibasic, Heptahydrate (CAS #: 10048-95-0)
(*Inorganic Arsenic Compounds*)
(CEPA, 1999 – Schedule 1, #28)