

DESCRIPTIVE NOTES

INTRODUCTION
The time- and depth-structure maps presented herein are part of an eight-map series of the subsurface of Sabine Peninsula spanning the Early Permian through Early Cretaceous interval. These maps are the product of the application of modern geoscientific methods of processing and interpretation to a suite of legacy seismic-reflection data from onshore Sabine Peninsula (Melville Island, Western Arctic). The resultant processed seismic lines were interpreted using the existing regional geological framework (see Harrison, 1999) by integrating existing regional well data, geological logs, age control, and lithological information through synthetic seismograms.

REGIONAL SETTING

The Sabine Peninsula is located within the Sverdrup Basin in the Queen Elizabeth Islands of the western Arctic. The Sverdrup Basin extends for about 1300 km in a north-south-southwest direction and is up to 350 km wide. The basin contains up to 13 km of sedimentary strata (Embry and Beauchamp, 2008). The Sverdrup Basin is separated from the underlying Franklin Basin by an unconformity at the base of the Carboniferous strata. The Franklin Basin was extensively widespread following Late Devonian-earliest Carboniferous Eiseismitic Orogeny. The resulting rift-related structural depression acted as a major depocentre from the Carboniferous through the Palaeogene (Embry and Beauchamp, 2008). The Sverdrup Basin succession was uplifted and deformed during the early Cenozoic Eureka Orogeny.

SEISMIC DATA SET AND PROCESSING

Data access was obtained through a Memorandum of Understanding signed in 1997 by the Geological Survey of Canada (GSC), Panarctic Oils, the Arctic Islands Exploration Group, and the Offshore Arctic Exploration Group (venture parties). The data sets consist of original land seismic-reflection field tapes transcribed from 21-, 7-, and 9-track media. Data were collected using a dynamic charge of 20-30 kg per shot at about 20 m below the surface. Shot-point spacing ranged from 60 m to 300 m, the shorter spacing being used for most surveys. The majority of the seismic-reflection data were recorded using 48- or 96-channel systems. Channel stations were generally deployed using nine receivers spaced at about 5 m and station intervals ranging from 50 m to 70 m. The common-midpoint multiplicity of the data sets range from single to 12-fold coverage. The most common recording length was 6 s.

TIME TO DEPTH CONVERSION

All time surfaces converted to depth using the following procedure. First V_m of the 3-D velocity model are calculated using Dix equation:
V_m^2 = [V_1^2 t_1^2 + V_2^2 t_2^2 - V_1^2 t_1 t_2] / (t_2 - t_1)
where t_1 is the zero-offset arrival time of the jth reflection. Interval limits corresponded to seismic horizons that are picked and tied to geological interfaces. Then V_m are extracted from the velocity model along picked horizons. Velocity maps are then computed using Universal kriging at a cell size of 250 m. Finally, the time-structure surfaces of the various seismic horizons are converted to depth (Z) using:
Z = (V_m * t) / 2

SEISMIC INTERPRETATION AND VISUALIZATION METHODS

Processed seismic lines were loaded into IHS-Kingdom seismic and geological interpretation software. Prominent seismic-reflection horizons, tied to well formation-top information, were manually correlated. Seed points were generated at seismic line intersections, thereby permitting the interpretation of adjacent lines. The map would benefit from a detailed structural interpretation; however, confidence of this interpretation is minimized due to minor vertical offsets (about 1 s) attributed to faulting and the large line spacing. These reflections are readily identified across faults despite offset. Time-structure maps of the key seismic horizons were computed using universal kriging. Universal kriging permits the interpolation of a nonstationary, random field by adding a term in the kriging equation that accommodates any linear trends present in a scattered point set (Chiles and Delfiner, 1999). Given that all picked horizons showed a strong linear trend for time versus depth over distance, universal kriging provided the best fit to the picked horizons.

RECOMMENDED CITATION

Duchesne, M.J., Brako, V.I., Dewing, K., Claproot, M., Gjoavgen, E., and Brent, T.A., 2013. Time- and depth-structure map, Great Bear Cape Formation, Sabine Peninsula, Melville Island, Nunavut-Northwest Territories. Geological Survey of Canada, Canadian Geoscience Map 168, scale 1:200 000. doi:10.4095/293962

UNCERTAINTY

Quantifying the uncertainty of seismic subsurface maps is difficult since several sources of error, each with their unique level of uncertainty, are used in the map generation. Sources of error may arise from limitations in acquisition, processing, and interpretation. Moreover, seismic data are collected remotely and the images they provide are derived from generalized mathematical and physical concepts. Common to all acquisition that increase the uncertainty include gaps in coverage because of obstacles to source and receiver deployment, and effect of direction of shooting on data quality (Shenit and Gattai, 1995). Processing errors may result from inadequate static corrections, inaccurate velocity analysis, and inappropriate parameter determination.

TIME- AND DEPTH-STRUCTURE DATA DISPLAY

The time- and depth-structure data shown on this map were gridded at a cell size of 250 m using Universal kriging. Each map presents a grid with a stretched colour ramp at 20% transparency. Time contours generated from the time-structure grids are shown in black at a 100 m interval, whereas depth contours derived from the depth-structure grid are presented at 150 m intervals.

GREAT BEAR CAPE MAP DESCRIPTIONS

The Early Permian Great Bear Cape Formation consists of isolated and locally fossiliferous carbonate (Dewing and Embry, 2007, see also Fig. 3). Formation-top data indicate the Great Bear Cape Formation carbonate units are underlain by the carbonate units of the Raanes Formation. The Maryatt K-71 well was the only well on Sabine Peninsula to sample the Great Bear Cape Formation, hence its relationship with the surrounding strata (Dewing and Embry, 2007).

ACKNOWLEDGMENTS

The authors would like to thank J. Dietrich and B. MacLean (GSC Calgary) for their technical reviews that improved the overall quality of the maps. IHS is acknowledged for providing Kingdom 8.8 seismic interpretation software.

REFERENCES

- Chiles, J.-P. and Delfiner, P., 1999. Geostatistics: Modeling Spatial Uncertainty; Wiley Series in Probability and Statistics. Wiley, New York, New York, 284 p.
- Claproot, M., Duchesne, M.J., and Gjoavgen, E., 2011. A geostatistical approach for 2-D seismic velocity modelling. Geological Survey of Canada, OpenFile 7045, 21 p. doi:10.4095/286651
- Dewing, K. and Embry, A.F., 2007. Geological and geochemical data from the Canadian Arctic Islands. Part 1: Stratigraphic topography, Melville Island and adjacent northeast islands. Geological Survey of Canada, Open File 5442, 1 CD-ROM. doi:10.4095/22386
- Duchesne, M.J., Claproot, M., and Gjoavgen, E., 2012. Improving seismic velocity estimation for 2-D poststack time migration of regional seismic data using kriging with an external drift. The Leading Edge, v. 31, p. 1156-1166.
- Embry, A. and Beauchamp, B., 2008. Sverdrup Basin in Sedimentary Basins of the World, (ed.) K.J. Hall, Volume 5, The Sedimentary Basins of the United States and Canada. Elsevier, Amsterdam, The Netherlands, p. 451-471.
- Harrison, J.C., 1998. Melville Island and adjacent northeast islands, Canadian Arctic. Antipodology. District of Franklin, Northwest Territories. Geological Survey of Canada, Map 1844A, scale 1:250 000. doi:10.4095/203577
- Harrison, J.C., 1999. Melville Island's salt-based fold belt. Arctic Canada. Geological Survey of Canada, Bulletin 472, 344 p. doi:10.4095/203576
- Hass, A. and Dubrule, O., 1994. Geostatistical inversion - a sequential method of stochastic reservoir modelling constrained by seismic data. First Break, v. 12, p. 561-569.
- Shenit, R.E. and Gattai, L.P., 1995. Exploration Seismology. Cambridge University Press, New York, New York, 628 p.



Figure 1. Generalized surface geology map of Sabine Peninsula (after Harrison, 1994) displaying sedimentary stratigraphic divisions.

ABSTRACT

Sabine Peninsula of Melville Island was the subject of an oil and gas exploration boom from 1981 to 1985, during which time seismic-reflection data were collected and wells were drilled. As a result, the two largest conventional natural gas fields in Canada were discovered. Seismic-reflection methods use sound waves to image the internal structure of the Earth. Waves are emitted at the surface before being reflected back to the surface by geological interfaces and recorded. Modern analysis methods were used to re-investigate existing seismic data. In doing so, eight seismic unit boundaries identified on seismic profiles in two-way time were correlated to the regional geological framework and gridded to provide subsurface maps. Each map approximates the structures preserved at that particular time or depth allowing the enhancement of the geological knowledge of Sabine Peninsula and better delineation of elements of the petroleum systems therein.

RÉSUMÉ

La péninsule de Sabine de l'île de Melville a connu un boom d'exploration gazière et pétrolière entre 1981-1985 pendant lequel des données de sismique-réflexion furent acquises et des puits forés. En résultat, la découverte de deux plus grands champs de gaz naturel conventionnels du Canada. Les sismique-réflexion utilise des ondes sonores pour imager la structure interne de la Terre. Les ondes sont émises en surface avant d'être réfléchies de nouveau vers la surface par des interfaces géologiques où elles sont enregistrées. Des méthodes d'analyse modernes furent utilisées pour ré-investiger des données sismiques existantes. Ainsi, huit limites d'unités sismiques identifiées sur les profils sismiques en temps de parcours aller-retour furent corrélées au cadre géologique régional et maillées afin de produire des cartes de la sous-surface. Chaque carte est une approximation des structures préservées à un certain temps ou une certaine profondeur nous permettant d'améliorer les connaissances géologiques de la péninsule de Sabine et de mieux délimiter les éléments des systèmes pétroliers s'y trouvant.

COVER ILLUSTRATION

Permian sandstone hoodoos, Sabine Peninsula, Melville Island, Nunavut. Photograph by T.A. Brent, 2013-242

Catalogue No. M163-1168-2013E-PDF ISBN 978-1-105-29298-2 doi:10.4095/293962

© Her Majesty the Queen in Right of Canada 2013

Natural Resources Canada Ressources naturelles du Canada


CANADIAN GEOSCIENCE MAP 168 TIME- AND DEPTH-STRUCTURE MAP GREAT BEAR CAPE FORMATION Sabine Peninsula, Melville Island Nunavut-Northwest Territories 1:200 000



Canadian Geoscience Maps logo and Canada logo.

TIME- AND DEPTH-STRUCTURE MAP GREAT BEAR CAPE FORMATION Sabine Peninsula, Melville Island Nunavut-Northwest Territories 1:200 000

Map projection: Universal Transverse Mercator, zone 12. Base map scale: 1:250 000 from Natural Resource Canada, with modifications. Proximity to the North Magnetic Pole causes the magnetic compass to be useless in this area.



ess.nrncan.gc.ca

Authors: M.J. Duchesne, V.I. Brako, K. Dewing, M. Claproot, E. Gjoavgen, and T.A. Brent. Cartography by R. Boivin. Scientific editing by E. Inglis. Initiative of the Geological Survey of Canada, conducted under the auspices of the Western Arctic Islands' project as part of Natural Resources Canada's Geo-mapping for Energy and Minerals (GEM) program.

The Geological Survey of Canada welcomes corrections or additional information from users. The data may include additional observations not portrayed on this map. See documentation accompanying the data. This publication is available for free downloading through GEOCAN (http://geocan.ess.nrncan.gc.ca/). This map is not to be used for navigational purposes.