

CANMET

REPORT 82-13E

Canada Centre
for Mineral
and Energy
Technology

Centre canadien
de la technologie
des minéraux
et de l'énergie

ANALYSIS DIRECTORY OF CANADIAN COMMERCIAL COALS - SUPPLEMENT NO. 4

D.K. FAURSCHOU, G.W. BONNELL AND L.C. JANKE

ELLIOT LAKE LABORATORY
CANMET, E.M.R.

NOV 22 1983
RECEIVED
ELLIOT LAKE, ONTARIO

ENERGY RESEARCH PROGRAM
COAL RESEARCH LABORATORIES

JUNE 1982



Energy, Mines and
Resources Canada

Énergie, Mines et
Ressources Canada

Canada

© Minister of Supply and Services Canada 1983

Available in Canada through

Authorized Bookstore Agents
and other bookstores

or by mail from

Canadian Government Publishing Centre
Supply and Services Canada
Hull, Quebec, Canada K1A 0S9

CANMET
Energy, Mines and Resources Canada,
555 Booth St.,
Ottawa, Canada K1A 0G1

or through your bookseller

Catalogue No. M38-13/82-13E Canada: \$17.25
ISBN 0-660-11409-7 Other countries: \$20.70

Price subject to change without notice.

Disponible en français

ANALYSIS DIRECTORY OF CANADIAN COMMERCIAL COALS -
SUPPLEMENT No. 4

by

D.K. Faurschou*, G.W. Bonnell** and L.C. Janke***

SUMMARY

The quality of Canadian commercial coals was monitored from 1978 to 1981 by independently sampling mine run and prepared coals at operating mines, preparation plants, thermal generating plants and delivery points on an occasional basis, usually annual, with the cooperation of the coal industry. Sampling and sample preparation were done by personnel of the Coal Research Laboratories located at Sydney, Nova Scotia and Edmonton, Alberta. Analyses, for the most part, were performed at the CANMET laboratories in Ottawa and Sydney.

Generally, the samples represent production on a specific day, thus the results are broadly indicative, at least for comparative and screening purposes, of the quality of Canadian commercial coals produced at the time of sampling. Also, because of financial and manpower limitations, not all sites were sampled. For example, in 1980 and 1981 Western Canadian coals were not sampled.

Coals are identified by operator (not necessarily the lease owner), name of mine, seam, coalfield and location. Information is arranged by province and is intended to provide a ready indication of the quality of commercially available coals and to complement coal industry statistics available in other federal and provincial reports.

*Research Scientist, Ottawa, **Supervising Chemist, Sydney and ***Head, Solid Fuels Laboratory, Ottawa, CANMET, Energy, Mines and Resources Canada.

RÉPERTOIRE DES ANALYSES DES CHARBONS COMMERCIAUX CANADIENS

SUPPLÉMENT No. 4

par

D.K. Faurschou*, G.W. Bonnell** and L.C. Janke***

SOMMAIRE

De 1978 à 1981, on a examiné la qualité des charbons commerciaux canadiens par divers moyens, dont l'étude indépendante d'échantillons de produits bruts, de charbons préparés dans des mines en opération, dans des installations de préparation, des installations thermiques, de même qu'à l'occasion - généralement sur une base annuelle - à des points de livraison, et ce avec la collaboration de l'industrie du charbon.

L'échantillonnage et la préparation des échantillons a été effectuée par le personnel des Laboratoires de recherche sur le charbon, situés à Sydney, en Nouvelle-Ecosse, et à Edmonton, en Alberta. La plupart des analyses ont été faites aux laboratoires de CANMET à Ottawa et à Sydney.

En général, les échantillons représentant la production au cours d'une journée spécifique, les résultats offrent un vaste éventail, du moins à des fins de comparaison et de triage, de la qualité des charbons commerciaux canadiens produits lors de l'échantillonnage. Nous devons signaler qu'à cause de limitations financières et de main-d'œuvre, tous les sites n'ont pas été échantillonnés. Ainsi, les charbons de l'Ouest du Canada ne furent pas échantillonnés en 1980-1981.

On a identifié les charbons selon le nom de l'exploitant de la mine (lequel n'est pas nécessairement le même que celui du propriétaire du bail), de même que selon le filon, le bassin houiller et l'emplacement. L'information, disposée par province, vise à offrir une indication immédiate de la qualité des charbons commerciaux disponibles. En outre, elle a pour but de compléter les statistiques relatives à l'industrie du charbon qui sont disponibles dans d'autres rapports fédéraux et provinciaux.

*Chercheur scientifique, Ottawa, **Chimiste-surveillant, CANMET, Energie, Mines et Ressources Canada et ***Chef du Laboratoire des carburants solides, Ottawa.

CONTENTS

| | <u>Page</u> |
|---|-------------|
| SUMMARY | i |
| SOMMAIRE | ii |
| INTRODUCTION | 1 |
| CONVERSION FACTORS | 5 |
| COAL ANALYSES - NOVA SCOTIA | 7 |
| Cape Breton Development Corporation (CBDC): | |
| - Lingan Mine (u/g) | 8 |
| - No. 26 Colliery (u/g) | 24 |
| - Lingan/No. 26 combined (u/g) | 30 |
| - Prince Mine (u/g) | 34 |
| - T. Brogan & Sons (strip) | 48 |
| Drummond Coal Company Limited (u/g) | 52 |
| Evans Coal Mines Limited (u/g) | 56 |
| River Hébert Coal Company Limited: | |
| - Cochrane Mine (u/g) | 68 |
| Thorburn Mining Limited (reclamation) | 72 |
| Novaco Limited (strip) | 80 |
| COAL ANALYSES - NEW BRUNSWICK | 83 |
| N.B. Coal Limited (strip) | 84 |
| Knox Construction Limited (strip) | 102 |
| R. Mills Coal Company (reclamation) | 112 |
| COAL ANALYSES - SASKATCHEWAN | 115 |
| Manalta Coal Limited: | |
| - Klimax Mine (strip) | 116 |
| - Utility Mine (strip) | 126 |
| Bienfait Coal Co. Ltd. (strip) | 128 |
| Manitoba and Saskatchewan Coal Company (Limited): | |
| - Boundary Dam Mine (strip) | 132 |
| COAL ANALYSES - Alberta (Subbituminous) | 135 |
| Century Coals Limited: | |
| - Atlas (No. 1742) Mine (u/g) | 136 |
| Forestburg Collieries Limited: | |
| - Diplomat (No. 1578) Mine (strip) | 140 |

CONTENTS (cont'd)

| | <u>Page</u> |
|--|-------------|
| Manalta Coal Limited: | |
| - Vesta (No. 1046) Mine (strip) | 152 |
| - Whitewood (No. 1757) Mine (strip) | 154 |
| - Highvale (No. 1769) Mine (strip) | 156 |
| - Roselyn (No. 443) Mine (strip) | 158 |
| COAL ANALYSES - ALBERTA (Bituminous) | 167 |
| The Canmore Mines Limited (u/g) | 168 |
| Cardinal River Coals Limited (strip) | 170 |
| Coleman Collieries Limited (strip) | 172 |
| McIntyre Mines Limited: | |
| - Mines No. 1765 (u/g) and 1771 (strip), combined | 174 |
| Luscar Sterco (1977) Limited: | |
| - Coal Valley (No. 1778) Mine (strip) | 176 |
| COAL ANALYSES - BRITISH COLUMBIA (Bituminous) | 179 |
| Byron Creek Collieries Limited (strip) | 180 |
| Fording Coal Limited (strip) | 182 |
| Kaiser Resources Limited (strip and u/g) | 184 |
| REFERENCES | 188 |

TABLES

| | |
|---|-----|
| 1. Summary - classification of coal by rank | 189 |
| 2. Mines sampled and approximate raw coal production for 1978-1981 | 190 |
| 3. Statistical summary of Canadian commercial coals | 192 |

INTRODUCTION

Complete chemical and physical analytical services are provided by CANMET for departmental and other coal projects, with files dating back to 1910. Consequently, industry and other government departments make direct enquiries about the quality of Canadian coals. Most enquiries originate from current and prospective consumers who need information about the type of coal they use or who want to consider alternative sources of supply and from producers and prospective producers who wish to be informed about available products. As well, enquiries are received from various government departments requiring commercial coal quality information for inventory and regulatory purposes.

To meet these needs, CANMET prepares the "Analysis directory of Canadian commercial coals" which has been updated at various intervals since its original issue in 1948 (1,2,3,4). This supplement covers analyses of coals sampled by CANMET staff in Nova Scotia, New Brunswick, Saskatchewan, Alberta and British Columbia from 1978 to 1981. However, financial and manpower limitations did not permit complete coverage of coal sampling sites in Western Canada in 1980 and 1981.

Individual data sheets for each sample provide a selection of chemical and physical characteristics and identify the samples with regard to their relevant coalfields, seams and mining districts. This information provides a better understanding of variations in coal quality within and between coalfields. The selected format makes it possible to relate this information to the statistical data and summaries of coal industry developments which appear in various publications (5,6) and in certain federal and provincial coal reports dealing with production statistics and resource and reserve assessment (7).

Future presentations of analytical data on commercial coal may involve further changes in format that will provide more information consistent with developing concepts and establishing a national coal inventory for Canada.

Sample collection and preparation were conducted by staff of the regional laboratories of CANMET's Coal Research Laboratories in Sydney, Nova Scotia and Edmonton, Alberta with the cooperation and assistance of mine operators and consumers. Normal mining and preparation plant procedures were followed so that the samples would be unbiased.

All samples were obtained in accordance with recognized techniques and were considered representative, in general, of production on the day of collection.

Sample preparation facilities of the New Brunswick Electric Power Commission were used for partial preparation of samples from the Minto coal-field in New Brunswick. Elsewhere, mobile and base facilities of the regional laboratories were used.

The analyses were conducted by qualified, experienced personnel at the Sydney and Ottawa laboratories using standard procedures of the American Society for Testing and Materials (ASTM). Although sampling procedures and analytical results of individual samples must be accorded a high degree of confidence, the frequency and timing of sampling and selection of samples from a variety of sources - seams, trucks, conveyors, mine sites, preparation plants and delivery points - mean that the data may only be subjected to statistical analyses with some reservations. It must be understood that individual sample results are not necessarily typical or representative of production over long periods and certainly should not be related to specific contract specification requirements. It is hoped that the chemical and physical information will be useful for purposes such as: considering quality aspects of contract specifications, classifying coal by rank, considering environmental hazards, selecting combustion or conversion processes and to a limited extent evaluating coal suitability for metallurgical use. The specific data and their usefulness are discussed briefly below.

The proximate analysis includes mass per cent of moisture, ash, volatile matter and fixed carbon. For anthracitic and low-, medium- and high-volatile A bituminous coals these determinations together with sulphur content and calorific value are presented on the basis of as-received moisture which is characteristically low; however, for high-volatile B and C bituminous, subbituminous and lignite coals, the proximate analysis, sulphur content and calorific value are presented on the basis of equilibrium moisture content.

The as-received moisture is the total of the moisture loss determined on air drying under standard conditions (adherent or surface moisture) and the residual moisture determined as part of the proximate analysis (inherent or oven dried moisture). On the other hand, the equilibrium moisture provides a means of estimating the natural bed moisture exclusive of surface moisture and is essential for classifying low-rank coals.

Data on proximate analysis, sulphur content and calorific value are essential for establishing contract specifications and prices and for quality control of coal deliveries. The moisture, ash, and sulphur contents and the calorific value are subject to improvement by appropriate coal preparation techniques used to upgrade the coal. The fixed carbon and volatile matter contents on a moisture, mineral-matter-free basis, along with the calorific value are essential for classifying coals by rank according to ASTM (Table 1).

The rank of the coal indicates the degree to which the original organic matter has been metamorphosed by temperature and pressure over time to form lignite, subbituminous, bituminous or anthracite coals. Rank is important commercially because within wide limits it signifies the potential use of the coal, subject to considerations related to quality factors such as moisture, ash, sulphur and trace element content.

The ultimate analysis presented on a dry basis includes mass per cent of carbon, hydrogen, sulphur, nitrogen, ash and oxygen, the latter obtained by difference from 100%. This elemental analysis is basic to the selection of coal for conversion and combustion.

The sulphur and trace mercury contents are important considerations related to power plant emissions and regional or national environmental pollution regulations. As well, sulphur is an unwanted constituent in the manufacture of coke for the metallurgical industry.

Sulphur forms reported in this publication are subdivided into three groups: pyritic sulphur, sulfate sulphur and organic sulphur. Sulphur forms are important considerations in coal washability and liquefaction.

Ash fusibility temperatures are determined in a reducing atmosphere and are considered when selecting combustion equipment to avoid or reduce clinkering and slagging problems.

The mineral content of ash is important in furnace design as well as in the design of electrostatic precipitators. Mineral analysis of coal ash together with ash fusibility temperatures allow the prediction of slag viscosity. Mineral analysis of coal ash can also be used to predict the nature of fireside deposits formed in the boiler and characteristics of the fly ash such as electrical resistivity.

The Hardgrove Grindability Index is an indicator of the energy required to grind a coal to the desired fineness; the lower the index the more energy required.

The ASTM Free Swelling Index (FSI) is an indicator of the swelling and caking characteristics of coal and is particularly relevant to selecting metallurgical coals.

The coal analyses are arranged by province. Each page contains a three-line heading stating where possible:

- name of mine operator (not necessarily the lease owner),
- number or name of mine, seam, and coalfield,
- mine location by place name and county or district as appropriate, and province.

For Alberta, the location is also identified by section, township, range and meridian according to the Alberta Land Survey System.

The approximate annual coal production of the major mines in Canada, in thousands of tonnes, is shown in Table 2 for 1978-1981. Statistics are arranged by province, coalfield and company.

A statistical summary of grouped data which is considered useful for an overall understanding of the quality and variability of Canadian commercial coals is presented in Table 3. This summary presents mean, standard deviation and standard error for the results of ash, sulphur and sulphur forms, where the number of samples permit.

CONVERSION FACTORS


The data in this report are given in the International System of Units (SI) where practicable. This represents a transition of units in the series of directory reports. Relevant conversion factors are tabulated below:

a) SI to conventional units

| <u>SI</u> | x | <u>Conversion factor</u> | = | <u>Conventional</u> |
|-------------------------------|---|--------------------------|---|---------------------------------|
| °C | x | (1.8 x °C) + 32 | = | °F |
| kg, kilogram | x | 2.204 622 6 | = | lb (avoirdupois) |
| t, tonne (1000 kg) | x | 1.102 311 | = | t, short ton (2000 lb) |
| t, tonne | x | 0.984 206 5 | = | t, long ton (2 204.622 6 lb) |
| J, joule | x | 0.000 947 8 | = | Btu, British thermal units |
| MJ/kg, megajoule/ kilogram | x | 429.923 | = | Btu/lb |

b) Conventional to SI units

| <u>Conventional</u> | x | <u>Conversion factor</u> | = | <u>SI</u> |
|------------------------------|---|--------------------------|---|-------------------------------|
| °F | x | 5/9 (°F - 32) | = | °C |
| lb (avoirdupois) | x | 0.453 592 3 | = | kg, kilogram |
| t, short ton (2000 lb) | x | 0.907 184 74 | = | t, tonne (1000 kg) |
| t, long ton (2240 lb) | x | 1.016 046 908 8 | = | t, tonne (2 204.622 6 lb) |
| Btu, British thermal unit | x | 1055.06 | = | J, joule |
| Btu/lb | x | 0.002 326 | = | MJ/kg, megajoule/ kilogram |



COAL ANALYSES - NOVA SCOTIA

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | |
|-------------------------------|----------------------------|------------------------|
| Sampling date | 3-5-78 | 19-9-78 |
| Sampling location | Mine Loading Head | Seaboard Power Station |
| Product name | Course Slack | |
| Screen opening, mm | Minus 51, sq | |
| ERL number | 2810-78 | 2809-78 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 7.42 |
| Ash | % | 9.59 |
| Volatile matter | % | 31.81 |
| Fixed carbon | % | 51.18 |
| Sulphur, as rec'd | % | 2.16 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 28.92 |
| Btu/lb | 12 433 | 12 434 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 76.23 |
| Hydrogen | % | 4.99 |
| Sulphur | % | 2.34 |
| Nitrogen | % | 1.29 |
| Ash | % | 10.36 |
| Oxygen, by difference | % | 4.79 |
| Trace mercury | µg/g (ppm) | 0.19 |
| Ash fusibility temperature: | | |
| Initial | °C | 1105 |
| Spherical | °C | 1220 |
| Hemispherical | °C | 1300 |
| Fluid | °C | 1370 |
| Hardgrove grindability index | - | - |
| Free swelling index | 7.0 | 6.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | |
|--------------------|-------------------|------------------------|
| Sampling date | 3-5-78 | 19-9-78 |
| Sampling location | Mine Loading Head | Seaboard Power Station |
| Product name | Course Slack | |
| Screen opening, mm | Minus 51, sq | |
| ERL number | 2810-78 | 2809-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 1.79 | 1.71 |
| Sulfate sulphur | % | 0.07 | 0.01 |
| Organic sulphur | % | 0.48 | 0.46 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.82 | 1.49 |
| Adherent | % | 5.60 | 5.45 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 39.18 | 44.18 |
| Al ₂ O ₃ | | 21.17 | 24.71 |
| Fe ₂ O ₃ | | 28.17 | 21.39 |
| TiO ₂ | | 0.85 | 0.90 |
| P ₂ O ₅ | | 0.00 | 0.00 |
| CaO | | 1.53 | 1.32 |
| MgO | | 1.48 | 1.68 |
| SO ₃ | | 1.50 | 1.13 |
| Na ₂ O | | 0.75 | 0.67 |
| K ₂ O | | 3.00 | 3.54 |
| SrO | | - | - |
| BaO | | - | - |
| LOF | | - | - |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | | | |
|-------------------------------|-----------------------------------|---------|--------|--|--|
| Sampling date | 4-6-80 | | | | |
| Sampling location | Section A Room & Pillar Mining | | | | |
| Product name | Course Slack | | | | |
| Screen opening, mm | Minus 51, sq | | | | |
| ERL number | 3691-80 | 3692-80 | | | |
| Rank of coal | High-volatile A bituminous | | | | |
| Proximate analysis, as rec'd: | | | | | |
| Moisture | % | 2.12 | 1.24 | | |
| Ash | % | 11.24 | 30.31 | | |
| Volatile matter | % | 34.94 | 28.91 | | |
| Fixed carbon | % | 51.70 | 39.54 | | |
| Sulphur, as rec'd: | % | 1.55 | 1.59 | | |
| Calorific value, as rec'd: | | | | | |
| MJ/kg | | 30.17 | 23.62 | | |
| Btu/lb | | 12 969 | 10 154 | | |
| Ultimate analysis, dry basis: | | | | | |
| Carbon | % | 75.40 | 59.49 | | |
| Hydrogen | % | 5.12 | 4.07 | | |
| Sulphur | % | 1.58 | 1.61 | | |
| Nitrogen | % | 2.01 | 1.57 | | |
| Ash | % | 11.48 | 30.69 | | |
| Oxygen, by difference | % | 4.41 | 2.58 | | |
| Trace mercury | µg/g (ppm) | 0.17 | 0.12 | | |
| Ash fusibility temperature: | | | | | |
| Initial | °C | 1210 | 1230 | | |
| Spherical | °C | 1340 | 1345 | | |
| Hemispherical | °C | 1380 | 1390 | | |
| Fluid | °C | 1450 | 1425 | | |
| Hardgrove grindability index | | 57 | 58 | | |
| Free swelling index | | 7.5 | 6.5 | | |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | |
|--------------------------------|-----------------------------------|---------|-------|
| Sampling date | 4-6-80 | | |
| Sampling location | Section A Room & Pillar Mining | | |
| Product name | Course Slack | | |
| Screen opening, mm | Minus 51, sq | | |
| ERL number | 3691-80 | 3692-80 | |
| Sulphur Forms (dry basis): | | | |
| Pyritic sulphur | % | 1.10 | 1.11 |
| Sulfate sulphur | % | 0.00 | 0.00 |
| Organic sulphur | % | 0.48 | 0.50 |
| Moisture (as rec'd): | | | |
| Inherent | % | 2.12 | 1.24 |
| Adherent | % | - | - |
| Ash analysis, %: | | | |
| SiO ₂ | | 47.61 | 57.16 |
| Al ₂ O ₃ | | 23.83 | 20.79 |
| Fe ₂ O ₃ | | 17.68 | 12.15 |
| TiO ₂ | | 0.88 | 0.99 |
| P ₂ O ₅ | | 0.14 | 0.21 |
| CaO | | 1.50 | 0.86 |
| MgO | | 1.37 | 1.59 |
| SO ₃ | | 1.12 | 0.46 |
| Na ₂ O | | 0.65 | 0.55 |
| K ₂ O | | 3.25 | 3.03 |
| SrO | | 0.02 | 0.02 |
| BaO | | 0.14 | 0.13 |
| LOF | | 0.00 | 0.42 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|---|---------------|--------|
| Sampling date | 13-6-80 | | |
| Sampling location | Coal Preparation Plant Victoria Junction | | |
| Product name | Raw Feed | Course Screen | |
| Screen opening, mm | 38 x 0, sq | 38 x 28 mesh | |
| ERL number | 3712-80 | 3711-80 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 5.36 | 5.34 |
| Ash | % | 16.83 | 2.20 |
| Volatile matter | % | 31.14 | 36.45 |
| Fixed carbon | % | 46.67 | 56.01 |
| Sulphur, as rec'd | % | 1.66 | 1.18 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 27.44 | 33.05 |
| Btu/lb | | 11 797 | 14 210 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 68.78 | 83.44 |
| Hydrogen | % | 4.76 | 5.92 |
| Sulphur | % | 1.75 | 1.25 |
| Nitrogen | % | 1.65 | 1.88 |
| Ash | % | 17.78 | 2.32 |
| Oxygen, by difference | % | 5.28 | 5.19 |
| Trace mercury | µg/g (ppm) | 0.13 | 0.10 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1180 | 1045 |
| Spherical | °C | 1305 | 1120 |
| Hemispherical | °C | 1360 | 1177 |
| Fluid | °C | 1380 | 1266 |
| Hardgrove grindability index | | 62 | 61 |
| Free swelling index | | 6.0 | 7.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | |
|--------------------|---|---------------|
| Sampling date | 13-6-80 | |
| Sampling location | Coal Preparation Plant Victoria Junction | |
| Product name | Raw Feed | Course Screen |
| Screen opening, mm | 38 x 0, sq | 38 x 28 mesh |
| ERL number | 3712-80 | 3711-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 1.50 | 0.67 |
| Sulfate sulphur | % | 0.02 | 0.00 |
| Organic sulphur | % | 0.23 | 0.58 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.40 | 1.32 |
| Adherent | % | 3.96 | 4.02 |

Ash analysis, %:

| | |
|--------------------------------|-------|
| SiO ₂ | 47.98 |
| Al ₂ O ₃ | 24.66 |
| Fe ₂ O ₃ | 16.14 |
| TiO ₂ | 0.86 |
| P ₂ O ₅ | 0.08 |
| CaO | 1.29 |
| MgO | 1.93 |
| SO ₃ | 1.10 |
| Na ₂ O | 0.82 |
| K ₂ O | 3.77 |
| SrO | 0.02 |
| BaO | 0.00 |
| LOF | 0.28 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | |
|-------------------------------|----------------------------|---------|
| Sampling date | 3-6-80 | 13-5-80 |
| Sampling location | Mine Conveyor | |
| Product name | Crushed Slack | |
| Screen opening, mm | Minus 51, sq | |
| ERL number | 3693-80 | 3695-80 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 1.51 |
| Ash | % | 18.63 |
| Volatile matter | % | 32.60 |
| Fixed carbon | % | 47.26 |
| Sulphur, as rec'd | % | 2.00 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 31.72 |
| Btu/lb | | 13 637 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 68.34 |
| Hydrogen | % | 4.60 |
| Sulphur | % | 2.03 |
| Nitrogen | % | 1.61 |
| Ash | % | 18.92 |
| Oxygen, by difference | % | 4.50 |
| Trace mercury | µg/g (ppm) | 0.18 |
| Ash fusibility temperature: | | |
| Initial | °C | 1230 |
| Spherical | °C | 1345 |
| Hemispherical | °C | 1390 |
| Fluid | °C | 1425 |
| Hardgrove grindability index | | 60 |
| Free swelling index | | 7.5 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | |
|--------------------|---------------|---------|
| Sampling date | 3-6-80 | 13-5-80 |
| Sampling location | Mine Conveyor | |
| Product name | Crushed Slack | |
| Screen opening, mm | Minus 51, sq | |
| ERL number | 3693-80 | 3695-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 1.25 | 0.84 |
| Sulfate sulphur | % | 0.00 | 0.01 |
| Organic sulphur | % | 0.78 | 0.47 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.51 | 2.19 |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 47.74 | 36.12 |
| Al ₂ O ₃ | | 24.88 | 20.22 |
| Fe ₂ O ₃ | | 15.85 | 24.53 |
| TiO ₂ | | 0.81 | 0.73 |
| P ₂ O ₅ | | 0.09 | 0.12 |
| CaO | | 1.07 | 5.41 |
| MgO | | 1.69 | 1.32 |
| SO ₃ | | 1.06 | 5.82 |
| Na ₂ O | | 0.81 | 0.77 |
| K ₂ O | | 3.92 | 2.27 |
| SrO | | 0.02 | 0.01 |
| BaO | | 0.14 | 0.06 |
| LOF | | 0.00 | 0.00 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|--------------|----------------------|
| Sampling date | 15-7-80 | 15-7-80 | 15-7-80 |
| Sampling location | (Gantry) Section A | (Silo) | Lingan Power Station |
| Product name | | Course Slack | |
| Screen opening, mm | | Minus 51, sq | |
| ERL number | 4162-80 | 4163-80 | 4164-80 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 3.16 | 7.35 |
| Ash | % | 7.91 | 25.40 |
| Volatile matter | % | 35.25 | 27.08 |
| Fixed carbon | % | 53.68 | 40.17 |
| Sulphur, as rec'd | % | 2.77 | 1.70 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 30.87 | 23.41 |
| Btu/lb | | 13 271 | 10 067 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 76.37 | 61.67 |
| Hydrogen | % | 5.41 | 4.41 |
| Sulphur | % | 2.86 | 1.84 |
| Nitrogen | % | 1.46 | 1.13 |
| Ash | % | 8.17 | 27.41 |
| Oxygen, by difference | % | 5.73 | 3.50 |
| Trace mercury | µg/g (ppm) | 0.21 | 0.10 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1060 | 1250 |
| Spherical | °C | 1130 | 1345 |
| Hemispherical | °C | 1250 | 1415 |
| Fluid | °C | 1330 | 1450 |
| Hardgrove grindability index | | 58 | 60 |
| Free swelling index | | 7.0 | 7.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | |
|--------------------------------|-----------------------|--------------|-------------------------|
| Sampling date | 15-7-80 | 15-7-80 | 15-7-80 |
| Sampling location | (Gantry) Section A | (Silo) | Lingan Power Station |
| Product name | | Course Slack | |
| Screen opening, mm | | Minus 51, sq | |
| ERL number | 4162-80 | 4163-80 | 4164-80 |
| Sulphur Forms (dry basis): | | | |
| Pyritic sulphur | % | 1.74 | 0.81 |
| Sulfate sulphur | % | 0.06 | 0.01 |
| Organic sulphur | % | 1.06 | 0.40 |
| Moisture (as rec'd): | | | |
| Inherent | % | 2.19 | 1.50 |
| Adherent | % | 0.97 | 2.43 |
| Ash analysis, %: | | | |
| SiO ₂ | | 33.46 | 46.27 |
| Al ₂ O ₃ | | 18.83 | 23.38 |
| Fe ₂ O ₃ | | 37.48 | 20.92 |
| TiO ₂ | | 0.84 | 0.87 |
| P ₂ O ₅ | | 0.07 | 0.11 |
| CaO | | 3.15 | 1.48 |
| MgO | | 0.87 | 1.54 |
| SO ₃ | | 2.73 | 1.52 |
| Na ₂ O | | 0.53 | 0.71 |
| K ₂ O | | 1.67 | 3.31 |
| SrO | | 0.00 | 0.02 |
| BaO | | 0.00 | 0.06 |
| LOF | | 0.80 | 0.00 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|-------------|--------------|
| Sampling date | 11-7-80 | | |
| Sampling location | Wash Plant, Sydney Mines | | |
| Product name | Egg | Nut | Course Slack |
| Screen opening, mm | Plus 44, rd | 44 x 64, rd | Minus 44, rd |
| ERL number | 4168-80 | 4169-80 | 4170-80 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 4.95 | 5.72 |
| Ash | % | 3.88 | 3.59 |
| Volatile matter | % | 35.49 | 36.00 |
| Fixed carbon | % | 55.68 | 54.69 |
| Sulphur, equil | % | 2.30 | 2.33 |
| Calorific value, as rec'd: | | | |
| | MJ/kg | 31.96 | 31.70 |
| | Btu/lb | 13 739 | 13 627 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 80.28 | 81.26 |
| Hydrogen | % | 5.74 | 5.84 |
| Sulphur | % | 2.42 | 2.47 |
| Nitrogen | % | 1.51 | 1.53 |
| Ash | % | 4.08 | 3.81 |
| Oxygen, by difference | % | 5.97 | 5.09 |
| Trace mercury | µg/g (ppm) | 0.13 | 0.15 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1115 | 1100 |
| Spherical | °C | 1195 | 1165 |
| Hemispherical | °C | 1220 | 1240 |
| Fluid | °C | 1280 | 1315 |
| Hardgrove grindability index | | 56 | 56 |
| Free swelling index | | 6.5 | 4.5 |
| Notes: | | | 7.0 |

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | |
|-----------------------------------|--------------------------|-------------|--------------|
| Sampling date | 11-7-80 | | |
| Sampling location | Wash Plant, Sydney Mines | | |
| Product name | Egg | Nut | Course Slack |
| Screen opening, mm | Plus 44, rd | 44 x 64, rd | Minus 44, rd |
| ERL number | 4168-80 | 4169-80 | 4170-80 |
| Sulphur Forms (dry basis): | | | |
| Pyritic sulphur | % | 1.73 | 1.56 |
| Sulfate sulphur | % | 0.01 | 0.04 |
| Organic sulphur | % | 0.68 | 0.87 |
| Moisture (as rec'd): | | | |
| Inherent | % | 2.42 | 2.72 |
| Adherent | % | 2.53 | 3.00 |
| Ash analysis, %: | | | |
| SiO ₂ | | 17.78 | 22.85 |
| Al ₂ O ₃ | | 11.21 | 14.03 |
| Fe ₂ O ₃ | | 62.81 | 57.98 |
| TiO ₂ | | 0.50 | 0.68 |
| P ₂ O ₅ | | 0.51 | 0.53 |
| CaO | | 2.73 | 1.06 |
| MgO | | 0.52 | 0.41 |
| SO ₃ | | 1.49 | 0.49 |
| Na ₂ O | | 0.63 | 0.67 |
| K ₂ O | | 0.43 | 0.72 |
| SrO | - | - | 0.02 |
| BaO | - | - | 0.00 |
| LOF | - | - | 0.00 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|---------------|--------|
| Sampling date | 11-7-80 | | |
| Sampling location | Wash Plant, Sydney Mines | | |
| Product name | Pea | Fines | |
| Screen opening, mm | 19 x 64, rd | Minus 6.4, rd | |
| ERL number | 4171-80 | 4172-80 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 10.51 | 7.55 |
| Ash | % | 4.81 | 11.77 |
| Volatile matter | % | 33.39 | 31.11 |
| Fixed carbon | % | 51.29 | 49.57 |
| Sulphur, as rec'd | % | 3.04 | 1.57 |
| Calorific value, as rec'd: | | | |
| | MJ/kg | 28.76 | 28.02 |
| | Btu/lb | 12 366 | 12 047 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 64.66 | 77.01 |
| Hydrogen | % | 4.28 | 5.42 |
| Sulphur | % | 3.41 | 1.70 |
| Nitrogen | % | 1.22 | 1.48 |
| Ash | % | 5.38 | 12.73 |
| Oxygen, by difference | % | 21.05 | 1.66 |
| Trace mercury | µg/g (ppm) | 0.14 | 0.13 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1105 | 1165 |
| Spherical | °C | 1195 | 1350 |
| Hemispherical | °C | 1280 | 1365 |
| Fluid | °C | 1395 | 1400 |
| Hardgrove grindability index | | 59 | 58 |
| Free swelling index | | 4.5 | 6.5 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | |
|--------------------|---------------------------|---------------|
| Sampling date | 11-7-80 | |
| Sampling location | Wash Plant, Sydney Mines | |
| Product name | Pea | Fines |
| Screen opening, mm | 19 x 6 $\frac{1}{4}$, rd | Minus 6.4, rd |
| ERL number | 4171-80 | 4172-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 1.94 | 1.18 |
| Sulfate sulphur | % | 0.08 | 0.02 |
| Organic sulphur | % | 1.39 | 0.50 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 4.58 | 2.58 |
| Adherent | % | 5.93 | 4.97 |

Ash analysis, %:

| | |
|--------------------------------|-------|
| SiO ₂ | 25.92 |
| Al ₂ O ₃ | 15.31 |
| Fe ₂ O ₃ | 51.83 |
| TiO ₂ | 0.74 |
| P ₂ O ₅ | 0.21 |
| CaO | 1.66 |
| MgO | 0.78 |
| SO ₃ | 1.60 |
| Na ₂ O | 0.68 |
| K ₂ O | 0.88 |
| SrO | 0.03 |
| BaO | 0.00 |
| LOF | 0.00 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | |
|---------------------------------|----------------------------|--------|---------|
| Sampling date | 24-3-81 | | |
| Sampling location | (Gantry) | (Silo) | |
| | Section A | | |
| Product name | Mine Run | | |
| Screen opening, mm | | | |
| ERL number | 3340-81 | | 3341-81 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 4.31 | 3.26 |
| Ash | % | 5.74 | 23.41 |
| Volatile matter | % | 34.02 | 28.11 |
| Fixed carbon | % | 55.93 | 45.22 |
| Sulphur, as rec'd | % | 1.74 | 2.18 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 31.22 | 25.46 |
| Btu/lb | | 13 425 | 10 948 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 77.41 | 59.26 |
| Hydrogen | % | 4.82 | 3.80 |
| Sulphur | % | 1.82 | 2.25 |
| Nitrogen | % | 1.27 | 0.94 |
| Ash | % | 6.00 | 24.20 |
| Oxygen, by difference | % | 8.68 | 9.55 |
| Trace mercury μg/g (ppm) | | 0.22 | 0.15 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1024 | 1227 |
| Spherical | °C | 1135 | 1352 |
| Hemispherical | °C | 1143 | 1407 |
| Fluid | °C | 1207 | 1457 |
| Hardgrove grindability index | | 58 | 58 |
| Free swelling index | | 7.0 | 6.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | |
|--------------------|-----------|---------|
| Sampling date | 24-3-81 | |
| Sampling location | (Gantry) | (Silo) |
| | Section A | |
| Product name | Mine Run | |
| Screen opening, mm | | |
| ERL number | 3340-81 | 3341-81 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 1.20 | 1.91 |
| Sulfate sulphur | % | 0.01 | 0.02 |
| Organic sulphur | % | 0.61 | 0.32 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 0.94 | 0.87 |
| Adherent | % | 3.37 | 2.39 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 25.01 | 51.41 |
| Al ₂ O ₃ | | 14.29 | 25.95 |
| Fe ₂ O ₃ | | 32.76 | 13.81 |
| TiO ₂ | | 0.62 | 0.88 |
| P ₂ O ₅ | | 0.11 | 0.05 |
| CaO | | 10.81 | 0.78 |
| MgO | | 0.96 | 1.92 |
| SO ₃ | | 9.70 | 0.92 |
| Na ₂ O | | 0.74 | 0.74 |
| K ₂ O | | 1.39 | 4.20 |
| SrO | | 0.01 | 0.01 |
| BaO | | 0.00 | 0.00 |
| LOF | | 4.49 | 0.81 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
No. 26 Colliery; Harbour Seam; Sydney Coalfield
Glace Bay, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|--------------|--------|
| Sampling date | 21-11-80 | | |
| Sampling location | Mine | | |
| Product name | Screen | Slack | |
| Screen opening, mm | Plus 75, rd | Minus 75, rd | |
| ERL number | 2454-81 | 2453-81 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 0.61 | 5.51 |
| Ash | % | 4.95 | 12.90 |
| Volatile matter | % | 32.33 | 28.90 |
| Fixed carbon | % | 62.11 | 52.69 |
| Sulphur, as rec'd | % | 0.70 | 0.68 |
| Calorific value, as rec'd: | | | |
| | MJ/kg | 33.93 | 29.07 |
| | Btu/lb | 11 587 | 12 500 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 82.35 | 74.66 |
| Hydrogen | % | 5.49 | 4.93 |
| Sulphur | % | 0.70 | 0.72 |
| Nitrogen | % | 1.75 | 1.49 |
| Ash | % | 4.98 | 13.65 |
| Oxygen, by difference | % | 4.73 | 4.55 |
| Trace mercury | µg/g (ppm) | 0.06 | 0.07 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1121 | 1138 |
| Spherical | °C | 1171 | 1288 |
| Hemispherical | °C | 1182 | 1315 |
| Fluid | °C | 1260 | 1338 |
| Hardgrove grindability index | | 65 | 70 |
| Free swelling index | | 6.5 | 6.5 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 No. 26 Colliery; Harbour Seam; Sydney Coalfield
 Glace Bay, Cape Breton County, Nova Scotia

| | | |
|--------------------|-------------|--------------|
| Sampling date | 21-11-80 | |
| Sampling location | Mine | |
| Product name | Screen | Slack |
| Screen opening, mm | Plus 75, rd | Minus 75, rd |
| ERL number | 2454-81 | 2453-81 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.38 | 0.54 |
| Sulfate sulphur | % | 0.00 | 0.00 |
| Organic sulphur | % | 0.32 | 0.18 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 0.61 | 0.64 |
| Adherent | % | - | 4.87 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 38.72 | 48.76 |
| Al ₂ O ₃ | | 15.67 | 21.15 |
| Fe ₂ O ₃ | | 34.73 | 16.96 |
| TiO ₂ | | 0.73 | 0.93 |
| P ₂ O ₅ | | 0.18 | 0.15 |
| CaO | | 2.09 | 3.18 |
| MgO | | 1.84 | 1.49 |
| SO ₃ | | 2.27 | 2.90 |
| Na ₂ O | | 0.58 | 0.97 |
| K ₂ O | | 1.67 | 3.00 |
| SrO | | 0.00 | 0.03 |
| BaO | | 0.00 | 0.07 |
| LOF | | 0.42 | 0.85 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 No. 26 Colliery; Harbour Seam; Sydney Coalfield
 Glace Bay, Cape Breton County, Nova Scotia

| | | | |
|---|----------------------------|--------------|--------|
| Sampling date | 25-3-81 | | |
| Sampling location | Mine | | |
| Product name | Screen | Slack | |
| Screen opening, mm | Plus 75, rd | Minus 75, rd | |
| ERL number | 3342-81 | 3343-81 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 0.46 | 3.62 |
| Ash | % | 3.41 | 7.28 |
| Volatile matter | % | 32.26 | 30.41 |
| Fixed carbon | % | 63.87 | 58.69 |
| Sulphur, as rec'd | % | 0.90 | 0.93 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 34.59 | 31.31 |
| Btu/lb | | 14 872 | 13 462 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 83.32 | 78.73 |
| Hydrogen | % | 5.20 | 4.89 |
| Sulphur | % | 0.90 | 0.96 |
| Nitrogen | % | 1.31 | 1.37 |
| Ash | % | 3.43 | 7.55 |
| Oxygen, by difference | % | 5.84 | 6.49 |
| Trace mercury μg/g (ppm) | | 0.07 | 0.06 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1093 | 1107 |
| Spherical | °C | 1268 | 1229 |
| Hemispherical | °C | 1346 | 1324 |
| Fluid | °C | 1357 | 1332 |
| Hardgrove grindability index | | 69 | 68 |
| Free swelling index | | 7.5 | 7.5 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 No. 26 Colliery; Harbour Seam; Sydney Coalfield
 Glace Bay, Cape Breton County, Nova Scotia

| | | |
|--------------------|-------------|--------------|
| Sampling date | 25-3-81 | |
| Sampling location | Mine | |
| Product name | Screen | Slack |
| Screen opening, mm | Plus 75, rd | Minus 75, rd |
| ERL number | 3342-81 | 3343-81 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.32 | 0.46 |
| Sulfate sulphur | % | 0.00 | 0.01 |
| Organic sulphur | % | 0.58 | 0.49 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 0.46 | 0.84 |
| Adherent | % | - | 2.78 |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 39.33 | 43.01 |
| Al ₂ O ₃ | 23.16 | 21.47 |
| Fe ₂ O ₃ | 27.84 | 20.79 |
| TiO ₂ | 1.14 | 0.88 |
| P ₂ O ₅ | 0.17 | 0.19 |
| CaO | 1.43 | 3.33 |
| MgO | 1.46 | 1.79 |
| SO ₃ | 1.57 | 3.32 |
| Na ₂ O | 0.91 | 1.07 |
| K ₂ O | 1.67 | 2.73 |
| SrO | 0.01 | 0.02 |
| BaO | 0.00 | 0.02 |
| LOF | 1.16 | 1.55 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 No. 26 Colliery; Harbour Seam; Sydney Coalfield
 Glace Bay, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|--------------|--------|
| Sampling date | 15-5-80 | | |
| Sampling location | Mine | | |
| Product name | Screen | Slack | |
| Screen opening, mm | Plus 51, sq | Minus 51, sq | |
| ERL number | 3696-80 | 3697-80 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 0.99 | 1.04 |
| Ash | % | 8.74 | 4.63 |
| Volatile matter | % | 32.52 | 33.60 |
| Fixed carbon | % | 57.75 | 60.73 |
| Sulphur, as rec'd | % | 1.38 | 0.59 |
| Calorific value, as rec'd: | | | |
| | MJ/kg | 32.19 | 34.07 |
| | Btu/lb | 13 838 | 14 648 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 79.31 | 83.35 |
| Hydrogen | % | 5.21 | 5.46 |
| Sulphur | % | 1.39 | 0.60 |
| Nitrogen | % | 1.84 | 2.01 |
| Ash | % | 8.83 | 4.68 |
| Oxygen, by difference | % | 3.42 | 3.90 |
| Trace mercury | µg/g (ppm) | 0.24 | 0.03 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1105 | 1115 |
| Spherical | °C | 1180 | 1195 |
| Hemispherical | °C | 1240 | 1270 |
| Fluid | °C | 1320 | 1315 |
| Hardgrove grindability index | | 69 | 67 |
| Free swelling index | | 8.0 | 6.5 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 No. 26 Colliery; Harbour Seam; Sydney Coalfield
 Glace Bay, Cape Breton County, Nova Scotia

| | | |
|--------------------|-------------|--------------|
| Sampling date | 15-5-80 | |
| Sampling location | Mine | |
| Product name | Screen | Slack |
| Screen opening, mm | Plus 51, sq | Minus 51, sq |
| ERL number | 3696-80 | 3697-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.85 | 0.13 |
| Sulfate sulphur | % | 0.00 | 0.00 |
| Organic sulphur | % | 0.54 | 0.47 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 0.99 | 1.04 |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 43.95 | 39.80 |
| Al ₂ O ₃ | | 19.96 | 22.38 |
| Fe ₂ O ₃ | | 25.15 | 26.32 |
| TiO ₂ | | 0.82 | 1.04 |
| P ₂ O ₅ | | 0.09 | 0.12 |
| CaO | | 1.41 | 1.83 |
| MgO | | 1.46 | 1.97 |
| SO ₃ | | 1.28 | 1.59 |
| Na ₂ O | | 0.68 | 0.91 |
| K ₂ O | | 2.53 | 2.12 |
| SrO | | 0.01 | 0.02 |
| BaO | | 0.04 | 0.00 |
| LOF | | 0.28 | 0.14 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan/No. 26 Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|---|--------------|--------|
| Sampling date | 13-6-80 | | |
| Sampling location | Coal Preparation Plant Victoria Junction | | |
| Product name | Metallurgical Coal | Thermal Coal | |
| Screen opening, mm | Minus 38, sq. | Minus 38, sq | |
| ERL number | 3707-80 | 3708-80 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 8.06 | 4.17 |
| Ash | % | 2.42 | 3.29 |
| Volatile matter | % | 32.04 | 26.31 |
| Fixed carbon | % | 57.48 | 66.23 |
| Sulphur, as rec'd | % | 0.81 | 1.48 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 32.23 | 32.42 |
| Btu/lb | | 13 854 | 13 937 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 84.66 | 82.78 |
| Hydrogen | % | 5.65 | 5.69 |
| Sulphur | % | 0.88 | 1.55 |
| Nitrogen | % | 1.98 | 1.88 |
| Ash | % | 2.63 | 3.43 |
| Oxygen, by difference | % | 4.21 | 4.67 |
| Trace mercury | µg/g (ppm) | 0.07 | 0.12 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1100 | 1065 |
| Spherical | °C | 1190 | 1125 |
| Hemispherical | °C | 1260 | 1175 |
| Fluid | °C | 1370 | 1225 |
| Hardgrove grindability index | | 61 | 58 |
| Free swelling index | | 8.5 | 7.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan/No. 26 Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | |
|--------------------|---|--------------|
| Sampling date | 13-6-80 | |
| Sampling location | Coal Preparation Plant Victoria Junction | |
| Product name | Metallurgical Coal | Thermal Coal |
| Screen opening, mm | Minus 38, sq | Minus 38, sq |
| ERL number | 3707-80 | 3708-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.29 | 0.86 |
| Sulfate sulphur | % | 0.01 | 0.01 |
| Organic sulphur | % | 0.58 | 0.68 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.06 | 1.24 |
| Adherent | % | 7.00 | 2.93 |

Ash analysis, %:

| | |
|-------------------------|-------|
| SiO_2 | 28.95 |
| Al_2O_3 | 17.67 |
| Fe_2O_3 | 45.67 |
| TiO_2 | 0.98 |
| P_2O_5 | 0.18 |
| CaO | 1.49 |
| MgO | 0.88 |
| SO_3 | 1.18 |
| Na_2O | 0.72 |
| K_2O | 0.96 |
| SrO | 0.00 |
| BaO | 0.00 |
| LOF | 0.06 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan/No. 26 Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|---|---------------|-------|
| Sampling date | 13-6-80 | | |
| Sampling location | Coal Preparation Plant Victoria Junction | | |
| Product name | Fines | Course Reject | |
| Screen opening, mm | Minus 6.4, sq | 38 x 28 Mesh | |
| ERL number | 3713-80 | 3714-80 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 13.72 | 3.16 |
| Ash | % | 3.57 | 39.25 |
| Volatile matter | % | 29.43 | 22.65 |
| Fixed carbon | % | 53.28 | 34.94 |
| Sulphur, as rec'd | % | 1.09 | 1.42 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 29.77 | - |
| Btu/lb | | 12 711 | - |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 81.65 | 47.94 |
| Hydrogen | % | 5.63 | 3.23 |
| Sulphur | % | 1.26 | 1.47 |
| Nitrogen | % | 1.74 | 1.27 |
| Ash | % | 4.14 | 40.53 |
| Oxygen, by difference | % | 5.58 | 5.56 |
| Trace mercury | μg/g (ppm) | 0.10 | 0.90 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1090 | 1205 |
| Spherical | °C | 1190 | 1300 |
| Hemispherical | °C | 1280 | 1350 |
| Fluid | °C | 1345 | 1365 |
| Hardgrove grindability index | | - | - |
| Free swelling index | | 8.0 | 1.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Lingan/No. 26 Mine; Harbour Seam; Sydney Coalfield
 Lingan, Cape Breton County, Nova Scotia

| | | |
|--------------------|---|---------------|
| Sampling date | 13-6-80 | |
| Sampling location | Coal Preparation Plant Victoria Junction | |
| Product name | Fines | Course Reject |
| Screen opening, mm | Minus 6.4, sq | 38 x 28 Mesh |
| ERL number | 3713-80 | 3714-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|---|
| Pyritic sulphur | % | 0.68 | - |
| Sulfate sulphur | % | 0.00 | - |
| Organic sulphur | % | 0.58 | - |

Moisture (as rec'd):

| | | | |
|----------------|---|-------|------|
| Inherent | % | 1.22 | 1.34 |
| Adherent | % | 12.50 | 1.82 |

Ash analysis, %:

| | |
|--------------------------------|-------|
| SiO ₂ | 45.58 |
| Al ₂ O ₃ | 25.27 |
| Fe ₂ O ₃ | 11.68 |
| TiO ₂ | 1.00 |
| P ₂ O ₅ | 0.08 |
| CaO | 2.42 |
| MgO | 1.60 |
| SO ₃ | 2.13 |
| Na ₂ O | 0.56 |
| K ₂ O | 3.90 |
| SrO | 0.03 |
| BaO | 0.00 |
| LOF | 0.49 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|----------|----------|
| Sampling date | 12-5-80 | 15-7-80 | 23-3-81 |
| Sampling location | Mine | Mine | Mine |
| Product name | Mine Run | Mine Run | Mine Run |
| Screen opening, mm | | | |
| ERL number | 3694-80 | 4165-80 | 3329-81 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 9.35 | 4.31 |
| Ash | % | 13.83 | 10.02 |
| Volatile matter | % | 31.35 | 39.98 |
| Fixed carbon | % | 45.47 | 51.69 |
| Sulphur, equil | % | 3.64 | 5.22 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 25.71 | 26.82 |
| Btu/lb | | 11 054 | 11 531 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 68.44 | 73.25 |
| Hydrogen | % | 4.53 | 5.09 |
| Sulphur | % | 4.01 | 5.46 |
| Nitrogen | % | 1.59 | 1.21 |
| Ash | % | 15.26 | 10.47 |
| Oxygen, by difference | % | 6.17 | 5.42 |
| Trace mercury | µg/g (ppm) | 0.23 | 0.19 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1070 | 1095 |
| Spherical | °C | 1170 | 1170 |
| Hemispherical | °C | 1260 | 1230 |
| Fluid | °C | 1320 | 1350 |
| Hardgrove grindability index | | 61 | 62 |
| Free swelling index | | 3.5 | 3.5 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | | |
|--------------------|----------|----------|----------|
| Sampling date | 12-5-80 | 15-7-80 | 23-3-81 |
| Sampling location | Mine | Mine | Mine |
| Product name | Mine Run | Mine Run | Mine Run |
| Screen opening, mm | | | |
| ERL number | 3694-80 | 4165-80 | 3329-81 |

Sulphur Forms (dry basis):

| | | | | |
|-----------------------|---|------|------|------|
| Pyritic sulphur | % | 2.60 | 3.85 | 2.67 |
| Sulfate sulphur | % | 0.04 | 0.19 | 0.06 |
| Organic sulphur | % | 1.37 | 1.42 | 1.53 |

Moisture (as rec'd):

| | | | | |
|----------------|---|------|------|------|
| Inherent | % | 3.02 | 4.31 | 2.28 |
| Adherent | % | 6.33 | - | 4.49 |

Ash analysis, %:

| | | | | |
|--------------------------------|--|-------|-------|-------|
| SiO ₂ | | 39.29 | 26.27 | 40.00 |
| Al ₂ O ₃ | | 22.87 | 14.85 | 18.63 |
| Fe ₂ O ₃ | | 28.36 | 51.08 | 32.11 |
| TiO ₂ | | 0.95 | 0.57 | 0.71 |
| P ₂ O ₅ | | 0.36 | 0.22 | 0.20 |
| CaO | | 2.55 | 1.96 | 2.02 |
| MgO | | 0.73 | 0.91 | 1.07 |
| SO ₃ | | 2.96 | 1.74 | 1.49 |
| Na ₂ O | | 0.60 | 0.47 | 0.95 |
| K ₂ O | | 1.33 | 1.21 | 1.70 |
| SrO | | 0.02 | 0.00 | 0.03 |
| BaO | | 0.11 | 0.00 | 0.00 |
| LOF | | 0.12 | 0.18 | 0.11 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | |
|-------------------------------|------------------------------------|----------|
| Sampling date | 16-7-80 | 16-3-81 |
| Sampling location | Seaboard Generating Station (NSPC) | |
| Product name | Mine Run | Mine Run |
| Screen opening, mm | | |
| ERL number | 4173-80 | 3336-81 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 4.66 |
| Ash | % | 10.59 |
| Volatile matter | % | 33.47 |
| Fixed carbon | % | 51.28 |
| Sulphur, as rec'd | % | 4.03 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 28.98 |
| Btu/lb | | 12 460 |
| | | 23.50 |
| | | 10 104 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 72.76 |
| Hydrogen | % | 5.03 |
| Sulphur | % | 4.23 |
| Nitrogen | % | 1.53 |
| Ash | % | 11.11 |
| Oxygen, by difference | % | 5.34 |
| Trace mercury | µg/g (ppm) | 0.14 |
| Ash fusibility temperature: | | |
| Initial | °C | 1060 |
| Spherical | °C | 1195 |
| Hemispherical | °C | 1310 |
| Fluid | °C | 1350 |
| Hardgrove grindability index | | 63 |
| Free swelling index | | 3.0 |
| Notes: | | 6.5 |

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | |
|--------------------|------------------------------------|----------|
| Sampling date | 16-7-80 | 16-3-81 |
| Sampling location | Seaboard Generating Station (NSPC) | |
| Product name | Mine Run | Mine Run |
| Screen opening, mm | | |
| ERL number | 4173-80 | 3336-81 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 2.89 | 3.94 |
| Sulfate sulphur | % | 0.19 | 0.61 |
| Organic sulphur | % | 1.15 | 0.33 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 4.66 | 1.23 |
| Adherent | % | - | 7.64 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 34.50 | 42.19 |
| Al ₂ O ₃ | | 19.48 | 22.48 |
| Fe ₂ O ₃ | | 36.94 | 27.54 |
| TiO ₂ | | 0.72 | 0.81 |
| P ₂ O ₅ | | 0.09 | 0.14 |
| CaO | | 2.13 | 1.20 |
| MgO | | 1.53 | 0.83 |
| SO ₃ | | 2.06 | 1.44 |
| Na ₂ O | | 0.51 | 0.53 |
| K ₂ O | | 1.65 | 2.35 |
| SrO | | 0.02 | 0.03 |
| BaO | | 0.00 | 0.00 |
| LOF | | 0.00 | 0.70 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | |
|-------------------------------|----------------------------|--------------|
| Sampling date | 21-5-80 | |
| Sampling location | Wash Plant, Sydney Mines | |
| Product name | Egg | Nut |
| Screen opening, mm | Plus 44, rd | 44 x 6.4, rd |
| ERL number | 3678-80 | 3679-80 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 6.01 |
| Ash | % | 5.70 |
| Volatile matter | % | 36.23 |
| Fixed carbon | % | 52.06 |
| Sulphur, as rec'd | % | 2.88 |
| Calorific value, as rec'd: | | |
| MJ/kg | 30.28 | 29.08 |
| Btu/lb | 13 018 | 12 501 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 76.52 |
| Hydrogen | % | 5.17 |
| Sulphur | % | 3.07 |
| Nitrogen | % | 1.64 |
| Ash | % | 6.06 |
| Oxygen, by difference | % | 7.54 |
| Trace mercury | µg/g (ppm) | 0.26 |
| Ash fusibility temperature: | | |
| Initial | °C | 1060 |
| Spherical | °C | 1125 |
| Hemispherical | °C | 1170 |
| Fluid | °C | 1370 |
| Hardgrove grindability index | | 52 |
| Free swelling index | | 6.5 |
| Notes: | | 5.5 |

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | |
|--------------------|--------------------------|--------------|
| Sampling date | 21-5-80 | |
| Sampling location | Wash Plant, Sydney Mines | |
| Product name | Egg | Nut |
| Screen opening, mm | Plus 44, rd | 44 x 6.4, rd |
| ERL number | 3678-80 | 3679-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 2.08 | 1.92 |
| Sulfate sulphur | % | 0.00 | 0.11 |
| Organic sulphur | % | 0.99 | 1.13 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 3.41 | 4.53 |
| Adherent | % | 2.60 | 3.00 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 27.59 | 30.68 |
| Al ₂ O ₃ | | 11.99 | 20.12 |
| Fe ₂ O ₃ | | 16.99 | 41.16 |
| TiO ₂ | | 0.83 | 0.87 |
| P ₂ O ₅ | | 0.23 | 0.16 |
| CaO | | 1.45 | 1.84 |
| MgO | | 0.63 | 0.57 |
| SO ₃ | | 1.00 | 1.29 |
| Na ₂ O | | 0.73 | 0.64 |
| K ₂ O | | 0.69 | 1.11 |
| SrO | | 0.02 | 0.03 |
| BaO | | 0.00 | 0.00 |
| LOF | | 0.04 | 0.12 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|--------------|--------|
| Sampling date | 21-5-80 | | |
| Sampling location | Wash Plant, Sydney Mines | | |
| Product name | Course Slack | Pea | |
| Screen opening, mm | Minus 44, rd | 19 x 6.4, rd | |
| ERL number | 3680-80 | 3681-80 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 10.68 | 6.30 |
| Ash | % | 5.09 | 5.31 |
| Volatile matter | % | 33.18 | 34.68 |
| Fixed carbon | % | 51.05 | 53.71 |
| Sulphur, as rec'd | % | 3.00 | 1.92 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 28.53 | 31.27 |
| Btu/lb | | 12 267 | 13 447 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 75.49 | 79.55 |
| Hydrogen | % | 5.01 | 5.46 |
| Sulphur | % | 3.36 | 2.06 |
| Nitrogen | % | 1.44 | 1.49 |
| Ash | % | 5.70 | 5.67 |
| Oxygen, by difference | % | 9.00 | 5.77 |
| Trace mercury | µg/g (ppm) | 0.18 | 0.17 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1115 | 1080 |
| Spherical | °C | 1180 | 1170 |
| Hemispherical | °C | 1200 | 1260 |
| Fluid | °C | 1305 | 1370 |
| Hardgrove grindability index | | 60 | 58 |
| Free swelling index | | 5.5 | 8.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | |
|--------------------|--------------------------|--------------|
| Sampling date | 21-5-80 | |
| Sampling location | Wash Plant, Sydney Mines | |
| Product name | Course Slack | Pea |
| Screen opening, mm | Minus 44, rd | 19 x 6.4, rd |
| ERL number | 3680-80 | 3681-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 1.93 | 1.35 |
| Sulfate sulphur | % | 0.11 | 0.02 |
| Organic sulphur | % | 1.32 | 0.69 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 4.73 | 1.30 |
| Adherent | % | 5.95 | 5.00 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 23.28 | 30.63 |
| Al ₂ O ₃ | | 15.26 | 18.64 |
| Fe ₂ O ₃ | | 54.16 | 41.71 |
| TiO ₂ | | 0.69 | 0.64 |
| P ₂ O ₅ | | 0.08 | 0.18 |
| CaO | | 1.65 | 1.46 |
| MgO | | 0.73 | 1.25 |
| SO ₃ | | 1.38 | 1.08 |
| Na ₂ O | | 0.64 | 0.61 |
| K ₂ O | | 0.74 | 2.03 |
| SrO | | 0.00 | 0.01 |
| BaO | | 0.00 | 0.08 |
| LOF | | 0.78 | 0.48 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|---------------|---------|
| Sampling date | 21-5-80 | | |
| Sampling location | Wash Plant, Sydney Mines | | |
| Product name | 3/4 Slack | Fines | |
| Screen opening, mm | Minus 19, rd | Minus 6.4, rd | |
| ERL number | 3682-80 | | 3683-80 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 10.49 | 10.03 |
| Ash | % | 6.11 | 12.34 |
| Volatile matter | % | 32.98 | 31.16 |
| Fixed carbon | % | 50.42 | 46.47 |
| Sulphur, as rec'd | % | 2.84 | 3.74 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 27.88 | 25.66 |
| Btu/lb | | 11 983 | 11 032 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 74.26 | 67.95 |
| Hydrogen | % | 4.79 | 4.23 |
| Sulphur | % | 3.18 | 4.16 |
| Nitrogen | % | 1.22 | 1.31 |
| Ash | % | 6.83 | 13.72 |
| Oxygen, by difference | % | 9.72 | 8.63 |
| Trace mercury | µg/g (ppm) | 0.14 | 0.19 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1060 | 1105 |
| Spherical | °C | 1115 | 1215 |
| Hemispherical | °C | 1210 | 1265 |
| Fluid | °C | 1345 | 1400 |
| Hardgrove grindability index | | 61 | 63 |
| Free swelling index | | 4.5 | 4.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | |
|--------------------|--------------------------|---------------|
| Sampling date | 21-5-80 | |
| Sampling location | Wash Plant, Sydney Mines | |
| Product name | 3/4 Slack | Fines |
| Screen opening, mm | Minus 19, rd | Minus 6.4, rd |
| ERL number | 3682-80 | 3683-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 1.66 | 2.49 |
| Sulfate sulphur | % | 0.16 | 0.20 |
| Organic sulphur | % | 1.36 | 1.47 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 4.67 | 4.83 |
| Adherent | % | 5.82 | 5.20 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 30.28 | 33.59 |
| Al ₂ O ₃ | | 19.01 | 20.22 |
| Fe ₂ O ₃ | | 42.24 | 32.72 |
| TiO ₂ | | 0.65 | 0.68 |
| P ₂ O ₅ | | 0.26 | 0.16 |
| CaO | | 1.52 | 2.77 |
| MgO | | 0.94 | 1.47 |
| SO ₃ | | 1.23 | 3.32 |
| Na ₂ O | | 0.74 | 0.45 |
| K ₂ O | | 1.55 | 1.88 |
| SrO | | 0.03 | 0.03 |
| BaO | | 0.12 | 0.00 |
| LOF | | 0.56 | 1.31 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
Prince Mine; Hub Seam; Sydney Coalfield
Point Aconi, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|---------------|---------|
| Sampling date | 16-3-81 | | |
| Sampling location | Wash Plant, Sydney Mines | | |
| Product name | Raw Feed | Egg | Fines |
| Screen opening, mm | Plus 44, rd | Minus 6.4, rd | |
| ERL number | 3330-81 | 3331-81 | 3334-81 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 5.76 | 4.62 |
| Ash | % | 37.12 | 4.87 |
| Volatile matter | % | 24.67 | 35.45 |
| Fixed carbon | % | 32.45 | 55.06 |
| Sulphur, equil | % | 3.45 | 2.68 |
| Calorific value, as rec'd: | | | |
| | MJ/kg | 17.89 | 30.72 |
| | Btu/lb | 7690 | 13 208 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 44.73 | 76.54 |
| Hydrogen | % | 3.18 | 4.91 |
| Sulphur | % | 3.66 | 2.81 |
| Nitrogen | % | 0.73 | 1.16 |
| Ash | % | 39.39 | 5.10 |
| Oxygen, by difference | % | 8.31 | 9.48 |
| Trace mercury | µg/g (ppm) | 0.13 | 0.15 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1354 | 1077 |
| Spherical | °C | 1482+ | 1196 |
| Hemispherical | °C | 1482+ | 1341 |
| Fluid | °C | 1482+ | 1393 |
| Hardgrove grindability index | | 54 | 57 |
| Free swelling index | | 1.0 | 6.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | | |
|--------------------------------|--------------------------|-------------|---------------|
| Sampling date | 16-3-81 | | |
| Sampling location | Wash Plant, Sydney Mines | | |
| Product name | Raw Feed | Egg | Fines |
| Screen opening, mm | | Plus 44, rd | Minus 6.4, rd |
| ERL number | 3330-81 | 3331-81 | 3334-81 |
| Sulphur Forms (dry basis): | | | |
| Pyritic sulphur | % | 2.57 | 1.54 |
| Sulfate sulphur | % | 0.07 | 0.07 |
| Organic sulphur | % | 1.02 | 1.20 |
| Moisture (as rec'd): | | | |
| Inherent | % | 1.61 | 3.06 |
| Adherent | % | 4.15 | 1.56 |
| Ash analysis, %: | | | |
| SiO ₂ | | 51.28 | 43.92 |
| Al ₂ O ₃ | | 30.60 | 23.46 |
| Fe ₂ O ₃ | | 11.76 | 20.41 |
| TiO ₂ | | 1.00 | 0.76 |
| P ₂ O ₅ | | 0.41 | 0.15 |
| CaO | | 0.64 | 3.16 |
| MgO | | 1.19 | 1.57 |
| SO ₃ | | 0.64 | 3.28 |
| Na ₂ O | | 0.53 | 0.56 |
| K ₂ O | | 1.98 | 2.96 |
| SrO | | 0.12 | 0.02 |
| BaO | | 0.00 | 0.00 |
| LOF | | 0.10 | 0.41 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|--------------|--------|
| Sampling date | 16-3-81 | | |
| Sampling location | Wash Plant, Sydney Mines | | |
| Product name | Oiled Nut | Oiled Pea | |
| Screen opening, mm | 44 x 6.4, rd | 19 x 6.4, rd | |
| ERL number | 3332-81 | 3333-81 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 5.22 | 6.14 |
| Ash | % | 6.21 | 3.51 |
| Volatile matter | % | 34.29 | 32.00 |
| Fixed carbon | % | 54.28 | 58.35 |
| Sulphur, as rec'd | % | 3.23 | 1.47 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 30.19 | 31.72 |
| Btu/lb | | 12 977 | 13 641 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 75.76 | 79.38 |
| Hydrogen | % | 4.85 | 5.07 |
| Sulphur | % | 3.41 | 1.57 |
| Nitrogen | % | 1.17 | 1.12 |
| Ash | % | 6.55 | 3.74 |
| Oxygen, by difference | % | 8.26 | 9.12 |
| Trace mercury | µg/g (ppm) | 0.17 | 0.15 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1077 | 1082 |
| Spherical | °C | 1196 | 1152 |
| Hemispherical | °C | 1329 | 1279 |
| Fluid | °C | 1379 | 1338 |
| Hardgrove grindability index | | 58 | 57 |
| Free swelling index | | 6.0 | 7.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 Prince Mine; Hub Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | |
|--------------------|--------------------------|--------------|
| Sampling date | 16-3-81 | |
| Sampling location | Wash Plant, Sydney Mines | |
| Product name | Oiled Nut | Oiled Pea |
| Screen opening, mm | 44 x 6.4, rd | 19 x 6.4, rd |
| ERL number | 3332-81 | 3333-81 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 2.13 | 0.94 |
| Sulfate sulphur | % | 0.00 | 0.00 |
| Organic sulphur | % | 1.28 | 0.63 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 2.25 | 1.70 |
| Adherent | % | 2.97 | 4.44 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 28.74 | 30.92 |
| Al ₂ O ₃ | | 18.13 | 17.24 |
| Fe ₂ O ₃ | | 48.04 | 42.61 |
| TiO ₂ | | 0.74 | 0.84 |
| P ₂ O ₅ | | 0.13 | 0.13 |
| CaO | | 1.33 | 2.46 |
| MgO | | 0.00 | 0.96 |
| SO ₃ | | 1.20 | 2.39 |
| Na ₂ O | | 0.77 | 0.76 |
| K ₂ O | | 1.19 | 1.55 |
| SrO | | 0.02 | 0.01 |
| BaO | | 0.00 | 0.00 |
| LOF | | 0.50 | 0.90 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 T. Brogan & Sons Construction Ltd.; Bonar Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|---|----------|--------|
| Sampling date | 20-6-80 | 20-3-81 | |
| Sampling location | Trenton Power Station Nova Scotia Power Commission | Mine | |
| Product name | Mine Run | Mine Run | |
| Screen opening, mm | | | |
| ERL number | 3685-80 | 3339-81 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 13.41 | 7.94 |
| Ash | % | 13.39 | 10.50 |
| Volatile matter | % | 30.22 | 31.85 |
| Fixed carbon | % | 42.98 | 49.71 |
| Sulphur, as rec'd | % | 6.92 | 4.19 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 23.59 | 26.53 |
| Btu/lb | | 10 143 | 11 405 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 62.46 | 69.58 |
| Hydrogen | % | 3.81 | 4.18 |
| Sulphur | % | 8.00 | 4.55 |
| Nitrogen | % | 1.26 | 0.95 |
| Ash | % | 15.47 | 11.41 |
| Oxygen, by difference | % | 9.00 | 9.33 |
| Trace mercury | µg/g (ppm) | - | 0.12 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1160 | 1102 |
| Spherical | °C | 1215 | 1143 |
| Hemispherical | °C | 1250 | 1232 |
| Fluid | °C | 1345 | 1324 |
| Hardgrove grindability index | | 65 | 58 |
| Free swelling index | 1.5 | | 3.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 T. Brogan & Sons Construction Ltd.; Bonar Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | |
|-------------------|---|---------|
| Sampling date | 20-6-80 | 20-3-81 |
| Sampling location | Trenton Power Station Nova Scotia Power Commission | Mine |

| | | |
|--------------------|----------|----------|
| Product name | Mine Run | Mine Run |
| Screen opening, mm | | |

| | | |
|------------|---------|---------|
| ERL number | 3685-80 | 3339-81 |
|------------|---------|---------|

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|---|------|
| Pyritic sulphur | % | - | 3.88 |
| Sulfate sulphur | % | - | 0.23 |
| Organic sulphur | % | - | 0.44 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 5.61 | 3.63 |
| Adherent | % | 7.80 | 4.31 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 26.39 | 33.06 |
| Al ₂ O ₃ | | 14.11 | 16.12 |
| Fe ₂ O ₃ | | 54.60 | 44.51 |
| TiO ₂ | | 0.36 | 0.60 |
| P ₂ O ₅ | | 0.27 | 0.33 |
| CaO | | 0.92 | 0.92 |
| MgO | | 0.72 | 0.98 |
| SO ₃ | | 0.58 | 0.82 |
| Na ₂ O | | 0.26 | 0.43 |
| K ₂ O | | 0.98 | 1.87 |
| SrO | | 0.00 | 0.12 |
| BaO | | 0.18 | 0.00 |
| LOF | | 0.44 | 0.83 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 T. Brogan & Sons Construction Ltd.; Bonar Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | | |
|---|----------------------------|--------------|--------|
| Sampling date | 14-7-80 | | |
| Sampling location | Mine | | |
| Product name | Mine Run | Mine Run | |
| Screen opening, mm | (Upper Seam) | (Lower Seam) | |
| ERL number | 4166-80 | 4167-80 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 5.00 | 7.24 |
| Ash | % | 14.76 | 6.42 |
| Volatile matter | % | 33.47 | 34.24 |
| Fixed carbon | % | 46.77 | 52.10 |
| Sulphur, as rec'd | % | 10.90 | 5.18 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 25.80 | 28.64 |
| Btu/lb | | 11 090 | 12 312 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 64.23 | 74.29 |
| Hydrogen | % | 4.55 | 5.27 |
| Sulphur | % | 11.47 | 5.58 |
| Nitrogen | % | 1.14 | 1.38 |
| Ash | % | 15.54 | 6.92 |
| Oxygen, by difference | % | 3.07 | 6.56 |
| Trace mercury μg/g (ppm) | | 0.14 | 0.13 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1230 | 1230 |
| Spherical | °C | 1240 | 1290 |
| Hemispherical | °C | 1255 | 1320 |
| Fluid | °C | 1290 | 1330 |
| Hardgrove grindability index | | 65 | 56 |
| Free swelling index | | 2.0 | 2.0 |

Notes:

CAPE BRETON DEVELOPMENT CORPORATION (CBDC)
 T. Brogan & Sons Construction Ltd.; Bonar Seam; Sydney Coalfield
 Point Aconi, Cape Breton County, Nova Scotia

| | | |
|--------------------------------|--------------|--------------|
| Sampling date | 14-7-80 | |
| Sampling location | Mine | |
| Product name | Mine Run | Mine Run |
| Screen opening, mm | (Upper Seam) | (Lower Seam) |
| ERL number | 4166-80 | 4167-80 |
| <hr/> | | |
| Sulphur Forms (dry basis): | | |
| Pyritic sulphur | % | 7.98 |
| Sulfate sulphur | % | 0.35 |
| Organic sulphur | % | 3.14 |
| <hr/> | | |
| Moisture (as rec'd): | | |
| Inherent | % | 5.00 |
| Adherent | % | - |
| <hr/> | | |
| Ash analysis, %: | | |
| SiO ₂ | | 10.46 |
| Al ₂ O ₃ | | 5.96 |
| Fe ₂ O ₃ | | 81.21 |
| TiO ₂ | | 0.16 |
| P ₂ O ₅ | | 0.22 |
| CaO | | 1.25 |
| MgO | | 0.51 |
| SO ₃ | | 0.90 |
| Na ₂ O | | 0.16 |
| K ₂ O | | 0.21 |
| SrO | | 0.01 |
| BaO | | 0.00 |
| LOF | | 0.00 |

Notes:

DRUMMOND COAL COMPANY LIMITED
 Drummond Colliery; No. 1 (Scott Pit) Seam; Pictou Coalfield
 Westville, Pictou County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|----------|----------|
| Sampling date | 15-7-78 | 19-6-80 | 23-10-80 |
| Sampling location | Mine | Mine | Mine |
| Product name | | Mine Run | |
| Screen opening, mm | | | |
| ERL number | 4260-79 | 3686-80 | 4897-80 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 1.44 | 1.74 |
| Ash | % | 20.47 | 21.46 |
| Volatile matter | % | 25.65 | 26.24 |
| Fixed carbon | % | 52.44 | 50.56 |
| Sulphur, as rec'd | % | 2.94 | 2.43 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 26.79 | 26.00 |
| Btu/lb | | 11 518 | 11 176 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 66.18 | 65.13 |
| Hydrogen | % | 4.21 | 3.73 |
| Sulphur | % | 2.98 | 2.47 |
| Nitrogen | % | 1.69 | 1.77 |
| Ash | % | 20.77 | 21.84 |
| Oxygen, by difference | % | 4.17 | 5.06 |
| Trace mercury | µg/g (ppm) | 0.04 | - |
| | | | 0.06 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1250 | 1325 |
| Spherical | °C | 1400 | 1360 |
| Hemispherical | °C | 1450 | 1380 |
| Fluid | °C | 1480+ | 1470 |
| Hardgrove grindability index | | 55 | 58 |
| Free swelling index | | 2.5 | 1.5 |
| | | | 2.0 |

Notes:

DRUMMOND COAL COMPANY LIMITED
 Drummond Colliery; No. 1 (Scott Pit) Seam; Pictou Coalfield
 Westville, Pictou County, Nova Scotia

| | | | |
|-------------------|---------|---------|----------|
| Sampling date | 15-7-78 | 19-6-80 | 23-10-80 |
| Sampling location | Mine | Mine | Mine |

| | |
|--------------------|----------|
| Product name | Mine Run |
| Screen opening, mm | |

| | | | |
|------------|---------|---------|---------|
| ERL number | 4260-79 | 3686-80 | 4897-80 |
|------------|---------|---------|---------|

Sulphur Forms (dry basis):

| | | | | |
|-----------------------|---|------|---|------|
| Pyritic sulphur | % | 1.98 | - | 2.31 |
| Sulfate sulphur | % | 0.00 | - | 0.00 |
| Organic sulphur | % | 1.00 | - | 0.63 |

Moisture (as rec'd):

| | | | | |
|----------------|---|------|------|------|
| Inherent | % | 1.44 | 1.74 | 1.29 |
| Adherent | % | - | - | - |

Ash analysis, %:

| | | | | |
|-------------------------|--|-------|-------|-------|
| SiO_2 | | 53.45 | 53.80 | 49.46 |
| Al_2O_3 | | 24.31 | 24.15 | 22.25 |
| Fe_2O_3 | | 13.45 | 13.24 | 12.89 |
| TiO_2 | | 0.72 | 0.72 | 0.64 |
| P_2O_5 | | 0.49 | 0.51 | 0.37 |
| CaO | | 1.48 | 1.71 | 4.19 |
| MgO | | 1.00 | 1.01 | 1.46 |
| SO_3 | | 1.32 | 1.23 | 4.53 |
| Na_2O | | 0.56 | 0.58 | 0.48 |
| K_2O | | 2.12 | 1.84 | 1.87 |
| SrO | | 0.05 | 0.05 | 0.04 |
| BaO | | 0.07 | 0.02 | 0.06 |
| LOF | | 0.62 | 0.66 | 0.69 |

Notes:

DRUMMOND COAL COMPANY LIMITED
 Drummond Colliery; No. 1 (Scott Pit) Seam; Pictou Coalfield
 Westville, Pictou County, Nova Scotia

| | | |
|--------------------------------|---------|----------------------------|
| Sampling date | 17-9-81 | 13-5-81 |
| Sampling location | Mine | |
| Product name | | Mine Run |
| Screen opening, mm | | |
| ERL number | 4640-81 | 2624-82 |
| Rank of coal | | High-volatile A bituminous |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 1.64 |
| Ash | % | 20.68 |
| Volatile matter | % | 26.67 |
| Fixed carbon | % | 51.01 |
| Sulphur, as rec'd | % | 2.39 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 26.76 |
| Btu/lb | | 11 504 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 65.24 |
| Hydrogen | % | 4.05 |
| Sulphur | % | 2.43 |
| Nitrogen | % | 1.63 |
| Ash | % | 21.02 |
| Oxygen, by difference | % | 5.63 |
| Trace mercury μg/g (ppm) | | 0.06 |
| Ash fusibility temperature: | | |
| Initial | °C | 1177 |
| Spherical | °C | 1313 |
| Hemispherical | °C | 1327 |
| Fluid | °C | 1327 |
| Hardgrove grindability index | | 53 |
| Free swelling index | | 1.5 |

Notes:

DRUMMOND COAL COMPANY LIMITED
 Drummond Colliery; No. 1 (Scott Pit) Seam; Pictou Coalfield
 Westville, Pictou County, Nova Scotia

| | | |
|--------------------|---------|----------|
| Sampling date | 17-9-81 | 13-5-81 |
| Sampling location | | Mine |
| Product name | | Mine Run |
| Screen opening, mm | | |
| ERL number | 4640-81 | 2624-82 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|---|
| Pyritic sulphur | % | 1.71 | - |
| Sulfate sulphur | % | 0.06 | - |
| Organic sulphur | % | 0.66 | - |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.64 | 1.10 |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 52.94 | 50.53 |
| Al ₂ O ₃ | | 23.02 | 23.24 |
| Fe ₂ O ₃ | | 12.16 | 17.18 |
| TiO ₂ | | 0.80 | 0.70 |
| P ₂ O ₅ | | 0.42 | 0.52 |
| CaO | | 3.33 | 1.42 |
| MgO | | 1.08 | 1.02 |
| SO ₃ | | 3.01 | 1.07 |
| Na ₂ O | | 0.42 | 0.60 |
| K ₂ O | | 1.96 | 1.93 |
| SrO | | 0.04 | 0.04 |
| BaO | | 0.00 | 0.12 |
| LOF | | 0.46 | 0.16 |

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia.

| | | |
|--------------------|--------------------------|--------------------|
| Sampling date | 26-10-79 | 30-10-80 |
| Sampling location | Mine Dry Screening Plant | |
| Product name | Lump | |
| Screen opening, mm | Plus 152, sq | |
| ERL number | 3788-80 4875-80 | 4901-80 2114-81 |

Rank of coal High-volatile B bituminous

Proximate analysis, equil:

| | | | |
|-----------------------|---|-------|-------|
| Moisture | % | 4.53 | 5.94 |
| Ash | % | 8.88 | 8.53 |
| Volatile matter | % | 32.26 | 37.02 |
| Fixed carbon | % | 54.33 | 48.51 |

Sulphur, equil % 6.39 6.77

Calorific value, equil:

| | | |
|--------|--------|--------|
| MJ/kg | 27.64 | 27.88 |
| Btu/lb | 11 884 | 11 985 |

Ultimate analysis, dry basis:

| | | | |
|----------------------------|---|-------|-------|
| Carbon | % | 68.72 | 70.46 |
| Hydrogen | % | 4.70 | 4.57 |
| Sulphur | % | 6.69 | 7.20 |
| Nitrogen | % | 1.36 | 1.29 |
| Ash | % | 9.30 | 9.07 |
| Oxygen, by difference | % | 9.23 | 7.41 |

Trace mercury μg/g (ppm) 0.13 0.09

Ash fusibility temperature:

| | | | |
|---------------------|----|------|------|
| Initial | °C | 1015 | 1049 |
| Spherical | °C | 1050 | 1065 |
| Hemispherical | °C | 1065 | 1071 |
| Fluid | °C | 1150 | 1654 |

Hardgrove grindability index 60 57

Free swelling index 2.0 2.5

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| | | |
|--------------------|--------------------------|----------|
| Sampling date | 26-10-79 | 30-10-80 |
| Sampling location | Mine Dry Screening Plant | |
| Product name | Lump | |
| Screen opening, mm | Plus 152, sq | |

| | | |
|------------|---------|---------|
| ERL number | 3788-80 | 4901-80 |
| | 4875-80 | 2114-81 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 3.53 |
| Sulfate sulphur | % | 0.17 |
| Organic sulphur | % | 3.50 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | |
|--------------------------------|-------|
| SiO ₂ | 22.33 |
| Al ₂ O ₃ | 8.91 |
| Fe ₂ O ₃ | 49.58 |
| TiO ₂ | 0.40 |
| P ₂ O ₅ | 1.27 |
| CaO | 6.28 |
| MgO | 0.78 |
| SO ₃ | 6.16 |
| Na ₂ O | 1.07 |
| K ₂ O | 0.55 |
| SrO | 0.01 |
| BaO | 0.14 |
| LOF | 1.53 |

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| | | | |
|--------------------|----------|--------------------------|----------|
| Sampling date | 30-11-78 | 26-10-79 | 30-10-80 |
| Sampling location | | Mine Dry Screening Plant | |
| Product name | | Medium Lump | |
| Screen opening, mm | | 152 x 83, sq | |

| | | | |
|------------|---------|---------|---------|
| ERL number | 3963-78 | 3789-80 | 4902-80 |
| | | 4876-80 | 2114-81 |

| | | | |
|--------------------------------------|----------------------------|--------|--------|
| Rank of coal | High-volatile B bituminous | | |
| Proximate analysis, equil: | | | |
| Moisture | % | 4.51 | 3.26 |
| Ash | % | 7.69 | 15.36 |
| Volatile matter | % | 34.66 | 32.29 |
| Fixed carbon | % | 23.14 | 49.09 |
| Sulphur, equil | % | 6.22 | 7.50 |
| | | | 6.45 |
| Calorific value, equil: | | | |
| | MJ/kg | 29.46 | 25.67 |
| | Btu/lb | 12 667 | 11 034 |
| | | | 28.28 |
| | | | 12 158 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 70.78 | 62.06 |
| Hydrogen | % | 4.57 | 4.20 |
| Sulphur | % | 6.51 | 7.75 |
| Nitrogen | % | 1.39 | 1.14 |
| Ash | % | 8.05 | 15.88 |
| Oxygen, by difference | % | 8.70 | 8.97 |
| Trace mercury | µg/g (ppm) | 0.09 | 0.15 |
| | | | 0.10 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1025 | 1060 |
| Spherical | °C | 1055 | 1075 |
| Hemispherical | °C | 1065 | 1115 |
| Fluid | °C | 1205 | 1195 |
| | | | 1038 |
| | | | 1049 |
| | | | 1071 |
| | | | 1204 |
| Hardgrove grindability index | | 57 | 59 |
| Free swelling index | | 2.5 | 2.0 |
| | | | 1.5 |

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| | | | |
|--------------------|----------|--------------------------|----------|
| Sampling date | 30-11-78 | 26-10-79 | 30-10-80 |
| Sampling location | | Mine Dry Screening Plant | |
| Product name | | Medium Lump | |
| Screen opening, mm | | 152 x 83, sq | |

| | | | |
|------------|---------|---------|---------|
| ERL number | 3963-78 | 3789-80 | 4902-80 |
| | | 4876-80 | 2114-81 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 3.08 |
| Sulfate sulphur | % | 0.13 |
| Organic sulphur | % | 3.61 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 24.02 | 27.57 |
| Al ₂ O ₃ | 8.78 | 10.34 |
| Fe ₂ O ₃ | 49.41 | 47.51 |
| TiO ₂ | 0.50 | 0.49 |
| P ₂ O ₅ | 1.25 | 0.83 |
| CaO | 5.91 | 4.60 |
| MgO | 0.47 | 0.74 |
| SO ₃ | 7.70 | 3.75 |
| Na ₂ O | 1.47 | 1.23 |
| K ₂ O | 0.49 | 0.61 |
| SrO | - | 0.01 |
| BaO | - | 0.19 |
| LOF | - | 1.05 |

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| Sampling date | 30-11-78 | 26-10-79 | 30-10-80 |
|-------------------------------|------------|----------------------------|--------------------|
| Sampling location | | Mine Dry Screening Plant | |
| Product name | | Egg | |
| Screen opening, mm | | 83 x 51, sq | |
| ERL number | 3964-78 | 3790-80 4877-80 | 4903-80 2115-81 |
| Rank of coal | | High-volatile B bituminous | |
| Proximate analysis, equil: | | | |
| Moisture | % | 4.79 | 3.36 |
| Ash | % | 9.64 | 8.81 |
| Volatile matter | % | 34.06 | 35.41 |
| Fixed carbon | % | 51.51 | 52.42 |
| Sulphur, equil | % | 7.00 | 6.19 |
| Calorific value, equil: | | | |
| MJ/kg | | 28.26 | 27.96 |
| Btu/lb | | 12 148 | 12 023 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 70.42 | 69.72 |
| Hydrogen | % | 4.29 | 4.55 |
| Sulphur | % | 7.35 | 6.68 |
| Nitrogen | % | 1.41 | 1.28 |
| Ash | % | 10.12 | 10.67 |
| Oxygen, by difference | % | 6.41 | 7.10 |
| Trace mercury | µg/g (ppm) | 0.13 | 0.09 |
| Ash fusibility temperature: | | | |
| Initial | °C | - | 1010 |
| Spherical | °C | - | 1050 |
| Hemispherical | °C | - | 1070 |
| Fluid | °C | - | 1125 |
| Hardgrove grindability index | | 58 | 59 |
| Free swelling index | | 2.5 | 2.5 |
| Notes: | | | 4.0 |

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| | | | |
|--------------------|----------|--------------------------|----------|
| Sampling date | 30-11-78 | 26-10-79 | 30-10-80 |
| Sampling location | | Mine Dry Screening Plant | |
| Product name | | Egg | |
| Screen opening, mm | | 83 x 51, sq | |

| | | |
|----------------------------|---|------|
| Sulphur Forms (dry basis): | | |
| Pyritic sulphur | % | 3.07 |
| Sulfate sulphur | % | 0.11 |
| Organic sulphur | % | 3.50 |
| Moisture (as rec'd): | | |
| Inherent | % | - |
| Adherent | % | - |

| | | |
|--------------------------------|-------|-------|
| Ash analysis, %: | | |
| SiO ₂ | 25.54 | 34.05 |
| Al ₂ O ₃ | 9.48 | 11.38 |
| Fe ₂ O ₃ | 42.55 | 38.67 |
| TiO ₂ | 0.49 | 0.54 |
| P ₂ O ₅ | 0.50 | 0.61 |
| CaO | 3.88 | 4.33 |
| MgO | 0.88 | 1.15 |
| SO ₃ | 4.70 | 3.59 |
| Na ₂ O | 1.33 | 1.08 |
| K ₂ O | 0.65 | 1.09 |
| SrO | - | 0.01 |
| BaO | - | 0.15 |
| LOF | - | 1.10 |

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| | | | |
|--------------------|----------|--------------------------|----------|
| Sampling date | 30-11-78 | 26-10-79 | 30-10-80 |
| Sampling location | | Mine Dry Screening Plant | |
| Product name | | Nut | |
| Screen opening, mm | | 51 x 19, sq | |

| | | | |
|--------------------------------------|----------------------------|--------|--------|
| Rank of coal | High-volatile B bituminous | | |
| Proximate analysis, equil: | | | |
| Moisture | % | 5.38 | 5.71 |
| Ash | % | 9.46 | 12.25 |
| Volatile matter | % | 33.04 | 35.08 |
| Fixed carbon | % | 52.12 | 46.96 |
| Sulphur, as equil | % | 6.98 | 6.03 |
| Calorific value, equil: | | | |
| MJ/kg | | 28.14 | 27.00 |
| Btu/lb | | 12 099 | 11 607 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 70.29 | 67.62 |
| Hydrogen | % | 4.47 | 4.34 |
| Sulphur | % | 7.38 | 6.40 |
| Nitrogen | % | 1.43 | 1.20 |
| Ash | % | 10.00 | 12.99 |
| Oxygen, by difference | % | 6.43 | 7.45 |
| Trace mercury | µg/g (ppm) | 0.11 | 0.09 |
| | | | 0.08 |
| Ash fusibility temperature: | | | |
| Initial | °C | - | 1005 |
| Spherical | °C | - | 1054 |
| Hemispherical | °C | - | 1071 |
| Fluid | °C | - | 1193 |
| Hardgrove grindability index | | 60 | 59 |
| Free swelling index | | 2.5 | 3.0 |
| | | | 3.5 |

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| | | | |
|--------------------|--------------------------|--------------------|--------------------|
| Sampling date | 30-11-78 | 26-10-79 | 30-10-80 |
| Sampling location | Mine Dry Screening Plant | | |
| Product name | Nut | | |
| Screen opening, mm | 51 x 19, sq | | |
| ERL number | 3965-78 | 3791-80 4878-80 | 4904-80 2116-81 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 3.34 |
| Sulfate sulphur | % | 0.02 |
| Organic sulphur | % | 3.04 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 26.22 | 32.50 |
| Al ₂ O ₃ | 10.93 | 14.05 |
| Fe ₂ O ₃ | 51.56 | 35.21 |
| TiO ₂ | 0.51 | 0.45 |
| P ₂ O ₅ | 0.39 | 0.41 |
| CaO | 3.25 | 5.78 |
| MgO | 0.80 | 1.65 |
| SO ₃ | 3.54 | 5.70 |
| Na ₂ O | 1.32 | 1.03 |
| K ₂ O | 0.88 | 1.74 |
| SrO | - | 0.01 |
| BaO | - | 0.25 |
| LOF | - | 1.37 |

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| | Sampling date | 30-11-78 | 26-10-79 | 30-10-80 |
|-------------------------------|-----------------------------------|--------------------------|----------|----------|
| | Sampling location | Mine Dry Screening Plant | | |
| Product name | Stoker Pea | | | |
| Screen opening, mm | 19 x 6.4, sq | | | |
| ERL number | 3966-78 3792-80 4905-80 | | | 2117-81 |
| Rank of coal | High-volatile B bituminous | | | |
| Proximate analysis, equil: | | | | |
| Moisture | % | 5.35 | 4.42 | 6.46 |
| Ash | % | 10.30 | 9.33 | 11.65 |
| Volatile matter | % | 32.63 | 34.97 | 35.52 |
| Fixed carbon | % | 51.72 | 51.28 | 46.37 |
| Sulphur, equil | % | 6.50 | 6.00 | 6.04 |
| Calorific value, equil: | | | | |
| MJ/kg | | 27.96 | 27.81 | 26.66 |
| Btu/lb | | 12 022 | 11 956 | 11 462 |
| Ultimate analysis, dry basis: | | | | |
| Carbon | % | 69.07 | 69.14 | 67.11 |
| Hydrogen | % | 4.40 | 4.79 | 4.26 |
| Sulphur | % | 6.86 | 6.28 | 6.46 |
| Nitrogen | % | 1.37 | 1.36 | 1.24 |
| Ash | % | 10.88 | 9.76 | 12.45 |
| Oxygen, by difference | % | 7.42 | 8.67 | 8.48 |
| Trace mercury | µg/g (ppm) | 0.09 | 0.09 | 0.07 |
| Ash fusibility temperature: | | | | |
| Initial | °C | - | 1015 | 1065 |
| Spherical | °C | - | 1080 | 1099 |
| Hemispherical | °C | - | 1095 | 1121 |
| Fluid | °C | - | 1240 | 1204 |
| Hardgrove grindability index | | 62 | 59 | 63 |
| Free swelling index | | 2.0 | 4.0 | 1.0 |

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| | | | |
|--------------------|--------------------------|--------------------|--------------------|
| Sampling date | 30-11-78 | 26-10-79 | 30-10-80 |
| Sampling location | Mine Dry Screening Plant | | |
| Product name | | Stoker Pea | |
| Screen opening, mm | | 19 x 6.4, sq | |
| ERL number | 3966-78 | 3792-80 4879-80 | 4905-80 2117-81 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 2.47 |
| Sulfate sulphur | % | 0.48 |
| Organic sulphur | % | 3.51 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 28.01 | 30.85 |
| Al ₂ O ₃ | 11.83 | 13.47 |
| Fe ₂ O ₃ | 46.73 | 33.90 |
| TiO ₂ | 0.48 | 0.49 |
| P ₂ O ₅ | 0.45 | 0.53 |
| CaO | 4.28 | 6.51 |
| MgO | 0.83 | 1.48 |
| SO ₃ | 4.89 | 7.24 |
| Na ₂ O | 1.34 | 0.86 |
| K ₂ O | 1.18 | 1.56 |
| SrO | - | 0.01 |
| BaO | - | 0.17 |
| LOF | - | 1.27 |

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| | Sampling date | 30-11-78 | 26-10-79 | 30-10-80 |
|-------------------------------|-------------------|----------------------------|--------------------------|----------|
| | Sampling location | | Mine Dry Screening Plant | |
| Product name | | | Fines | |
| Screen opening, mm | | | Minus 6.4, sq | |
| ERL number | 3967-78 | 3793-80 | 4906-80 | 4906-80 |
| | | 4880-80 | 2118-81 | |
| Rank of coal | | High-volatile B bituminous | | |
| Proximate analysis, equil: | | | | |
| Moisture | % | 5.49 | 5.05 | 4.91 |
| Ash | % | 10.12 | 12.55 | 13.63 |
| Volatile matter | % | 31.99 | 34.12 | 34.86 |
| Fixed carbon | % | 48.40 | 48.28 | 46.60 |
| Sulphur, equil | % | 6.01 | 5.74 | 6.42 |
| Calorific value, equil: | | | | |
| MJ/kg | | 26.55 | 25.94 | 26.66 |
| Btu/lb | | 11 416 | 11 155 | 11 460 |
| Ultimate analysis, dry basis: | | | | |
| Carbon | % | 66.34 | 65.52 | 65.31 |
| Hydrogen | % | 4.26 | 4.50 | 4.20 |
| Sulphur | % | 6.36 | 6.05 | 6.75 |
| Nitrogen | % | 1.31 | 1.31 | 1.21 |
| Ash | % | 14.94 | 13.22 | 14.33 |
| Oxygen, by difference | % | 6.79 | 9.40 | 8.20 |
| Trace mercury | µg/g (ppm) | 0.12 | 0.08 | 0.07 |
| Ash fusibility temperature: | | | | |
| Initial | °C | - | 1015 | 1082 |
| Spherical | °C | - | 1115 | 1110 |
| Hemispherical | °C | - | 1140 | 1171 |
| Fluid | °C | - | 1180 | 1260 |
| Hardgrove grindability index | | 64 | 64 | 63 |
| Free swelling index | | 1.0 | 2.5 | 3.5 |

Notes:

EVANS COAL MINES LIMITED
 Evans Mines; No. 5 Seam; Inverness Coalfield
 St. Rose, Inverness County, Nova Scotia

| | | | |
|--------------------|----------|--------------------------|----------|
| Sampling date | 30-11-78 | 26-10-79 | 30-10-80 |
| Sampling location | | Mine Dry Screening Plant | |
| Product name | | Fines | |
| Screen opening, mm | | Minus 6.4, sq | |

| | | | |
|------------|---------|---------|---------|
| ERL number | 3967-78 | 3793-80 | 4906-80 |
| | | 4880-80 | 2118-81 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 3.66 |
| Sulfate sulphur | % | 0.05 |
| Organic sulphur | % | 3.04 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 23.79 | 29.49 |
| Al ₂ O ₃ | 10.53 | 13.19 |
| Fe ₂ O ₃ | 30.93 | 35.05 |
| TiO ₂ | 0.43 | 0.44 |
| P ₂ O ₅ | 0.29 | 0.36 |
| CaO | 13.52 | 7.03 |
| MgO | 2.14 | 1.57 |
| SO ₃ | 15.93 | 7.44 |
| Na ₂ O | 1.11 | 0.97 |
| K ₂ O | 1.32 | 1.71 |
| SrO | - | 0.00 |
| BaO | - | 0.13 |
| LOF | - | 2.43 |

Notes:

RIVER HÉBERT COAL COMPANY LIMITED
 Cochrane Mine; Kimberley Seam; Joggins Coalfield
 River Hébert, Cumberland County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|--------------|--------|
| Sampling date | 12-7-79 | | |
| Sampling location | Mine | | |
| Product name | Screen | Slack | |
| Screen opening, mm | Plus 38, sq | Minus 38, sq | |
| ERL number | 4256-79 | 4257-79 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 1.54 | 2.87 |
| Ash | % | 14.02 | 17.83 |
| Volatile matter | % | 34.95 | 32.47 |
| Fixed carbon | % | 49.49 | 46.83 |
| Sulphur, as rec'd | % | 7.91 | 5.41 |
| Calorific value, as rec'd: | | | |
| | MJ/kg | 28.34 | 26.40 |
| | Btu/lb | 12 186 | 11 348 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 67.03 | 65.36 |
| Hydrogen | % | 4.69 | 4.50 |
| Sulphur | % | 8.03 | 5.55 |
| Nitrogen | % | 1.54 | 1.42 |
| Ash | % | 14.24 | 18.36 |
| Oxygen, by difference | % | 4.47 | 4.81 |
| Trace mercury | µg/g (ppm) | 0.41 | 0.21 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1140 | 1040 |
| Spherical | °C | 1170 | 1080 |
| Hemispherical | °C | 1280 | 1095 |
| Fluid | °C | 1415 | 1120 |
| Hardgrove grindability index | | 56 | 58 |
| Free swelling index | | 4.0 | 2.0 |

Notes:

RIVER HÉBERT COAL COMPANY LIMITED
 Cochrane Mine; Kimberley Seam; Joggins Coalfield
 River Hébert, Cumberland County, Nova Scotia

| | | |
|--------------------|-------------|--------------|
| Sampling date | 12-7-79 | |
| Sampling location | Mine | |
| Product name | Screen | Slack |
| Screen opening, mm | Plus 38, sq | Minus 38, sq |
| ERL number | 4256-79 | 4257-79 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 4.67 | 2.90 |
| Sulfate sulphur | % | 0.21 | 0.17 |
| Organic sulphur | % | 3.15 | 2.48 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.54 | 1.92 |
| Adherent | % | - | 0.95 |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 36.71 | 18.55 |
| Al ₂ O ₃ | 16.81 | 8.35 |
| Fe ₂ O ₃ | 25.30 | 51.53 |
| TiO ₂ | 0.63 | 0.43 |
| P ₂ O ₅ | 0.80 | 0.86 |
| CaO | 6.35 | 7.84 |
| MgO | 1.50 | 0.83 |
| SO ₃ | 5.96 | 7.96 |
| Na ₂ O | 0.53 | 0.29 |
| K ₂ O | 2.76 | 0.84 |
| SrO | 0.02 | 0.01 |
| BaO | 0.00 | 0.00 |
| LOF | 1.30 | 1.98 |

Notes:

RIVER HÉBERT COAL COMPANY LIMITED
 Cochrane Mine; Kimberley Seam; Joggins Coalfield
 River Hébert, Cumberland County, Nova Scotia

| | | | |
|-------------------------------|---|--------------|--------|
| Sampling date | 12-7-79 | | |
| Sampling location | Harrison Lake Power Plant, Maccan, Nova Scotia | | |
| Product name | Screen | Slack | |
| Screen opening, mm | Plus 38, sq | Minus 38, sq | |
| ERL number | 4258-79 | 4259-79 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 1.83 | 2.63 |
| Ash | % | 10.45 | 19.11 |
| Volatile matter | % | 35.11 | 31.66 |
| Fixed carbon | % | 52.61 | 46.60 |
| Sulphur, as rec'd | % | 6.57 | 5.34 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 29.74 | 26.48 |
| Btu/lb | | 12 787 | 11 384 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 70.40 | 64.65 |
| Hydrogen | % | 4.90 | 4.37 |
| Sulphur | % | 6.69 | 5.49 |
| Nitrogen | % | 1.62 | 1.40 |
| Ash | % | 10.84 | 19.63 |
| Oxygen, by difference | % | 5.75 | 4.46 |
| Trace mercury | µg/g (ppm) | 0.35 | 0.20 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1080 | 1125 |
| Spherical | °C | 1150 | 1240 |
| Hemispherical | °C | 1205 | 1315 |
| Fluid | °C | 1305 | 1325 |
| Hardgrove grindability index | | 57 | 57 |
| Free swelling index | | 4.0 | 4.0 |

Notes:

RIVER HÉBERT COAL COMPANY LIMITED
 Cochrane Mine; Kimberley Seam; Joggins Coalfield
 River Hébert, Cumberland County, Nova Scotia

| | | |
|--------------------|---|--------------|
| Sampling date | 12-7-79 | |
| Sampling location | Harrison Lake Power Plant, Maccan, Nova Scotia | |
| Product name | Screen | Slack |
| Screen opening, mm | Plus 38, sq | Minus 38, sq |
| ERL number | 4258-79 | 4259-79 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 3.48 | 2.37 |
| Sulfate sulphur | % | 0.07 | 0.07 |
| Organic sulphur | % | 3.14 | 3.05 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.83 | 1.96 |
| Adherent | % | - | 0.67 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 22.01 | 39.28 |
| Al ₂ O ₃ | | 9.82 | 16.90 |
| Fe ₂ O ₃ | | 48.86 | 23.98 |
| TiO ₂ | | 0.48 | 0.61 |
| P ₂ O ₅ | | 1.32 | 0.81 |
| CaO | | 6.73 | 5.55 |
| MgO | | 0.89 | 1.60 |
| SO ₃ | | 6.35 | 5.97 |
| Na ₂ O | | 0.33 | 0.53 |
| K ₂ O | | 0.91 | 2.74 |
| SrO | | 0.02 | 0.02 |
| BaO | | 0.11 | 0.08 |
| LOF | | 1.67 | 1.04 |

Notes:

THORBURN MINING LIMITED
Coal Reclamation Project; Waste Dumps; Pictou Coalfield
Stellarton, Pictou County, Nova Scotia

| | | | |
|---|----------------------------|------------|-------|
| Sampling date | 24-10-80 | | |
| Sampling location | Stellarton Wash Plant | | |
| Product name | Egg | Stoker | |
| Screen opening, mm | Plus 19, sq | 19 x 5, sq | |
| ERL number | 4900-80 | 4899-80 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 3.93 | 5.03 |
| Ash | % | 27.96 | 32.00 |
| Volatile matter | % | 25.30 | 23.28 |
| Fixed carbon | % | 42.81 | 39.69 |
| Sulphur, as rec'd | % | 0.95 | 0.69 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 22.74 | 20.82 |
| Btu/lb | | 9777 | 8953 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 59.17 | 54.97 |
| Hydrogen | % | 3.78 | 3.52 |
| Sulphur | % | 0.99 | 0.73 |
| Nitrogen | % | 1.60 | 1.46 |
| Ash | % | 29.10 | 33.70 |
| Oxygen, by difference | % | 5.36 | 5.62 |
| Trace mercury µg/g (ppm) | | 0.03 | 0.05 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1177 | 1216 |
| Spherical | °C | 1438 | 1427 |
| Hemispherical | °C | 1482+ | 1482+ |
| Fluid | °C | 1482+ | 1482+ |
| Hardgrove grindability index | | 56 | 58 |
| Free swelling index | | 1.0 | 1.0 |

Notes:

THORBURN MINING LIMITED
 Coal Reclamation Project; Waste Dumps; Pictou Coalfield
 Stellarton, Pictou County, Nova Scotia

| | | |
|--------------------|-----------------------|------------|
| Sampling date | 24-10-80 | |
| Sampling location | Stellarton Wash Plant | |
| Product name | Egg | Stoker |
| Screen opening, mm | Plus 19, sq | 19 x 5, sq |
| ERL number | 4900-80 | 4899-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.64 | 0.62 |
| Sulfate sulphur | % | 0.09 | 0.10 |
| Organic sulphur | % | 0.26 | 0.01 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.31 | 1.51 |
| Adherent | % | 2.62 | 3.52 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 52.94 | 52.84 |
| Al ₂ O ₃ | | 26.97 | 26.10 |
| Fe ₂ O ₃ | | 7.50 | 9.78 |
| TiO ₂ | | 0.69 | 0.74 |
| P ₂ O ₅ | | 0.23 | 0.23 |
| CaO | | 1.99 | 1.77 |
| MgO | | 1.72 | 1.38 |
| SO ₃ | | 1.97 | 1.36 |
| Na ₂ O | | 0.23 | 0.25 |
| K ₂ O | | 2.97 | 2.86 |
| SrO | | 0.05 | 0.04 |
| BaO | | 0.06 | 0.10 |
| LOF | | 0.28 | 0.00 |

Notes:

THORBURN MINING LIMITED
 Coal Reclamation Project; Waste Dumps; Pictou Coalfield
 Stellarton, Pictou County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|-------------|--------------|
| Sampling date | 19-6-80 | | |
| Sampling location | Stellarton Wash Plant | | |
| Product name | Raw Feed | Screen | Slack |
| Screen opening, mm | | Plus 19, sq | Minus 19, sq |
| ERL number | 3689-80 | 3687-80 | 3688-80 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 12.81 | 7.52 |
| Ash | % | 47.70 | 32.07 |
| Volatile matter | % | 15.68 | 21.88 |
| Fixed carbon | % | 23.81 | 38.53 |
| Sulphur, as rec'd | % | 0.42 | 1.05 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 11.50 | 19.56 |
| Btu/lb | | 4945 | 8409 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 35.53 | 53.71 |
| Hydrogen | % | 2.40 | 3.65 |
| Sulphur | % | 0.48 | 1.13 |
| Nitrogen | % | 1.00 | 1.06 |
| Ash | % | 54.70 | 34.68 |
| Oxygen, by difference | % | 5.89 | 5.77 |
| Trace mercury | µg/g (ppm) | - | - |
| Ash fusibility temperature: | | | |
| Initial | °C | 1350 | 1480+ |
| Spherical | °C | 1480+ | 1480+ |
| Hemispherical | °C | | |
| Fluid | °C | | |
| Hardgrove grindability index | | 71 | 55 |
| Free swelling index | NA | 1.5 | 0.5 |

Notes:

THORBURN MINING LIMITED
 Coal Reclamation Project; Waste Dumps; Pictou Coalfield
 Stellarton, Pictou County, Nova Scotia

| | | | |
|--------------------|-----------------------|-----------------------|-----------------------|
| Sampling date | 19-6-80 | | |
| Sampling location | Stellarton Wash Plant | | |
| Product name | Raw Feed | Screen Plus 19, sq | Slack Minus 19, sq |
| Screen opening, mm | | | |
| ERL number | 3689-80 | 3687-80 | 3688-80 |

Sulphur Forms (dry basis):

| | |
|-----------------------|---|
| Pyritic sulphur | % |
| Sulfate sulphur | % |
| Organic sulphur | % |

Moisture (as rec'd):

| | | | | |
|----------------|---|------|------|------|
| Inherent | % | 3.81 | 2.02 | 2.73 |
| Adherent | % | 9.00 | 5.50 | 9.50 |

Ash analysis, %:

| | | | |
|--------------------------------|-------|-------|-------|
| SiO ₂ | 55.08 | 55.41 | 54.02 |
| Al ₂ O ₃ | 28.36 | 31.12 | 29.68 |
| Fe ₂ O ₃ | 7.29 | 6.03 | 7.15 |
| TiO ₂ | 0.79 | 0.68 | 0.69 |
| P ₂ O ₅ | 0.13 | 0.13 | 0.20 |
| CaO | 1.16 | 0.44 | 0.64 |
| MgO | 1.21 | 0.87 | 0.85 |
| SO ₃ | 0.82 | 0.19 | 0.43 |
| Na ₂ O | 0.27 | 0.26 | 0.26 |
| K ₂ O | 3.05 | 3.48 | 3.27 |
| SrO | 0.04 | 0.04 | 0.06 |
| BaO | 0.11 | 0.09 | 0.11 |
| LOF | 1.17 | 0.78 | 0.83 |

Notes:

THORBURN MINING LIMITED
Coal Reclamation Project; Waste Dumps; Pictou Coalfield
Stellarton, Pictou County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|-------------|--------------|
| Sampling date | 22-5-81 | | |
| Sampling location | Stellarton Wash Plant | | |
| Product name | Raw Feed | Screen | Slack |
| Screen opening, mm | | Plus 19, sq | Minus 19, sq |
| ERL number | 2627-82 | 2625-82 | 2626-82 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 1.37 | 1.30 |
| Ash | % | 37.41 | 29.35 |
| Volatile matter | % | 23.93 | 23.58 |
| Fixed carbon | % | 37.29 | 45.77 |
| Sulphur, as rec'd | % | 0.93 | 1.09 |
| Calorific value, as rec'd: | | | |
| | MJ/kg | 18.58 | 24.33 |
| | Btu/lb | 7988 | 10 458 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 47.22 | 58.48 |
| Hydrogen | % | 3.04 | 3.74 |
| Sulphur | % | 0.94 | 1.10 |
| Nitrogen | % | 0.90 | 1.11 |
| Ash | % | 37.93 | 29.74 |
| Oxygen, by difference | % | 9.97 | 5.83 |
| Trace mercury | µg/g (ppm) | 0.06 | 0.08 |
| | | | 0.10 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1085 | 1296 |
| Spherical | °C | 1313 | 1460 |
| Hemispherical | °C | 1335 | 1463 |
| Fluid | °C | 1363 | 1482+ |
| Hardgrove grindability index | | 54 | 54 |
| Free swelling index | | 0.5 | 1.0 |

Notes:

THORBURN MINING LIMITED
 Coal Reclamation Project; Waste Dumps; Pictou Coalfield
 Stellarton, Pictou County, Nova Scotia

| | | | |
|--------------------|-----------------------|-------------|--------------|
| Sampling date | 22-5-81 | | |
| Sampling location | Stellarton Wash Plant | | |
| Product name | Raw Feed | Screen | Slack |
| Screen opening, mm | | Plus 19, sq | Minus 19, sq |
| ERL number | 2627-82 | 2625-82 | 2626-82 |

Sulphur Forms (dry basis):

| | |
|-----------------------|---|
| Pyritic sulphur | % |
| Sulfate sulphur | % |
| Organic sulphur | % |

Moisture (as rec'd):

| | | | | |
|----------------|---|------|------|------|
| Inherent | % | 1.37 | 1.30 | 1.54 |
| Adherent | % | - | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|-------|-------|-------|
| SiO ₂ | 47.50 | 51.08 | 56.36 |
| Al ₂ O ₃ | 23.70 | 25.68 | 27.82 |
| Fe ₂ O ₃ | 14.86 | 8.74 | 7.88 |
| TiO ₂ | 0.62 | 0.66 | 0.73 |
| P ₂ O ₅ | 0.27 | 0.22 | 0.20 |
| CaO | 3.93 | 3.45 | 0.98 |
| MgO | 2.90 | 2.27 | 0.90 |
| SO ₃ | 2.82 | 3.13 | 0.46 |
| Na ₂ O | 0.22 | 0.27 | 0.27 |
| K ₂ O | 2.20 | 2.56 | 2.58 |
| SrO | 0.03 | 0.04 | 0.06 |
| BaO | 0.16 | 0.07 | 0.06 |
| LOF | 0.41 | 0.77 | 0.20 |

Notes:

THORBURN MINING LIMITED
 Coal Reclamation Project; Waste Dumps; Pictou Coalfield
 Stellarton, Pictou County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|-------------|--------------|
| Sampling date | 18-9-81 | | |
| Sampling location | Stellarton Wash Plant | | |
| Product name | Raw Feed | Screen | Slack |
| Screen opening, mm | | Plus 19, sq | Minus 19, sq |
| ERL number | 4644-81 | 4642-81 | 4643-81 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 2.16 | 7.20 |
| Ash | % | 67.92 | 25.87 |
| Volatile matter | % | 15.88 | 25.14 |
| Fixed carbon | % | 14.04 | 41.79 |
| Sulphur, as rec'd | % | 1.86 | 0.61 |
| Calorific value, as rec'd: | | | |
| | MJ/kg | 6.92 | 21.96 |
| | Btu/lb | 2975 | 9441 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 19.56 | 57.87 |
| Hydrogen | % | 1.66 | 3.68 |
| Sulphur | % | 1.90 | 0.66 |
| Nitrogen | % | 0.56 | 1.51 |
| Ash | % | 69.42 | 27.88 |
| Oxygen, by difference | % | 6.90 | 8.40 |
| Trace mercury | µg/g (ppm) | 0.04 | 0.09 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1157 | 1429 |
| Spherical | °C | 1332 | 1471 |
| Hemispherical | °C | 1393 | 1482+ |
| Fluid | °C | 1418 | 1482+ |
| Hardgrove grindability index | | 67 | 51 |
| Free swelling index | NA | 0.5 | 0.5 |

Notes:

THORBURN MINING LIMITED
 Coal Reclamation Project; Waste Dumps; Pictou Coalfield
 Stellarton, Pictou County, Nova Scotia

| | | | |
|--------------------------------|-----------------------|-------------|--------------|
| Sampling date | 18-9-81 | | |
| Sampling location | Stellarton Wash Plant | | |
| Product name | Raw Feed | Screen | Slack |
| Screen opening, mm | | Plus 19, sq | Minus 19, sq |
| ERL number | 4644-81 | 4642-81 | 4643-81 |
| Sulphur Forms (dry basis): | | | |
| Pyritic sulphur | % | 1.74 | 0.57 |
| Sulfate sulphur | % | 0.13 | 0.03 |
| Organic sulphur | % | 0.03 | 0.00 |
| Moisture (as rec'd): | | | |
| Inherent | % | 2.16 | 2.56 |
| Adherent | % | - | 4.63 |
| Ash analysis, %: | | | |
| SiO ₂ | | 51.01 | 56.97 |
| Al ₂ O ₃ | | 23.29 | 28.01 |
| Fe ₂ O ₃ | | 16.68 | 5.30 |
| TiO ₂ | | 0.75 | 0.92 |
| P ₂ O ₅ | | 0.15 | 0.09 |
| CaO | | 1.18 | 2.13 |
| MgO | | 1.48 | 1.13 |
| SO ₃ | | 1.56 | 0.73 |
| Na ₂ O | | 0.23 | 0.37 |
| K ₂ O | | 2.63 | 2.91 |
| SrO | | 0.01 | 0.03 |
| BaO | | 0.05 | 0.00 |
| LOF | | 0.20 | 0.40 |

Notes:

NOVACO LIMITED
Sydney Main Seam; Sydney Coalfield
Point Aconi, Cape Breton County, Nova Scotia

| | | | |
|-------------------------------|----------------------------|----------|--------|
| Sampling date | 12-3-81 | 9-3-81 | |
| Sampling location | | | |
| Product name | Slack | Mine Run | |
| Screen opening, mm | Minus 38, rd | | |
| ERL number | 3337-81 | 3338-81 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 12.79 | 7.71 |
| Ash | % | 9.11 | 14.24 |
| Volatile matter | % | 31.16 | 31.60 |
| Fixed carbon | % | 46.94 | 46.45 |
| Sulphur, as rec'd | % | 4.16 | 5.36 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 25.98 | 25.38 |
| Btu/lb | | 11 169 | 10 912 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 71.77 | 66.05 |
| Hydrogen | % | 4.26 | 4.12 |
| Sulphur | % | 4.77 | 5.81 |
| Nitrogen | % | 1.03 | 0.98 |
| Ash | % | 10.45 | 15.43 |
| Oxygen, by difference | % | 7.72 | 7.61 |
| Trace mercury | µg/g (ppm) | 0.17 | 0.30 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1085 | 1096 |
| Spherical | °C | 1107 | 1135 |
| Hemispherical | °C | 1113 | 1204 |
| Fluid | °C | 1318 | 1285 |
| Hardgrove grindability index | | 58 | 58 |
| Free swelling index | | 3.5 | 3.5 |

Notes: A wholly owned Provincial Crown Corporation

NOVACO LIMITED
Sydney Main Seam; Sydney Coalfield
Point Aconi, Cape Breton County, Nova Scotia

| | | |
|--------------------|--------------|----------|
| Sampling date | 12-3-81 | 9-3-81 |
| Sampling location | | |
| Product name | Slack | Mine Run |
| Screen opening, mm | Minus 38, rd | |
| ERL number | 3337-81 | 3338-81 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 3.18 | 4.38 |
| Sulfate sulphur | % | 0.09 | 0.24 |
| Organic sulphur | % | 1.50 | 1.19 |


Moisture (as rec'd):

| | | | |
|----------------|---|-------|------|
| Inherent | % | 2.10 | 2.82 |
| Adherent | % | 10.69 | 4.89 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 30.85 | 33.96 |
| Al ₂ O ₃ | | 14.99 | 15.20 |
| Fe ₂ O ₃ | | 48.68 | 46.70 |
| TiO ₂ | | 0.63 | 0.66 |
| P ₂ O ₅ | | 0.14 | 0.07 |
| CaO | | 1.13 | 0.78 |
| MgO | | 0.00 | 0.00 |
| SO ₃ | | 1.11 | 0.71 |
| Na ₂ O | | 0.32 | 0.30 |
| K ₂ O | | 1.63 | 1.92 |
| SrO | | 0.01 | 0.00 |
| BaO | | 0.00 | 0.00 |
| LOF | | 0.49 | 0.52 |

Notes:



COAL ANALYSES - NEW BRUNSWICK

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|-------------------------------|----------------------------|------------------|
| Sampling date | 20-8-79 | 30-9-80 |
| Sampling location | Dragline 8200 | Dragline 8200 |
| Product name | Seam Sample | Seam Sample |
| Screen opening, mm | | |
| ERL number | 3778-80 | 4591-80 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 2.07 |
| Ash | % | 14.41 |
| Volatile matter | % | 32.79 |
| Fixed carbon | % | 50.73 |
| Sulphur, as rec'd | % | 5.84 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 28.17 |
| Btu/lb | 12 599 | 12 111 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 69.92 |
| Hydrogen | % | 4.37 |
| Sulphur | % | 5.96 |
| Nitrogen | % | 0.76 |
| Ash | % | 14.72 |
| Oxygen, by difference | % | 4.27 |
| Trace mercury | µg/g (ppm) | 0.25 |
| Ash fusibility temperature: | | |
| Initial | °C | 1000 |
| Spherical | °C | 1015 |
| Hemispherical | °C | 1055 |
| Fluid | °C | 1110 |
| Hardgrove grindability index | | 61 |
| Free swelling index | | 6.0 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------|------------------|------------------|
| Sampling date | 20-8-79 | 30-9-80 |
| Sampling location | Dragline 8200 | Dragline 8200 |
| Product name | Seam Sample | Seam Sample |
| Screen opening, mm | | |
| ERL number | 3778-80 | 4591-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 4.47 | 5.73 |
| Sulfate sulphur | % | 0.09 | 0.00 |
| Organic sulphur | % | 1.40 | 1.22 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.32 | 1.02 |
| Adherent | % | 0.75 | 2.31 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 34.78 | 35.80 |
| Al ₂ O ₃ | | 10.80 | 11.10 |
| Fe ₂ O ₃ | | 40.68 | 41.21 |
| TiO ₂ | | 0.64 | 0.59 |
| P ₂ O ₅ | | 2.84 | 2.08 |
| CaO | | 5.12 | 3.99 |
| MgO | | 0.41 | 0.46 |
| SO ₃ | | 1.07 | 1.19 |
| Na ₂ O | | 0.19 | 0.12 |
| K ₂ O | | 0.69 | 0.88 |
| SrO | | 0.00 | 0.01 |
| BaO | | 0.00 | 0.12 |
| LOF | | 0.18 | 2.44 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|-------------------------------|---------------------------------|----------|
| Sampling date | 30-9-80 | 1-10-80 |
| Sampling location | Grand Lake Power Station (NBEP) | |
| | Dragline 8200 | |
| Product name | | Mine Run |
| Screen opening, mm | | |
| ERL number | 4592-80 | 4593-80 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 3.51 |
| Ash | % | 16.92 |
| Volatile matter | % | 31.03 |
| Fixed carbon | % | 48.54 |
| Sulphur, as rec'd | % | 7.50 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 27.66 |
| Btu/lb | | 11 891 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 68.86 |
| Hydrogen | % | 4.80 |
| Sulphur | % | 7.77 |
| Nitrogen | % | 0.93 |
| Ash | % | 17.54 |
| Oxygen, by difference | % | 0.10 |
| Trace mercury | µg/g (ppm) | 0.29 |
| | | 0.33 |
| Ash fusibility temperature: | | |
| Initial | °C | 1060 |
| Spherical | °C | 1077 |
| Hemispherical | °C | 1165 |
| Fluid | °C | 1204 |
| Hardgrove grindability index | | 65 |
| Free swelling index | | 6.5 |
| Notes: | | 6.0 |

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|-------------------|--|---------|
| Sampling date | 30-9-80 | 1-10-80 |
| Sampling location | Grand Lake Power Station (NBEPIC) Dragline 8200 | |

| | |
|--------------------|----------|
| Product name | Mine Run |
| Screen opening, mm | |

| | | |
|------------|---------|---------|
| ERL number | 4592-80 | 4593-80 |
|------------|---------|---------|

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 6.64 | 6.16 |
| Sulfate sulphur | % | 0.04 | 0.06 |
| Organic sulphur | % | 1.09 | 1.49 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 0.82 | 0.97 |
| Adherent | % | 2.69 | 2.45 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 31.99 | 33.14 |
| Al ₂ O ₃ | | 11.19 | 11.58 |
| Fe ₂ O ₃ | | 45.34 | 42.46 |
| TiO ₂ | | 0.49 | 0.49 |
| P ₂ O ₅ | | 1.54 | 1.72 |
| CaO | | 3.47 | 3.84 |
| MgO | | 0.52 | 0.49 |
| SO ₃ | | 1.31 | 1.64 |
| Na ₂ O | | 0.12 | 0.13 |
| K ₂ O | | 1.24 | 1.29 |
| SrO | | 0.00 | 0.00 |
| BaO | | 0.10 | 0.12 |
| LOF | | 3.14 | 2.94 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | | |
|--------------------------------|-------------------------------|-------------------------------|---|
| Sampling date | 22-8-79 | 3-10-80 | 3-10-80 |
| Sampling location | Dragline 7200 ² | Dragline 7200 ² | Grand Lake Power Stn (NBEPIC) Dragline 7200 ² |
| Product name | Seam Sample | Seam Sample | Mine Run |
| Screen opening, mm | | | |
| ERL number | 3785-80 | 4599-80 | 4600-80 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 4.21 | 2.99 |
| Ash | % | 19.63 | 13.95 |
| Volatile matter | % | 33.73 | 32.22 |
| Fixed carbon | % | 52.44 | 51.14 |
| Sulphur, as rec'd | % | 10.74 | 7.94 |
| Calorific value, as rec'd: | | | |
| MJ/kg | 25.37 | 29.23 | 29.35 |
| Btu/lb | 10 904 | 12 565 | 12 619 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 61.40 | 68.93 |
| Hydrogen | % | 3.63 | 4.62 |
| Sulphur | % | 11.21 | 8.18 |
| Nitrogen | % | 0.63 | 0.93 |
| Ash | % | 20.49 | 14.38 |
| Oxygen, by difference | % | 2.90 | 2.96 |
| Trace mercury μg/g (ppm) | 1.25 | 0.26 | 0.25 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1045 | 1043 |
| Spherical | °C | 1105 | 1049 |
| Hemispherical | °C | 1125 | 1055 |
| Fluid | °C | 1190 | 1115 |
| Hardgrove grindability index | 59 | 64 | 64 |
| Free swelling index | 3.5 | 7.0 | 6.5 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | | |
|--------------------------------|-------------------------------|-------------------------------|---|
| Sampling date | 22-8-79 | 3-10-80 | 3-10-80 |
| Sampling location | Dragline 7200 ² | Dragline 7200 ² | Grand Lake Power Stn (NBEPIC) Dragline 7200 ² |
| Product name | Seam Sample | Seam Sample | Mine Run |
| Screen opening, mm | | | |
| ERL number | 3785-80 | 4599-80 | 4600-80 |
| <hr/> | | | |
| Sulphur Forms (dry basis): | | | |
| Pyritic sulphur | % | 8.52 | 6.92 |
| Sulfate sulphur | % | 1.00 | 0.08 |
| Organic sulphur | % | 1.69 | 1.18 |
| <hr/> | | | |
| Moisture (as rec'd): | | | |
| Inherent | % | 2.27 | 1.00 |
| Adherent | % | 1.94 | 1.99 |
| <hr/> | | | |
| Ash analysis, %: | | | |
| SiO ₂ | | 16.41 | 18.35 |
| Al ₂ O ₃ | | 6.14 | 5.71 |
| Fe ₂ O ₃ | | 62.15 | 62.66 |
| TiO ₂ | | 0.26 | 0.30 |
| P ₂ O ₅ | | 1.29 | 1.67 |
| CaO | | 6.80 | 5.05 |
| MgO | | 0.30 | 0.44 |
| SO ₃ | | 5.13 | 2.16 |
| Na ₂ O | | 0.12 | 0.12 |
| K ₂ O | | 0.32 | 0.42 |
| SrO | | 0.00 | 0.01 |
| BaO | | 0.03 | 0.01 |
| LOF | | 1.04 | 2.21 |
| | | | 1.75 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|-------------------------------|---|----------------------------|
| Sampling date | 21-8-79 | 22-8-79 |
| Sampling location | Grand Lake Power Station (NBEPC) Dragline 9W | |
| Product name | | Mine Run |
| Screen opening, mm | | |
| ERL number | 3779-80 | 3780-80 |
| Rank of coal | | High-volatile A bituminous |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 2.43 |
| Ash | % | 20.61 |
| Volatile matter | % | 31.85 |
| Fixed carbon | % | 45.11 |
| Sulphur, as rec'd | % | 7.12 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 24.17 |
| Btu/lb | | 10 393 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 63.91 |
| Hydrogen | % | 4.13 |
| Sulphur | % | 7.30 |
| Nitrogen | % | 0.63 |
| Ash | % | 21.13 |
| Oxygen, by difference | % | 2.90 |
| Trace mercury | µg/g (ppm) | 0.55 |
| Ash fusibility temperature: | | |
| Initial | °C | 1010 |
| Spherical | °C | 1105 |
| Hemispherical | °C | 1145 |
| Fluid | °C | 1205 |
| Hardgrove grindability index | | 64 |
| Free swelling index | | 4.0 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------------------|--|----------|
| Sampling date | 21-8-79 | 22-8-79 |
| Sampling location | Grand Lake Power Station (NBEPIC) Dragline 9W | |
| Product name | | Mine Run |
| Screen opening, mm | | |
| ERL number | 3779-80 | 3780-80 |
| Sulphur Forms (dry basis): | | |
| Pyritic sulphur | % | 5.68 |
| Sulfate sulphur | % | 0.25 |
| Organic sulphur | % | 1.37 |
| Moisture (as rec'd): | | |
| Inherent | % | 1.25 |
| Adherent | % | 1.18 |
| Ash analysis, %: | | |
| SiO ₂ | | 28.07 |
| Al ₂ O ₃ | | 11.42 |
| Fe ₂ O ₃ | | 39.41 |
| TiO ₂ | | 0.44 |
| P ₂ O ₅ | | 0.50 |
| CaO | | 6.88 |
| MgO | | 0.72 |
| SO ₃ | | 7.55 |
| Na ₂ O | | 0.15 |
| K ₂ O | | 1.57 |
| SrO | | 0.00 |
| BaO | | 0.06 |
| LOF | | 1.35 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|---|----------------------------|----------------|
| Sampling date | 24-8-79 | 3-10-80 |
| Sampling location | Dragline 9W | Dragline 9W |
| Product name | Seam Sample | Seam Sample |
| Screen opening, mm | | |
| ERL number | 3781-80 | 4603-80 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 1.70 |
| Ash | % | 18.84 |
| Volatile matter | % | 33.37 |
| Fixed carbon | % | 46.09 |
| Sulphur, as rec'd | % | 8.00 |
| Calorific value, as rec'd: | | |
| MJ/kg | 27.51 | 27.15 |
| Btu/lb | 11 827 | 11 674 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 63.40 |
| Hydrogen | % | 4.02 |
| Sulphur | % | 8.14 |
| Nitrogen | % | 0.87 |
| Ash | % | 19.17 |
| Oxygen, by difference | % | 4.40 |
| Trace mercury μg/g (ppm) | 0.76 | 0.71 |
| Ash fusibility temperature: | | |
| Initial | °C | 1070 |
| Spherical | °C | 1116 |
| Hemispherical | °C | 1140 |
| Fluid | °C | 1165 |
| Hardgrove grindability index | 64 | - |
| Free swelling index | 4.5 | 6.0 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------|----------------|----------------|
| Sampling date | 24-8-79 | 3-10-80 |
| Sampling location | Dragline 9W | Dragline 9W |
| Product name | Seam Sample | Seam Sample |
| Screen opening, mm | | |
| ERL number | 3781-80 | 4603-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 6.69 | 6.77 |
| Sulfate sulphur | % | 0.35 | 0.07 |
| Organic sulphur | % | 1.10 | 1.01 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.18 | 0.82 |
| Adherent | % | 0.52 | 0.91 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 33.86 | 26.28 |
| Al ₂ O ₃ | | 10.00 | 10.59 |
| Fe ₂ O ₃ | | 45.76 | 39.40 |
| TiO ₂ | | 0.57 | 0.44 |
| P ₂ O ₅ | | 0.78 | 1.22 |
| CaO | | 3.11 | 8.22 |
| MgO | | 0.35 | 0.67 |
| SO ₃ | | 2.45 | 6.48 |
| Na ₂ O | | 0.20 | 0.09 |
| K ₂ O | | 0.80 | 1.46 |
| SrO | | 0.00 | 0.01 |
| BaO | | 0.10 | 0.03 |
| LOF | | 0.00 | 2.41 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield.
 Minto, Sunbury/Queens Counties, New Brunswick

| | | | |
|-------------------------------|--|----------|------------------|
| Sampling date | 6-12-78 | 7-12-78 | 4-10-80 |
| Sampling location | Grand Lake Power Station (NBEPIC) Dragline 500W | | Dragline 500W |
| Product name | Mine Run | Mine Run | Seam Sample |
| Screen opening, mm | | | |
| ERL number | 2101-79 | 2102-79 | 4604-80 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 4.85 | 2.61 |
| Ash | % | 22.23 | 19.13 |
| Volatile matter | % | 28.80 | 31.36 |
| Fixed carbon | % | 44.12 | 46.90 |
| Sulphur, as rec'd | % | 9.55 | 9.19 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 25.14 | 28.40 |
| Btu/lb | | 10 809 | 12 210 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 60.76 | 60.63 |
| Hydrogen | % | 4.37 | 4.13 |
| Sulphur | % | 10.04 | 9.44 |
| Nitrogen | % | 0.78 | 0.73 |
| Ash | % | 23.36 | 19.64 |
| Oxygen, by difference | % | 0.69 | 5.43 |
| Trace mercury | µg/g (ppm) | 0.85 | 0.68 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1110 | 1115 |
| Spherical | °C | 1125 | 1140 |
| Hemispherical | °C | 1175 | 1175 |
| Fluid | °C | 1270 | 1275 |
| Hardgrove grindability index | | 62 | 62 |
| Free swelling index | | 6.0 | 7.5 |
| Notes: | | | 6.5 |

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | | |
|--------------------|--|----------|------------------|
| Sampling date | 6-12-78 | 7-12-78 | 4-10-80 |
| Sampling location | Grand Lake Power Station (NBEPIC) Dragline 500W | | Dragline 500W |
| Product name | Mine Run | Mine Run | Seam Sample |
| Screen opening, mm | | | |
| ERL number | 2101-79 | 2102-79 | 4604-80 |

Sulphur Forms (dry basis):

| | | | | |
|-----------------------|---|------|------|------|
| Pyritic sulphur | % | 8.25 | 7.65 | 5.63 |
| Sulfate sulphur | % | 0.37 | 0.17 | 0.09 |
| Organic sulphur | % | 1.42 | 1.62 | 1.74 |

Moisture (as rec'd):

| | | | | |
|----------------|---|------|------|------|
| Inherent | % | 0.96 | 0.41 | 1.03 |
| Adherent | % | 3.89 | 2.20 | 1.52 |

Ash analysis, %:

| | | | | |
|--------------------------------|--|-------|-------|-------|
| SiO ₂ | | 28.00 | 28.62 | 27.60 |
| Al ₂ O ₃ | | 10.98 | 10.51 | 9.29 |
| Fe ₂ O ₃ | | 23.88 | 24.79 | 46.43 |
| TiO ₂ | | 0.51 | 0.50 | 0.47 |
| P ₂ O ₅ | | 0.66 | 1.05 | 2.69 |
| CaO | | 2.00 | 1.94 | 6.42 |
| MgO | | 0.60 | 0.64 | 0.65 |
| SO ₃ | | 2.07 | 0.81 | 2.45 |
| Na ₂ O | | 0.05 | 0.07 | 0.12 |
| K ₂ O | | 1.25 | 1.08 | 0.88 |
| SrO | | - | - | 0.01 |
| BaO | | - | - | 0.00 |
| LOF | | - | - | 2.81 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | | |
|-------------------------------|---|----------|-------------------|
| Sampling date | 6-12-78 | 7-12-78 | 4-10-80 |
| Sampling location | Grand Lake Power Station (NBEPIC) Dragline 7400W | | Dragline 7400W |
| Product name | Mine Run | Mine Run | Seam Sample |
| Screen opening, mm | | | |
| ERL number | 2103-79 | 2104-79 | 3786-80 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 2.46 | 2.19 |
| Ash | % | 22.73 | 13.25 |
| Volatile matter | % | 30.46 | 36.32 |
| Fixed carbon | % | 44.35 | 48.24 |
| Sulphur, as rec'd | % | 9.58 | 6.87 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 25.79 | 29.74 |
| Btu/lb | | 11 091 | 12 788 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 60.46 | 71.15 |
| Hydrogen | % | 4.20 | 4.47 |
| Sulphur | % | 9.83 | 7.02 |
| Nitrogen | % | 0.72 | 1.07 |
| Ash | % | 23.31 | 13.55 |
| Oxygen, by difference | % | 1.48 | 2.74 |
| Trace mercury | µg/g (ppm) | 0.77 | 0.23 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1095 | 1060 |
| Spherical | °C | 1110 | 1110 |
| Hemispherical | °C | 1150 | 1180 |
| Fluid | °C | 1220 | 1205 |
| Hardgrove grindability index | | 64 | 62 |
| Free swelling index | | 7.0 | 6.5 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | | |
|--------------------------------|---|----------|-------------------|
| Sampling date | 6-12-78 | 7-12-78 | 22-8-79 |
| Sampling location | Grand Lake Power Station (NBEPIC) Dragline 7400W | | Dragline 7400W |
| Product name | Mine Run | Mine Run | Seam Sample |
| Screen opening, mm | | | |
| ERL number | 2103-79 | 2104-79 | 3786-80 |
| <hr/> | | | |
| Sulphur Forms (dry basis): | | | |
| Pyritic sulphur | % | 8.08 | 5.70 |
| Sulfate sulphur | % | 0.30 | 0.27 |
| Organic sulphur | % | 1.45 | 1.05 |
| <hr/> | | | |
| Moisture (as rec'd): | | | |
| Inherent | % | 0.67 | 1.43 |
| Adherent | % | 1.79 | 0.76 |
| <hr/> | | | |
| Ash analysis, %: | | | |
| SiO ₂ | | 30.39 | 23.27 |
| Al ₂ O ₃ | | 11.48 | 9.76 |
| Fe ₂ O ₃ | | 50.41 | 56.68 |
| TiO ₂ | | 0.54 | 0.42 |
| P ₂ O ₅ | | 0.88 | 1.37 |
| CaO | | 2.17 | 2.97 |
| MgO | | 0.93 | 0.39 |
| SO ₃ | | 1.80 | 2.02 |
| Na ₂ O | | 0.05 | 0.14 |
| K ₂ O | | 1.35 | 1.10 |
| SrO | - | - | 0.00 |
| BaO | - | - | 0.02 |
| LOF | - | - | 0.30 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------|----------------------|-------------|
| Sampling date | 5-12-78 | |
| Sampling location | Wash Plant, Midlands | |
| Product name | Screen | Nut |
| Screen opening, mm | Plus 102, sq | 64 x 19, sq |
| ERL number | 2095-78 | 2096-78 |

Rank of coal High-volatile A bituminous

Proximate analysis, as rec'd:

| | | | |
|-----------------------|---|-------|-------|
| Moisture | % | 0.80 | 1.26 |
| Ash | % | 15.84 | 17.50 |
| Volatile matter | % | 33.41 | 31.94 |
| Fixed carbon | % | 49.95 | 49.30 |

| | | | |
|-------------------------|---|------|------|
| Sulphur, as rec'd | % | 6.65 | 9.38 |
|-------------------------|---|------|------|

Calorific value, as rec'd:

| | | |
|--------|--------|--------|
| MJ/kg | 29.33 | 28.27 |
| Btu/lb | 12 611 | 12 152 |

Ultimate analysis, dry basis:

| | | | |
|----------------------------|---|-------|-------|
| Carbon | % | 68.91 | 65.67 |
| Hydrogen | % | 4.93 | 4.66 |
| Sulphur | % | 6.70 | 9.50 |
| Nitrogen | % | 0.90 | 0.92 |
| Ash | % | 15.97 | 17.72 |
| Oxygen, by difference | % | 2.59 | 1.53 |

| | | | |
|---------------|------------|------|------|
| Trace mercury | µg/g (ppm) | 0.44 | 0.73 |
|---------------|------------|------|------|

Ash fusibility temperature:

| | | | |
|---------------------|----|------|------|
| Initial | °C | 1055 | 1110 |
| Spherical | °C | 1095 | 1145 |
| Hemispherical | °C | 1210 | 1200 |
| Fluid | °C | 1215 | 1260 |

| | | |
|------------------------------|----|----|
| Hardgrove grindability index | 60 | 59 |
|------------------------------|----|----|

| | | |
|---------------------------|-----|-----|
| Free swelling index | 7.0 | 6.5 |
|---------------------------|-----|-----|

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------------------|----------------------|-------------|
| Sampling date | 5-12-78 | |
| Sampling location | Wash Plant, Midlands | |
| Product name | Screen | Nut |
| Screen opening, mm | Plus 102, sq | 64 x 19, sq |
| ERL number | 2095-78 | 2096-78 |
| Sulphur Forms (dry basis): | | |
| Pyritic sulphur | % | 4.82 |
| Sulfate sulphur | % | 0.05 |
| Organic sulphur | % | 1.83 |
| Moisture (as rec'd): | | |
| Inherent | % | 0.80 |
| Adherent | % | - |
| Ash analysis, %: | | |
| SiO ₂ | | 36.26 |
| Al ₂ O ₃ | | 11.01 |
| Fe ₂ O ₃ | | 43.01 |
| TiO ₂ | | 0.68 |
| P ₂ O ₅ | | 1.63 |
| CaO | | 3.73 |
| MgO | | 0.56 |
| SO ₃ | | 2.47 |
| Na ₂ O | | 0.04 |
| K ₂ O | | 0.54 |
| SrO | | - |
| BaO | | - |
| LOF | | - |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | | |
|--------------------------------|----------------------------|---------------|--------|
| Sampling date | 5-12-78 | | |
| Sampling location | Wash Plant, Midlands | | |
| Product name | Stoker Pea | Fines | |
| Screen opening, mm | 19 x 6.4, sq | Minus 6.4, sq | |
| ERL number | 2097-79 | 2098-79 | |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 1.51 | 5.87 |
| Ash | % | 14.64 | 19.23 |
| Volatile matter | % | 33.32 | 30.49 |
| Fixed carbon | % | 50.53 | 44.41 |
| Sulphur, as rec'd | % | 7.83 | 7.18 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 25.63 | 25.07 |
| Btu/lb | | 12 728 | 11 201 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 70.11 | 64.88 |
| Hydrogen | % | 4.95 | 4.64 |
| Sulphur | % | 7.95 | 7.63 |
| Nitrogen | % | 0.89 | 0.84 |
| Ash | % | 14.86 | 20.42 |
| Oxygen, by difference | % | 1.24 | 1.59 |
| Trace mercury μg/g (ppm) | | 0.49 | 0.47 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1045 | 1075 |
| Spherical | °C | 1100 | 1120 |
| Hemispherical | °C | 1145 | 1195 |
| Fluid | °C | 1315 | 1200 |
| Hardgrove grindability index | | 59 | 64 |
| Free swelling index | | 7.5 | 6.5 |

Notes:

N.B. COAL LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------|----------------------|---------------|
| Sampling date | 5-12-78 | |
| Sampling location | Wash Plant, Midlands | |
| Product name | Stoker Pea | Fines |
| Screen opening, mm | 19 x 6.4, sq | Minus 6.4, sq |
| ERL number | 2097-79 | 2098-79 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 5.93 | 5.63 |
| Sulfate sulphur | % | 0.08 | 0.37 |
| Organic sulphur | % | 1.94 | 1.63 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 0.81 | 1.38 |
| Adherent | % | 0.70 | 4.49 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 26.21 | 32.08 |
| Al ₂ O ₃ | | 8.72 | 12.59 |
| Fe ₂ O ₃ | | 55.80 | 40.98 |
| TiO ₂ | | 0.49 | 0.54 |
| P ₂ O ₅ | | 1.52 | 1.20 |
| CaO | | 3.46 | 4.92 |
| MgO | | 0.50 | 1.01 |
| SO ₃ | | 2.47 | 4.90 |
| Na ₂ O | | 0.12 | 0.07 |
| K ₂ O | | 0.69 | 1.68 |
| SrO | | - | - |
| BaO | | - | - |
| LOF | | - | - |

Notes:

KNOX CONSTRUCTION LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|-------------------------------------|----------------------------------|------------------|
| Sampling date | 6-12-78 | 7-12-78 |
| Sampling location | Grand Lake Power Station (NBEPC) | Dragline 4500 |
| Product name | | Mine Run |
| Screen opening, mm | | |
| ERL number | 2099-79 | 2100-79 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 2.55 3.19 |
| Ash | % | 19.11 18.45 |
| Volatile matter | % | 31.37 31.33 |
| Fixed carbon | % | 46.97 47.03 |
| Sulphur, as rec'd | % | 8.14 8.60 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 27.67 27.28 |
| Btu/lb | | 11 895 11 729 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 65.45 65.25 |
| Hydrogen | % | 4.64 4.41 |
| Sulphur | % | 8.36 8.88 |
| Nitrogen | % | 0.73 0.76 |
| Ash | % | 19.61 19.06 |
| Oxygen, by difference | % | 1.21 1.64 |
| Trace mercury $\mu\text{g/g}$ (ppm) | | 0.71 0.88 |
| Ash fusibility temperature: | | |
| Initial | °C | 1100 1120 |
| Spherical | °C | 1120 1140 |
| Hemispherical | °C | 1230 1245 |
| Fluid | °C | 1288 1290 |
| Hardgrove grindability index | | 64 64 |
| Free swelling index | | 6.0 6.0 |

Notes:

KNOX CONSTRUCTION LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|-------------------|-----------------------------------|---------|
| Sampling date | 6-12-78 | 7-12-78 |
| Sampling location | Grand Lake Power Station (NBEPIC) | |
| | Dragline 4500 | |

| | |
|--------------------|----------|
| Product name | Mine Run |
| Screen opening, mm | |

| | | |
|------------|---------|---------|
| ERL number | 2099-79 | 2100-79 |
|------------|---------|---------|

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 6.58 | 7.27 |
| Sulfate sulphur | % | 0.10 | 0.35 |
| Organic sulphur | % | 1.68 | 1.26 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 0.58 | 1.09 |
| Adherent | % | 1.97 | 2.10 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 30.69 | 26.73 |
| Al ₂ O ₃ | | 12.16 | 10.79 |
| Fe ₂ O ₃ | | 49.54 | 54.97 |
| TiO ₂ | | 0.53 | 0.46 |
| P ₂ O ₅ | | 1.07 | 0.84 |
| CaO | | 2.41 | 2.14 |
| MgO | | 0.74 | 0.88 |
| SO ₃ | | 1.41 | 1.78 |
| Na ₂ O | | 0.00 | 0.05 |
| K ₂ O | | 1.30 | 1.36 |
| SrO | | - | - |
| BaO | | - | - |
| LOF | | - | - |

Notes:

KNOX CONSTRUCTION LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------------------|----------------------------------|---------------|
| Sampling date | 21-8-79 | 22-8-79 |
| Sampling location | Grand Lake Power Station (NBEPC) | Dragline 4500 |
| Product name | Mine Run | |
| Screen opening, mm | | |
| ERL number | 3782-80 | 3783-80 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 3.82 |
| Ash | % | 21.48 |
| Volatile matter | % | 31.43 |
| Fixed carbon | % | 43.27 |
| Sulphur, as rec'd | % | 9.51 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 27.20 |
| Btu/lb | | 11 694 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 61.48 |
| Hydrogen | % | 3.66 |
| Sulphur | % | 9.89 |
| Nitrogen | % | 0.79 |
| Ash | % | 22.34 |
| Oxygen, by difference | % | 1.84 |
| Trace mercury μg/g (ppm) | | 0.21 |
| Ash fusibility temperature: | | |
| Initial | °C | 1000 |
| Spherical | °C | 1060 |
| Hemispherical | °C | 1075 |
| Fluid | °C | 1190 |
| Hardgrove grindability index | | 66 |
| Free swelling index | | 4.0 |

Notes:

KNOX CONSTRUCTION LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|-------------------|----------------------------------|---------|
| Sampling date | 21-8-79 | 22-8-79 |
| Sampling location | Grand Lake Power Station (NBEPC) | |
| | Dragline 4500 | |

| | | |
|--------------------|----------|--|
| Product name | Mine Run | |
| Screen opening, mm | | |

| | | |
|------------|---------|---------|
| ERL number | 3782-80 | 3783-80 |
|------------|---------|---------|

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 8.22 | 5.81 |
| Sulfate sulphur | % | 0.61 | 0.60 |
| Organic sulphur | % | 1.06 | 1.60 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.60 | 1.97 |
| Adherent | % | 2.22 | 2.05 |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 21.61 | 29.68 |
| Al ₂ O ₃ | 8.13 | 10.04 |
| Fe ₂ O ₃ | 50.77 | 47.41 |
| TiO ₂ | 0.35 | 0.50 |
| P ₂ O ₅ | 0.50 | 1.26 |
| CaO | 6.96 | 4.19 |
| MgO | 0.00 | 0.54 |
| SO ₃ | 8.00 | 2.98 |
| Na ₂ O | 0.14 | 0.15 |
| K ₂ O | 0.93 | 0.89 |
| SrO | 0.00 | 0.00 |
| BaO | 0.08 | 0.07 |
| LOF | 0.54 | 0.38 |

Notes:

KNOX CONSTRUCTION LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------------------|----------------------------|------------------|
| Sampling date | 24-8-79 | 2-10-80 |
| Sampling location | Dragline 4500 | Dragline 4500 |
| Product name | Seam Sample | Seam Sample |
| Screen opening, mm | | |
| ERL number | 3784-80 | 4594-80 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 3.04 |
| Ash | % | 19.03 |
| Volatile matter | % | 32.67 |
| Fixed carbon | % | 45.26 |
| Sulphur, as rec'd | % | 10.84 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 26.40 |
| Btu/lb | | 11 349 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 61.93 |
| Hydrogen | % | 3.70 |
| Sulphur | % | 11.18 |
| Nitrogen | % | 0.47 |
| Ash | % | 19.63 |
| Oxygen, by difference | % | 3.09 |
| Trace mercury μg/g (ppm) | | 1.23 |
| Ash fusibility temperature: | | |
| Initial | °C | 1040 |
| Spherical | °C | 1100 |
| Hemispherical | °C | 1120 |
| Fluid | °C | 1165 |
| Hardgrove grindability index | | 66 |
| Free swelling index | | 3.5 |

Notes:

KNOX CONSTRUCTION LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------|------------------|------------------|
| Sampling date | 24-8-79 | 2-10-80 |
| Sampling location | Dragline 4500 | Dragline 4500 |
| Product name | Seam Sample | Seam Sample |
| Screen opening, mm | | |
| ERL number | 3784-80 | 4594-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 9.21 | 7.75 |
| Sulfate sulphur | % | 0.85 | 0.04 |
| Organic sulphur | % | 1.12 | 0.52 |

Moisture (as rec'd):

| | | | |
|----------------|---|------|------|
| Inherent | % | 1.60 | 0.88 |
| Adherent | % | 1.44 | 1.74 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 14.71 | 26.63 |
| Al ₂ O ₃ | | 5.50 | 11.10 |
| Fe ₂ O ₃ | | 66.27 | 38.75 |
| TiO ₂ | | 0.29 | 0.37 |
| P ₂ O ₅ | | 0.58 | 1.14 |
| CaO | | 5.15 | 7.59 |
| MgO | | 0.16 | 0.70 |
| SO ₃ | | 4.93 | 3.37 |
| Na ₂ O | | 0.12 | 0.09 |
| K ₂ O | | 0.47 | 1.55 |
| SrO | | 0.00 | 0.01 |
| BaO | | 0.00 | 0.19 |
| LOF | | 1.26 | 7.58 |

Notes:

KNOX CONSTRUCTION LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------------------|----------------------------------|---------------|
| Sampling date | 1-10-80 | 2-10-80 |
| Sampling location | Grand Lake Power Station (NBEPC) | Dragline 4500 |
| Product name | Mine Run | |
| Screen opening, mm | | |
| ERL number | 4595-80 | 4596-80 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 2.56 |
| Ash | % | 21.68 |
| Volatile matter | % | 32.08 |
| Fixed carbon | % | 43.68 |
| Sulphur, as rec'd | % | 7.80 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 26.86 |
| Btu/lb | 11 548 | 11 491 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 63.05 |
| Hydrogen | % | 4.30 |
| Sulphur | % | 8.00 |
| Nitrogen | % | 0.83 |
| Ash | % | 22.25 |
| Oxygen, by difference | % | 1.57 |
| Trace mercury μg/g (ppm) | | 0.61 |
| Ash fusibility temperature: | | |
| Initial | °C | 1060 |
| Spherical | °C | 1115 |
| Hemispherical | °C | 1132 |
| Fluid | °C | 1215 |
| Hardgrove grindability index | | 65 |
| Free swelling index | | 6.5 |

Notes:

KNOX CONSTRUCTION LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------------------|----------------------------------|---------------|
| Sampling date | 1-10-80 | 2-10-80 |
| Sampling location | Grand Lake Power Station (NBEPC) | Dragline 4500 |
| Product name | | Mine Run |
| Screen opening, mm | | |
| ERL number | 4595-80 | 4596-80 |
| <hr/> | | |
| Sulphur Forms (dry basis): | | |
| Pyritic sulphur | % | 6.90 |
| Sulfate sulphur | % | 0.06 |
| Organic sulphur | % | 1.04 |
| <hr/> | | |
| Moisture (as rec'd): | | |
| Inherent | % | 0.79 |
| Adherent | % | 1.77 |
| <hr/> | | |
| Ash analysis, %: | | |
| SiO ₂ | | 26.70 |
| Al ₂ O ₃ | | 10.97 |
| Fe ₂ O ₃ | | 38.84 |
| TiO ₂ | | 0.42 |
| P ₂ O ₅ | | 1.24 |
| CaO | | 8.41 |
| MgO | | 0.73 |
| SO ₃ | | 3.86 |
| Na ₂ O | | 0.10 |
| K ₂ O | | 1.55 |
| SrO | | 0.01 |
| BaO | | 0.15 |
| LOF | | 6.76 |

Notes:

KNOX CONSTRUCTION LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | | |
|-------------------------------|----------------------------|------------------|---|
| Sampling date | 23-8-79 | 3-10-80 | 3-10-80 |
| Sampling location | Dragline 200W | Dragline 200W | Grand Lake Power Stn (NBEPC) Dragline 200W |
| Product name | Seam Sample | Seam Sample | Mine Run |
| Screen opening, mm | | | |
| ERL number | 3787-80 | 4601-80 | 4602-80 |
| Rank of coal | High-volatile A bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 3.35 | 2.88 |
| Ash | % | 24.71 | 17.28 |
| Volatile matter | % | 28.51 | 31.64 |
| Fixed carbon | % | 43.43 | 48.20 |
| Sulphur, as rec'd | % | 11.59 | 7.68 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 23.37 | 28.05 |
| Btu/lb | | 10 044 | 12 254 |
| | | | 12 061 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 54.77 | 67.06 |
| Hydrogen | % | 3.12 | 4.34 |
| Sulphur | % | 12.00 | 7.91 |
| Nitrogen | % | 0.66 | 0.83 |
| Ash | % | 25.56 | 17.79 |
| Oxygen, by difference | % | 3.89 | 2.07 |
| Trace mercury | µg/g (ppm) | 0.96 | 0.29 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1030 | 1060 |
| Spherical | °C | 1105 | 1077 |
| Hemispherical | °C | 1115 | 1110 |
| Fluid | °C | 1210 | 1193 |
| Hardgrove grindability index | | 60 | 61 |
| Free swelling index | | 4.0 | 6.0 |
| Notes: | | | 5.5 |

KNOX CONSTRUCTION LIMITED
 Dragline Operations; Minto/Chipman Area; Minto Coalfield
 Minto, Sunbury/Queens Counties, New Brunswick

| | | | |
|-------------------|------------------|------------------|--|
| Sampling date | 23-8-79 | 3-10-80 | 3-10-80 |
| Sampling location | Dragline 200W | Dragline 200W | Grand Lake Power Stn (NBEPIC) Dragline 200W |

| | | | |
|--------------------|-------------|-------------|----------|
| Product name | Seam Sample | Seam Sample | Mine Run |
| Screen opening, mm | | | |

| | | | |
|------------|---------|---------|---------|
| ERL number | 3787-80 | 4601-80 | 4602-80 |
|------------|---------|---------|---------|

Sulphur Forms (dry basis):

| | | | | |
|-----------------------|---|------|------|------|
| Pyritic sulphur | % | 9.42 | 5.81 | 6.76 |
| Sulfate sulphur | % | 1.03 | 0.08 | 0.08 |
| Organic sulphur | % | 1.55 | 1.48 | 1.07 |

Moisture (as rec'd):

| | | | | |
|----------------|---|------|------|------|
| Inherent | % | 2.02 | 1.08 | 1.10 |
| Adherent | % | 1.33 | 1.80 | 1.78 |

Ash analysis, %:

| | | | | |
|--------------------------------|--|-------|-------|-------|
| SiO ₂ | | 27.75 | 25.57 | 27.50 |
| Al ₂ O ₃ | | 10.73 | 8.56 | 8.93 |
| Fe ₂ O ₃ | | 56.64 | 48.20 | 47.05 |
| TiO ₂ | | 0.56 | 0.40 | 0.41 |
| P ₂ O ₅ | | 0.35 | 2.33 | 2.54 |
| CaO | | 1.26 | 6.28 | 6.19 |
| MgO | | 0.57 | 0.51 | 0.51 |
| SO ₃ | | 1.06 | 3.14 | 3.56 |
| Na ₂ O | | 0.13 | 0.11 | 0.12 |
| K ₂ O | | 0.89 | 0.88 | 0.90 |
| SrO | | 0.00 | 0.01 | 0.01 |
| BaO | | 0.00 | 0.03 | 0.13 |
| LOF | | 0.32 | 1.55 | 0.78 |

Notes:

R. MILLS COAL LIMITED
 Coal Reclamation Project; Waste Dumps; Minto Coalfield
 Midlands, Sunbury/Queens Counties, New Brunswick

| | | |
|-------------------------------|-------------------------------------|-------------------------------------|
| Sampling date | 3-10-80 | 30-9-80 |
| Sampling location | Pilot Recovery Plant (Stockpile) | Grand Lake Power Station (NBEPC) |
| Product name | Fines | Fines |
| Screen opening, mm | Minus 6.4, sq | Minus 6.4, sq |
| ERL number | 4597-80 | 4598-80 |
| Rank of coal | High-volatile A bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 8.87 |
| Ash | % | 18.43 |
| Volatile matter | % | 29.45 |
| Fixed carbon | % | 43.25 |
| Sulphur, as rec'd | % | 5.01 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 20.61 |
| Btu/lb | | 8862 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 63.26 |
| Hydrogen | % | 4.45 |
| Sulphur | % | 5.50 |
| Nitrogen | % | 0.92 |
| Ash | % | 20.22 |
| Oxygen, by difference | % | 5.65 |
| Trace mercury | µg/g (ppm) | 0.33 |
| Ash fusibility temperature: | | |
| Initial | °C | 1071 |
| Spherical | °C | 1149 |
| Hemispherical | °C | 1232 |
| Fluid | °C | 1304 |
| Hardgrove grindability index | - | - |
| Free swelling index | 6.5 | 5.0 |

Notes: Fine coal is recovered on a pilot plant basis from settling pond sludge.

R. MILLS COAL LIMITED
 Coal Reclamation Project; Waste Dumps; Minto Coalfield
 Midlands, Sunbury/Queens Counties, New Brunswick

| | | |
|--------------------|-------------------------------------|-------------------------------------|
| Sampling date | 3-10-80 | 30-9-80 |
| Sampling location | Pilot Recovery Plant (Stockpile) | Grand Lake Power Station (NBEPC) |
| Product name | Fines | Fines |
| Screen opening, mm | Minus 6.4, sq | Minus 6.4, sq |
| ERL number | 4597-80 | 4598-80 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 3.75 | 3.55 |
| Sulfate sulphur | % | 0.49 | 0.54 |
| Organic sulphur | % | 1.26 | 0.99 |


Moisture (as rec'd):

| | | | |
|----------------|---|------|-------|
| Inherent | % | 1.63 | 1.51 |
| Adherent | % | 7.24 | 14.86 |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 43.78 | 49.95 |
| Al ₂ O ₃ | | 15.77 | 17.08 |
| Fe ₂ O ₃ | | 31.62 | 22.52 |
| TiO ₂ | | 0.68 | 0.76 |
| P ₂ O ₅ | | 0.98 | 0.71 |
| CaO | | 1.22 | 1.49 |
| MgO | | 0.79 | 0.76 |
| SO ₃ | | 1.04 | 1.7 |
| Na ₂ O | | 0.20 | 0.21 |
| K ₂ O | | 2.45 | 2.85 |
| SrO | | 0.01 | 0.01 |
| BaO | | 0.14 | 0.13 |
| LOF | | 0.00 | 0.36 |

Notes:



COAL ANALYSES - SASKATCHEWAN

MANALTA COAL LIMITED
Klimax Mine; Estevan Seam; Ravenscrag Formation
Estevan, Saskatchewan

| | | |
|-------------------------------|-------------------|---------|
| Sampling date | 24-9-79 | 27-9-78 |
| Sampling location | Mine Screen Plant | |
| Product name | Pea | |
| Screen opening, mm | 32 x 13 | |
| ERL number | 3796-79 | 3662-78 |
| Rank of coal | Lignite A | |
| Proximate analysis, equil: | | |
| Moisture | % | 40.41 |
| Ash | % | 7.83 |
| Volatile matter | % | 36.13 |
| Fixed carbon | % | 15.63 |
| Sulphur, equil | % | 0.42 |
| Calorific value, equil: | | |
| | MJ/kg | 14.48 |
| | Btu/lb | 6225 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 65.95 |
| Hydrogen | % | 0.94 |
| Sulphur | % | 0.70 |
| Nitrogen | % | 1.23 |
| Ash | % | 13.15 |
| Oxygen, by difference | % | 18.03 |
| Trace mercury | µg/g (ppm) | - |
| | | 0.05 |
| Ash fusibility temperature: | | |
| Initial | °C | 1125 |
| Spherical | °C | 1225 |
| Hemispherical | °C | 1250 |
| Fluid | °C | 1290 |
| Hardgrove grindability index | | 46 |
| Free swelling index | NA | NA |

Notes:

MANALTA COAL LIMITED
 Klimax Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | |
|-------------------|-------------------|---------|
| Sampling date | 24-9-79 | 27-9-78 |
| Sampling location | Mine Screen Plant | |

| | | |
|--------------------|---------|--|
| Product name | Pea | |
| Screen opening, mm | 32 x 13 | |

| | | |
|------------|---------|---------|
| ERL number | 3796-79 | 3662-78 |
|------------|---------|---------|

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.20 | 0.29 |
| Sulfate sulphur | % | 0.05 | 0.02 |
| Organic sulphur | % | 0.45 | 0.42 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 34.91 | 37.88 |
| Al ₂ O ₃ | 19.87 | 21.22 |
| Fe ₂ O ₃ | 4.26 | 4.40 |
| TiO ₂ | 0.85 | 1.14 |
| P ₂ O ₅ | 0.47 | 0.37 |
| CaO | 15.90 | 15.82 |
| MgO | 3.69 | 3.92 |
| SO ₃ | 10.38 | 10.93 |
| Na ₂ O | 7.31 | 4.13 |
| K ₂ O | 0.24 | 0.22 |
| SrO | 0.53 | - |
| BaO | 0.55 | - |
| LOF | 0.71 | - |

Notes:

MANALTA COAL LIMITED
 Klimax Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | | |
|--------------------------------|-------------------|---------|-------|
| Sampling date | 24-9-79 | 27-9-78 | |
| Sampling location | Mine Screen Plant | | |
| Product name | Slack | | |
| Screen opening, mm | Minus 32 | | |
| ERL number | 3795-79 | 3664-78 | |
| Rank of coal | Lignite A | | |
| Proximate analysis, equil: | | | |
| Moisture | % | 37.97 | 34.60 |
| Ash | % | 9.37 | 11.77 |
| Volatile matter | % | 39.81 | 25.45 |
| Fixed carbon | % | 12.85 | 28.18 |
| Sulphur, equil | % | 0.49 | 0.60 |
| Calorific value, equil: | | | |
| MJ/kg | | 14.86 | 15.16 |
| Btu/lb | | 6388 | 6516 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 67.37 | 65.81 |
| Hydrogen | % | 0.66 | 0.55 |
| Sulphur | % | 0.79 | 0.91 |
| Nitrogen | % | 0.75 | 1.14 |
| Ash | % | 15.11 | 17.99 |
| Oxygen, by difference | % | 15.32 | 13.60 |
| Trace mercury μg/g (ppm) | - | | 0.06 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1105 | 1180 |
| Spherical | °C | 1205 | 1240 |
| Hemispherical | °C | 1225 | 1250 |
| Fluid | °C | 1320 | 1325 |
| Hardgrove grindability index | 63 | | 56 |
| Free swelling index | NA | | NA |

Notes:

MANALTA COAL LIMITED
 Klimax Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | |
|--------------------------------|-------------------|---------|
| Sampling date | 24-9-79 | 27-9-78 |
| Sampling location | Mine Screen Plant | |
| Product name | Slack | |
| Screen opening, mm | Minus 32 | |
| ERL number | 3795-79 | 3664-78 |
| <hr/> | | |
| Sulphur Forms (dry basis): | | |
| Pyritic sulphur | % | 0.28 |
| Sulfate sulphur | % | 0.14 |
| Organic sulphur | % | 0.37 |
| <hr/> | | |
| Moisture (as rec'd): | | |
| Inherent | % | - |
| Adherent | % | - |
| <hr/> | | |
| Ash analysis, %: | | |
| SiO ₂ | | 41.58 |
| Al ₂ O ₃ | | 20.76 |
| Fe ₂ O ₃ | | 4.88 |
| TiO ₂ | | 1.38 |
| P ₂ O ₅ | | 0.27 |
| CaO | | 13.53 |
| MgO | | 3.74 |
| SO ₃ | | 10.49 |
| Na ₂ O | | 3.10 |
| K ₂ O | | 0.29 |
| SrO | | - |
| BaO | | - |
| LOF | | - |

Notes:

MANALTA COAL LIMITED
 Klimax Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | |
|-------------------------------|--|---------|
| Sampling date | 25-9-79 | 26-9-78 |
| Sampling location | Estevan Generating Station Saskatchewan Power Corp. | |
| Product name | Power Plant Feed | |
| Screen opening, mm | Minus 38 | |
| ERL number | 3801-79 | 3660-78 |
| Rank of coal | Lignite A | |
| Proximate analysis, equil: | | |
| Moisture | % | 42.84 |
| Ash | % | 6.31 |
| Volatile matter | % | 35.84 |
| Fixed carbon | % | 15.01 |
| Sulphur, equil | % | 0.35 |
| Calorific value, equil: | | |
| MJ/kg | | 14.58 |
| Btu/lb | | 6267 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 68.06 |
| Hydrogen | % | 0.45 |
| Sulphur | % | 0.62 |
| Nitrogen | % | 1.21 |
| Ash | % | 11.05 |
| Oxygen, by difference | % | 18.61 |
| Trace mercury | µg/g (ppm) | - |
| | | 0.04 |
| Ash fusibility temperature: | | |
| Initial | °C | 1105 |
| Spherical | °C | 1205 |
| Hemispherical | °C | 1215 |
| Fluid | °C | 1225 |
| Hardgrove grindability index | | 37 |
| Free swelling index | NA | NA |

Notes:

MANALTA COAL LIMITED
 Klimax Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | |
|--------------------|--|------------------|
| Sampling date | 25-9-79 | 26-9-78 |
| Sampling location | Estevan Generating Station Saskatchewan Power Corp. | |
| Product name | | Power Plant Feed |
| Screen opening, mm | | Minus 38 |

| | | |
|--------------------------------|-------|-------|
| Ash analysis, %: | | |
| SiO ₂ | 32.38 | 38.59 |
| Al ₂ O ₃ | 18.50 | 19.43 |
| Fe ₂ O ₃ | 5.15 | 5.98 |
| TiO ₂ | 0.54 | 1.25 |
| P ₂ O ₅ | 0.22 | 0.33 |
| CaO | 15.75 | 12.81 |
| MgO | 3.64 | 3.65 |
| SO ₃ | 10.30 | 12.38 |
| Na ₂ O | 9.93 | 5.12 |
| K ₂ O | 0.74 | 0.49 |
| SrO | 0.49 | - |
| BaO | 1.23 | - |
| LOF | 0.66 | - |

Notes:

MANALTA COAL LIMITED
 Klimax Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | |
|-------------------------------|-------------------|
| Sampling date | 27-9-78 |
| Sampling location | Mine Screen Plant |
| Product name | Booker |
| Screen opening, mm | 51 x 32 |
| ERL number | 3661-78 |
| Rank of coal | Lignite A |
| Proximate analysis, equil: | |
| Moisture | % 34.61 |
| Ash | % 7.21 |
| Volatile matter | % 26.87 |
| Fixed carbon | % 31.31 |
| Sulphur, equil | % 0.80 |
| Calorific value, equil: | |
| MJ/kg | 16.57 |
| Btu/lb | 7124 |
| Ultimate analysis, dry basis: | |
| Carbon | % 69.98 |
| Hydrogen | % 0.70 |
| Sulphur | % 0.62 |
| Nitrogen | % 1.23 |
| Ash | % 11.03 |
| Oxygen, by difference | % 16.44 |
| Trace mercury | µg/g (ppm) .04 |
| Ash fusibility temperature: | |
| Initial | °C 1250 |
| Spherical | °C 1255 |
| Hemispherical | °C 1260 |
| Fluid | °C 1370 |
| Hardgrove grindability index | - |
| Free swelling index | NA |

Notes:

MANALTA COAL LIMITED
 Klimax Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | |
|--------------------|-------------------|
| Sampling date | 27-9-78 |
| Sampling location | Mine Screen Plant |
| Product name | Booker |
| Screen opening, mm | 51 x 32 |
| ERL number | 3661-78 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 0.17 |
| Sulfate sulphur | % | 0.02 |
| Organic sulphur | % | 0.43 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | |
|--------------------------------|-------|
| SiO ₂ | 31.43 |
| Al ₂ O ₃ | 20.07 |
| Fe ₂ O ₃ | 3.93 |
| TiO ₂ | 0.89 |
| P ₂ O ₅ | 0.63 |
| CaO | 20.08 |
| MgO | 6.01 |
| SO ₃ | 11.56 |
| Na ₂ O | 5.17 |
| K ₂ O | 0.23 |
| SrO | - |
| BaO | - |
| LOF | - |

Notes:

MANALTA COAL LIMITED
 Klimax Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | |
|-------------------|-------------------|---------|
| Sampling date | 24-9-79 | 27-9-78 |
| Sampling location | Mine Screen Plant | |

| | |
|--------------------|----------|
| Product name | Slack |
| Screen opening, mm | Minus 13 |

| | | |
|------------|---------|---------|
| ERL number | 3797-79 | 3663-78 |
|------------|---------|---------|

| | |
|--------------------|-----------|
| Rank of coal | Lignite A |
|--------------------|-----------|

Proximate analysis, equil:

| | | | |
|-----------------------|---|-------|-------|
| Moisture | % | 32.98 | 32.78 |
| Ash | % | 9.95 | 11.49 |
| Volatile matter | % | 40.57 | 27.62 |
| Fixed carbon | % | 16.50 | 28.11 |

| | | | |
|----------------------|---|------|------|
| Sulphur, equil | % | 0.45 | 0.56 |
|----------------------|---|------|------|

Calorific value, equil:

| | | |
|--------|-------|-------|
| MJ/kg | 15.87 | 15.73 |
| Btu/lb | 6824 | 6762 |

Ultimate analysis, dry basis:

| | | | |
|----------------------------|---|-------|-------|
| Carbon | % | 65.05 | 64.81 |
| Hydrogen | % | 0.50 | 0.73 |
| Sulphur | % | 0.67 | 0.84 |
| Nitrogen | % | 1.24 | 1.19 |
| Ash | % | 14.85 | 17.10 |
| Oxygen, by difference | % | 17.69 | 15.23 |

| | | | |
|---------------|------------|---|------|
| Trace mercury | µg/g (ppm) | - | 0.08 |
|---------------|------------|---|------|

Ash fusibility temperature:

| | | | |
|---------------------|----|------|------|
| Initial | °C | 1095 | 1190 |
| Spherical | °C | 1180 | 1245 |
| Hemispherical | °C | 1225 | 1250 |
| Fluid | °C | 1260 | 1400 |

| | | |
|------------------------------|----|----|
| Hardgrove grindability index | 56 | 58 |
|------------------------------|----|----|

| | | |
|---------------------------|----|----|
| Free swelling index | NA | NA |
|---------------------------|----|----|

Notes:

MANALTA COAL LIMITED
 Klimax Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | |
|--------------------|-------------------|---------|
| Sampling date | 24-9-79 | 27-9-78 |
| Sampling location | Mine Screen Plant | |
| Product name | Slack | |
| Screen opening, mm | Minus 13 | |
| ERL number | 3797-79 | 3663-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.05 | 0.47 |
| Sulfate sulphur | % | 0.11 | 0.06 |
| Organic sulphur | % | 0.51 | 0.31 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 36.42 | 41.01 |
| Al ₂ O ₃ | 19.91 | 20.26 |
| Fe ₂ O ₃ | 3.84 | 4.90 |
| TiO ₂ | 0.75 | 1.48 |
| P ₂ O ₅ | 0.33 | 0.29 |
| CaO | 14.89 | 13.90 |
| MgO | 3.27 | 3.79 |
| SO ₃ | 10.10 | 11.06 |
| Na ₂ O | 6.86 | 3.05 |
| K ₂ O | 0.21 | 0.29 |
| SrO | 0.48 | - |
| BaO | 1.96 | - |
| LOF | 1.05 | - |

Notes:

UTILITY COALS (1978) LTD. (operator)
 Utility Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | |
|-------------------|---|----------|
| Sampling date | 25-10-79 | 26-10-78 |
| Sampling location | Boundary Dam Generating Station Saskatchewan Power Corp. | |

| | |
|--------------------|------------------|
| Product name | Power Plant Feed |
| Screen opening, mm | Minus 38 |

| | | |
|------------|---------|---------|
| ERL number | 3802-79 | 3656-78 |
|------------|---------|---------|

| | |
|--------------------|-----------|
| Rank of coal | Lignite A |
|--------------------|-----------|

Proximate analysis, equil:

| | | | |
|-----------------------|---|-------|-------|
| Moisture | % | 40.38 | 33.40 |
| Ash | % | 7.52 | 11.96 |
| Volatile matter | % | 33.57 | 25.56 |
| Fixed carbon | % | 18.53 | 29.08 |

| | | | |
|----------------------|---|------|------|
| Sulphur, equil | % | 0.25 | 0.32 |
|----------------------|---|------|------|

Calorific value, equil:

| | | |
|--------|-------|-------|
| MJ/kg | 14.64 | 15.41 |
| Btu/lb | 6295 | 6625 |

Ultimate analysis, dry basis:

| | | | |
|----------------------------|---|-------|-------|
| Carbon | % | 65.99 | 63.13 |
| Hydrogen | % | 0.59 | 0.92 |
| Sulphur | % | 0.42 | 0.78 |
| Nitrogen | % | 1.24 | 1.23 |
| Ash | % | 12.61 | 17.95 |
| Oxygen, by difference | % | 19.14 | 15.99 |

| | | | |
|---------------|------------|---|------|
| Trace mercury | µg/g (ppm) | - | 0.06 |
|---------------|------------|---|------|

Ash fusibility temperature:

| | | | |
|---------------------|----|------|------|
| Initial | °C | 1100 | 1140 |
| Spherical | °C | 1175 | 1180 |
| Hemispherical | °C | 1205 | 1200 |
| Fluid | °C | 1225 | 1305 |

| | | |
|------------------------------|----|----|
| Hardgrove grindability index | 56 | 44 |
|------------------------------|----|----|

| | | |
|---------------------------|----|----|
| Free swelling index | NA | NA |
|---------------------------|----|----|

Notes:

UTILITY COALS (1978) LTD. (operator)
 Utility Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | |
|-------------------|---|----------|
| Sampling date | 25-10-79 | 26-10-78 |
| Sampling location | Boundary Dam Generating Station Saskatchewan Power Corp. | |

| | |
|--------------------|------------------|
| Product name | Power Plant Feed |
| Screen opening, mm | Minus 38 |

| | | |
|------------|---------|---------|
| ERL number | 3802-79 | 3656-78 |
|------------|---------|---------|

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|---|------|
| Pyritic sulphur | % | - | 0.06 |
| Sulfate sulphur | % | - | 0.07 |
| Organic sulphur | % | - | 0.65 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 37.32 | 44.61 |
| Al ₂ O ₃ | 20.59 | 18.28 |
| Fe ₂ O ₃ | 3.80 | 5.23 |
| TiO ₂ | 0.66 | 1.13 |
| P ₂ O ₅ | 0.51 | 0.40 |
| CaO | 16.50 | 11.81 |
| MgO | 3.20 | 4.42 |
| SO ₃ | 6.65 | 9.07 |
| Na ₂ O | 7.36 | 4.17 |
| K ₂ O | 0.32 | 0.96 |
| SrO | 0.51 | - |
| BaO | 1.42 | - |
| LOF | 0.69 | - |

Notes:

BIENFAIT COAL COMPANY LTD. (operator)
 Bienfait Mine; Taylorton & Estevan Seams; Ravenscrag Formation
 Bienfait, Saskatchewan

| | | | |
|-------------------------------|-------------------|---------|----------|
| Sampling date | 24-10-79 | | |
| Sampling location | Mine Screen Plant | | |
| Product name | Booker | Pea | Slack |
| Screen opening, mm | 51 x 25 | 25 x 13 | Minus 13 |
| ERL number | 3798-79 | 3799-79 | 3800-79 |
| Rank of coal | Lignite A | | |
| Proximate analysis, equil: | | | |
| Moisture | % | 33.30 | 41.32 |
| Ash | % | 7.59 | 8.41 |
| Volatile matter | % | 34.74 | 35.87 |
| Fixed carbon | % | 24.37 | 14.40 |
| Sulphur, equil | % | 0.38 | 0.39 |
| Calorific value, equil: | | | |
| MJ/kg | | 16.80 | 14.31 |
| Btu/lb | | 7222 | 6152 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 66.80 | 65.63 |
| Hydrogen | % | 0.93 | 0.80 |
| Sulphur | % | 0.57 | 0.66 |
| Nitrogen | % | 1.26 | 1.26 |
| Ash | % | 11.37 | 14.34 |
| Oxygen, by difference | % | 19.07 | 17.32 |
| Trace mercury | µg/g (ppm) | - | - |
| Ash fusibility temperature: | | | |
| Initial | °C | 1115 | 1140 |
| Spherical | °C | 1195 | 1215 |
| Hemispherical | °C | 1205 | 1225 |
| Fluid | °C | 1220 | 1315 |
| Hardgrove grindability index | | 38 | 48 |
| Free swelling index | NA | NA | NA |

Notes:

BIENFAIT COAL COMPANY LTD. (operator)
 Bienfait Mine; Taylorton & Estevan Seams; Ravenscrag Formation
 Bienfait, Saskatchewan

| | | | |
|--------------------|-------------------|---------|----------|
| Sampling date | 24-10-79 | | |
| Sampling location | Mine Screen Plant | | |
| Product name | Booker | Pea | Slack |
| Screen opening, mm | 51 x 25 | 25 x 13 | Minus 13 |
| ERL number | 3798-79 | 3799-79 | 3800-79 |

Sulphur Forms (dry basis):

| | | | | |
|-----------------------|---|------|------|------|
| Pyritic sulphur | % | 0.05 | 0.22 | 0.07 |
| Sulfate sulphur | % | 0.01 | 0.03 | 0.11 |
| Organic sulphur | % | 0.51 | 0.30 | 0.48 |

Moisture (as rec'd):

| | | | | |
|----------------|---|---|---|---|
| Inherent | % | - | - | - |
| Adherent | % | - | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|-------|-------|-------|
| SiO ₂ | 31.54 | 36.22 | 37.34 |
| Al ₂ O ₃ | 18.11 | 20.97 | 20.93 |
| Fe ₂ O ₃ | 5.34 | 4.57 | 4.33 |
| TiO ₂ | 0.73 | 0.97 | 0.79 |
| P ₂ O ₅ | 0.69 | 0.56 | 0.46 |
| CaO | 15.63 | 14.44 | 13.07 |
| MgO | 3.83 | 3.54 | 2.68 |
| SO ₃ | 11.31 | 7.87 | 8.73 |
| Na ₂ O | 9.87 | 7.85 | 7.43 |
| K ₂ O | 0.19 | 0.18 | 0.26 |
| SrO | 0.62 | 0.55 | 0.51 |
| BaO | 0.64 | 0.59 | 2.61 |
| LOF | 1.28 | 0.60 | 0.78 |

Notes:

BIENFAIT COAL COMPANY LTD. (operator)
 Bienfait Mine; Taylorton & Estevan Seams; Ravenscrag Formation
 Bienfait, Saskatchewan

| | | |
|--------------------------------|-------------------------------|----------|
| Sampling date | 25-10-78 | 25-10-78 |
| Sampling location | Mine Crusher and Screen Plant | |
| Product name | Screen | Slack |
| Screen opening, mm | 51 x 13 | Minus 13 |
| ERL number | 3658-78 | 3659-78 |
| Rank of coal | Lignite A | |
| Proximate analysis, equil: | | |
| Moisture | % | 32.25 |
| Ash | % | 8.29 |
| Volatile matter | % | 29.71 |
| Fixed carbon | % | 29.75 |
| Sulphur, equil | % | 0.43 |
| Calorific value, equil: | | |
| MJ/kg | 17.00 | 17.12 |
| Btu/lb | 7308 | 8359 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 70.25 |
| Hydrogen | % | 1.45 |
| Sulphur | % | 0.63 |
| Nitrogen | % | 1.32 |
| Ash | % | 12.24 |
| Oxygen, by difference | % | 14.11 |
| Trace mercury μg/g (ppm) | 0.06 | 0.05 |
| Ash fusibility temperature: | | |
| Initial | °C | 1145 |
| Spherical | °C | 1225 |
| Hemispherical | °C | 1250 |
| Fluid | °C | 1260 |
| Hardgrove grindability index | 46 | 50 |
| Free swelling index | NA | NA |

Notes:

BIENFAIT COAL COMPANY LTD. (operator)
 Bienfait Mine; Taylorton & Estevan Seams; Ravenscrag Formation
 Bienfait, Saskatchewan

| | | |
|--------------------|-------------------------------|----------|
| Sampling date | 25-10-78 | 25-10-78 |
| Sampling location | Mine Crusher and Screen Plant | |
| Product name | Screen | Slack |
| Screen opening, mm | 51 x 13 | Minus 13 |
| ERL number | 3658-78 | 3659-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.11 | 0.13 |
| Sulfate sulphur | % | 0.00 | 0.08 |
| Organic sulphur | % | 0.40 | 0.42 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 28.89 | 32.64 |
| Al ₂ O ₃ | | 16.10 | 16.60 |
| Fe ₂ O ₃ | | 5.68 | 5.27 |
| TiO ₂ | | 0.97 | 1.94 |
| P ₂ O ₅ | | 0.99 | 0.77 |
| CaO | | 18.01 | 15.75 |
| MgO | | 4.68 | 3.96 |
| SO ₃ | | 14.05 | 14.27 |
| Na ₂ O | | 10.36 | 8.49 |
| K ₂ O | | 0.30 | 0.33 |
| SrO | | - | - |
| BaO | | - | - |
| LOF | | - | - |

Notes:

MANITOBA & SASKATCHEWAN COAL COMPANY LTD. (operator)
 Boundary Dam Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | |
|-------------------|---|---------|
| Sampling date | 25-9-79 | 26-9-78 |
| Sampling location | Boundary Dam Generating Station Saskatchewan Power Corp. | |

| | |
|--------------------|------------------|
| Product name | Power Plant Feed |
| Screen opening, mm | Minus 38 |

| | | |
|------------|---------|---------|
| ERL number | 3803-79 | 3657-78 |
|------------|---------|---------|

| | |
|--------------------|-----------|
| Rank of coal | Lignite A |
|--------------------|-----------|

Proximate analysis, equil:

| | | | |
|-----------------------|---|-------|-------|
| Moisture | % | 43.74 | 33.68 |
| Ash | % | 9.01 | 14.02 |
| Volatile matter | % | 32.56 | 24.77 |
| Fixed carbon | % | 14.69 | 27.53 |

| | | | |
|----------------------|---|------|------|
| Sulphur, equil | % | 0.37 | 0.31 |
|----------------------|---|------|------|

Calorific value, equil:

| | | |
|--------|-------|-------|
| MJ/kg | 13.24 | 14.67 |
| Btu/lb | 5692 | 6307 |

Ultimate analysis, dry basis:

| | | | |
|----------------------------|---|-------|-------|
| Carbon | % | 63.44 | 60.28 |
| Hydrogen | % | 0.56 | 0.37 |
| Sulphur | % | 0.65 | 0.47 |
| Nitrogen | % | 1.15 | 1.08 |
| Ash | % | 16.02 | 21.13 |
| Oxygen, by difference | % | 18.18 | 16.67 |

| | | | |
|---------------|------------|---|------|
| Trace mercury | µg/g (ppm) | - | 0.07 |
|---------------|------------|---|------|

Ash fusibility temperature:

| | | | |
|---------------------|----|------|------|
| Initial | °C | 1140 | 1160 |
| Spherical | °C | 1205 | 1230 |
| Hemispherical | °C | 1225 | 1290 |
| Fluid | °C | 1290 | 1320 |

| | | |
|------------------------------|----|----|
| Hardgrove grindability index | 51 | 38 |
|------------------------------|----|----|

| | | |
|---------------------------|----|----|
| Free swelling index | NA | NA |
|---------------------------|----|----|

Notes:

MANITOBA & SASKATCHEWAN COAL COMPANY LTD. (operator)
 Boundary Dam Mine; Estevan Seam; Ravenscrag Formation
 Estevan, Saskatchewan

| | | |
|--------------------|---|---------|
| Sampling date | 25-9-79 | 26-9-78 |
| Sampling location | Boundary Dam Generating Station Saskatchewan Power Corp. | |
| Product name | Power Plant Feed | |
| Screen opening, mm | Minus 38 | |
| ERL number | 3803-79 | 3657-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|---|------|
| Pyritic sulphur | % | - | 0.18 |
| Sulfate sulphur | % | - | 0.00 |
| Organic sulphur | % | - | 0.29 |


Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 41.26 | 51.55 |
| Al ₂ O ₃ | | 20.32 | 20.72 |
| Fe ₂ O ₃ | | 4.20 | 3.68 |
| TiO ₂ | | 0.76 | 0.89 |
| P ₂ O ₅ | | 0.60 | 0.31 |
| CaO | | 12.92 | 8.69 |
| MgO | | 3.11 | 2.50 |
| SO ₃ | | 7.59 | 5.16 |
| Na ₂ O | | 6.43 | 5.69 |
| K ₂ O | | 0.48 | 0.88 |
| SrO | | 0.46 | - |
| BaO | | 1.18 | - |
| LOF | | 0.55 | - |

Notes:



COAL ANALYSES - ALBERTA (Subbituminous)

CENTURY COALS LIMITED
 Mine No. 1742 (Atlas); Drumheller Coalfield (CF26)
 East Coulee, Drumheller Area, Plains Region, Alberta
 Sec 6, Tp 27; R18, W4

| | | | |
|-------------------------------|-----------------|--------------|-------|
| Sampling date | 17-10-78 | 17-10-78 | |
| Sampling location | Stockpile | Stockpile | |
| Product name | Lump | Egg | |
| Screen opening, mm | 305 x 114, rd | 114 x 51, rd | |
| ERL number | 3799-78 | 3800-78 | |
| Rank of coal | Subbituminous B | | |
| Proximate analysis, equil: | | | |
| Moisture | % | 15.68 | 15.13 |
| Ash | % | 6.48 | 10.06 |
| Volatile matter | % | 32.72 | 32.06 |
| Fixed carbon | % | 45.12 | 42.75 |
| Sulphur, equil | % | 0.49 | 0.47 |
| Calorific value, equil: | | | |
| MJ/kg | | 23.40 | 22.11 |
| Btu/lb | | 10 060 | 9504 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 67.76 | 65.89 |
| Hydrogen | % | 3.45 | 4.02 |
| Sulphur | % | 0.59 | 0.56 |
| Nitrogen | % | 1.76 | 1.70 |
| Ash | % | 7.69 | 11.85 |
| Oxygen, by difference | % | 18.75 | 15.95 |
| Trace mercury | µg/g (ppm) | 0.05 | 0.05 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1150 | 1315 |
| Spherical | °C | 1195 | 1345 |
| Hemispherical | °C | 1245 | 1375 |
| Fluid | °C | 1275 | 1400 |
| Hardgrove grindability index | - | - | - |
| Free swelling index | NA | NA | NA |

Notes:

CENTURY COALS LIMITED
 Mine No. 1742 (Atlas); Drumheller Coalfield (CF26)
 East Coulee, Drumheller Area, Plains Region, Alberta
 Sec 6, Twp 27; R18, W4

| | | |
|--------------------|---------------|--------------|
| Sampling date | 17-10-78 | 17-10-78 |
| Sampling location | Stockpile | Stockpile |
| Product name | Lump | Egg |
| Screen opening, mm | 305 x 114, rd | 114 x 51, rd |
| ERL number | 3799-78 | 3800-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.02 | 0.03 |
| Sulfate sulphur | % | 0.00 | 0.00 |
| Organic sulphur | % | 0.57 | 0.53 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 39.75 | 48.80 |
| Al ₂ O ₃ | 22.77 | 26.15 |
| Fe ₂ O ₃ | 4.09 | 2.94 |
| TiO ₂ | 0.95 | 0.76 |
| P ₂ O ₅ | 3.12 | 1.50 |
| CaO | 11.70 | 7.64 |
| MgO | 1.19 | 0.67 |
| SO ₃ | 9.13 | 5.30 |
| Na ₂ O | 6.53 | 4.87 |
| K ₂ O | 0.80 | 1.40 |
| SrO | - | - |
| BaO | - | - |
| LOF | - | - |

Notes:

CENTURY COALS LIMITED
 Mine No. 1742 (Atlas); Drumheller Coalfield (CF26)
 East Coulee, Drumheller Area, Plains Region, Alberta
 Sec 6, Tp 27; R18, W4

| | | |
|-------------------------------|-----------------|--------------|
| Sampling date | 17-10-78 | 17-10-78 |
| Sampling location | Stockpile | Stockpile |
| Product name | Stoker | Slack |
| Screen opening, mm | 41 x 16, rd | Minus 16, rd |
| ERL number | 3801-78 | 3802-78 |
| Rank of coal | Subbituminous B | |
| Proximate analysis, equil: | | |
| Moisture | % | 17.36 |
| Ash | % | 9.80 |
| Volatile matter | % | 29.74 |
| Fixed carbon | % | 43.10 |
| Sulphur, equil | % | 0.47 |
| Calorific value, equil: | | |
| MJ/kg | | 21.18 |
| Btu/lb | | 9105 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 63.88 |
| Hydrogen | % | 3.69 |
| Sulphur | % | 0.57 |
| Nitrogen | % | 1.70 |
| Ash | % | 11.85 |
| Oxygen, by difference | % | 18.31 |
| Trace mercury | µg/g (ppm) | 0.04 |
| Ash fusibility temperature: | | |
| Initial | °C | 1315 |
| Spherical | °C | 1350 |
| Hemispherical | °C | 1460 |
| Fluid | °C | 1480+ |
| Hardgrove grindability index | - | - |
| Free swelling index | NA | NA |

Notes:

CENTURY COALS LIMITED
 Mine No. 1742 (Atlas); Drumheller Coalfield (CF26)
 East Coulee, Drumheller Area, Plains Region, Alberta
 Sec 6, Tp 27; Rl8, W4

| | | |
|--------------------|-------------|--------------|
| Sampling date | 17-10-78 | 17-10-78 |
| Sampling location | Stockpile | Stockpile |
| Product name | Stoker | Slack |
| Screen opening, mm | 41 x 16, rd | Minus 16, rd |
| ERL number | 3801-78 | 3802-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.05 | 0.06 |
| Sulfate sulphur | % | 0.00 | 0.00 |
| Organic sulphur | % | 0.52 | 0.51 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 48.49 | 48.43 |
| Al ₂ O ₃ | 26.00 | 26.53 |
| Fe ₂ O ₃ | 3.33 | 3.30 |
| TiO ₂ | 0.76 | 0.74 |
| P ₂ O ₅ | 1.48 | 1.30 |
| CaO | 7.81 | 7.73 |
| MgO | 1.00 | 1.21 |
| SO ₃ | 4.97 | 4.73 |
| Na ₂ O | 4.87 | 4.83 |
| K ₂ O | 1.36 | 1.22 |
| SrO | - | - |
| BaO | - | - |
| LOF | - | - |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W4

| | | |
|--------------------|----------------------------|---------|
| Sampling date | 7-11-79 | 3-10-78 |
| Sampling location | Forestburg Collieries Ltd. | |
| Product name | Lump | |
| Screen opening, mm | 305 x 114 | |
| ERL number | 4047-79 | 3651-78 |

| | | | |
|-------------------------------|-----------------|-------|-------|
| Rank of coal | Subbituminous C | | |
| Proximate analysis, equil: | | | |
| Moisture | % | 26.16 | 25.64 |
| Ash | % | 4.46 | 6.15 |
| Volatile matter | % | 35.12 | 30.28 |
| Fixed carbon | % | 34.26 | 37.93 |
| Sulphur, equil | % | 0.43 | 0.37 |
| Calorific value, equil: | | | |
| MJ/kg | | 20.27 | 19.93 |
| Btu/lb | | 8713 | 8567 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 71.12 | 69.99 |
| Hydrogen | % | 2.54 | 2.37 |
| Sulphur | % | 0.59 | 0.50 |
| Nitrogen | % | 1.86 | 1.64 |
| Ash | % | 6.05 | 8.27 |
| Oxygen, by difference | % | 17.84 | 17.23 |
| Trace mercury | µg/g (ppm) | - | 0.05 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1140 | 1250 |
| Spherical | °C | 1250 | 1293 |
| Hemispherical | °C | 1260 | 1315 |
| Fluid | °C | 1300 | 1370 |
| Hardgrove grindability index | | 29 | - |
| Free swelling index | | NA | NA |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W4

| | | |
|-------------------|----------------------------|---------|
| Sampling date | 7-11-79 | 3-10-78 |
| Sampling location | Forestburg Collieries Ltd. | |

| | |
|--------------------|-----------|
| Product name | Lump |
| Screen opening, mm | 305 x 114 |

| | | |
|------------|---------|---------|
| ERL number | 4047-79 | 3651-78 |
|------------|---------|---------|

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.04 | 0.03 |
| Sulfate sulphur | % | 0.01 | 0.00 |
| Organic sulphur | % | 0.54 | 0.47 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 27.44 | 38.54 |
| Al ₂ O ₃ | | 16.77 | 21.96 |
| Fe ₂ O ₃ | | 6.88 | 4.98 |
| TiO ₂ | | 0.37 | 0.76 |
| P ₂ O ₅ | | 1.16 | 0.88 |
| CaO | | 22.63 | 18.59 |
| MgO | | 3.29 | 2.70 |
| SO ₃ | | 14.86 | 9.59 |
| Na ₂ O | | 1.59 | 0.89 |
| K ₂ O | | 0.28 | 1.17 |
| SrO | | 0.42 | - |
| BaO | | 0.81 | - |
| LOF | | 2.55 | - |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W4

| | | |
|--------------------|----------------------------|---------|
| Sampling date | 7-11-79 | 3-10-78 |
| Sampling location | Forestburg Collieries Ltd. | |
| Product name | Egg | |
| Screen opening, mm | 11 $\frac{1}{4}$ x 51 | |
| ERL number | 4048-79 | 3652-78 |

| | | | |
|-------------------------------|-----------------|-------|-------|
| Rank of coal | Subbituminous C | | |
| Proximate analysis, equil: | | | |
| Moisture | % | 24.91 | 25.10 |
| Ash | % | 5.35 | 5.33 |
| Volatile matter | % | 35.07 | 30.36 |
| Fixed carbon | % | 34.67 | 39.21 |
| Sulphur, equil | % | 0.43 | 0.38 |
| Calorific value, equil: | | | |
| MJ/kg | | 20.41 | 20.32 |
| Btu/lb | | 8773 | 8736 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 71.31 | 73.87 |
| Hydrogen | % | 2.72 | 2.39 |
| Sulphur | % | 0.58 | 0.51 |
| Nitrogen | % | 1.72 | 1.83 |
| Ash | % | 7.12 | 7.12 |
| Oxygen, by difference | % | 16.55 | 14.28 |
| Trace mercury | µg/g (ppm) | - | 0.03 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1125 | 1190 |
| Spherical | °C | 1225 | 1225 |
| Hemispherical | °C | 1250 | 1255 |
| Fluid | °C | 1305 | 1325 |
| Hardgrove grindability index | | 30 | - |
| Free swelling index | | NA | NA |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W4

| | | |
|--------------------|----------------------------|---------|
| Sampling date | 7-11-79 | 3-10-78 |
| Sampling location | Forestburg Collieries Ltd. | |
| Product name | Egg | |
| Screen opening, mm | 11 $\frac{1}{4}$ x 51 | |
| ERL number | 4048-79 | 3652-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.04 | 0.03 |
| Sulfate sulphur | % | 0.01 | 0.00 |
| Organic sulphur | % | 0.53 | 0.48 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 33.67 | 34.95 |
| Al ₂ O ₃ | | 18.24 | 20.48 |
| Fe ₂ O ₃ | | 5.80 | 5.67 |
| TiO ₂ | | 0.34 | 0.76 |
| P ₂ O ₅ | | 0.85 | 1.02 |
| CaO | | 19.29 | 20.76 |
| MgO | | 2.44 | 3.46 |
| SO ₃ | | 12.16 | 11.34 |
| Na ₂ O | | 1.71 | 0.78 |
| K ₂ O | | 0.57 | 0.83 |
| SrO | | 0.42 | - |
| BaO | | 0.77 | - |
| LOF | | 2.37 | - |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W4

| | | |
|-------------------------------|-----------------|-----------------|
| Sampling date | 7-11-79 | 4-10-78 |
| Sampling location | Forestburg | Collieries Ltd. |
| Product name | Nut | |
| Screen opening, mm | 51 x 38 | |
| ERL number | 4049-79 | 3653-78 |
| Rank of coal | Subbituminous C | |
| Proximate analysis, equil: | | |
| Moisture | % | 25.53 |
| Ash | % | 6.05 |
| Volatile matter | % | 37.06 |
| Fixed carbon | % | 31.36 |
| Sulphur, equil | % | 0.42 |
| Calorific value, equil: | | |
| MJ/kg | | 20.01 |
| Btu/lb | | 8601 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 70.64 |
| Hydrogen | % | 2.66 |
| Sulphur | % | 0.56 |
| Nitrogen | % | 1.86 |
| Ash | % | 8.12 |
| Oxygen, by difference | % | 16.16 |
| Trace mercury | µg/g (ppm) | - |
| | | 0.03 |
| Ash fusibility temperature: | | |
| Initial | °C | 1140 |
| Spherical | °C | 1220 |
| Hemispherical | °C | 1330 |
| Fluid | °C | 1415 |
| Hardgrove grindability index | 29 | - |
| Free swelling index | NA | NA |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W4

| | | |
|----------------------------|----------------------------|---------|
| Sampling date | 7-11-79 | 4-10-78 |
| Sampling location | Forestburg Collieries Ltd. | |
| Product name | Nut | |
| Screen opening, mm | 51 x 38 | |
| ERL number | 4049-79 | 3653-78 |
| Sulphur Forms (dry basis): | | |
| Pyritic sulphur | % | 0.05 |
| Sulfate sulphur | % | 0.01 |
| Organic sulphur | % | 0.50 |
| Moisture (as rec'd): | | |
| Inherent | % | - |
| Adherent | % | - |

| | | |
|--------------------------------|--|-------|
| Ash analysis, %: | | |
| SiO ₂ | | 37.36 |
| Al ₂ O ₃ | | 20.70 |
| Fe ₂ O ₃ | | 5.57 |
| TiO ₂ | | 0.68 |
| P ₂ O ₅ | | 1.02 |
| CaO | | 19.33 |
| MgO | | 2.88 |
| SO ₃ | | 10.76 |
| Na ₂ O | | 0.82 |
| K ₂ O | | 0.92 |
| SrO | | - |
| BaO | | - |
| LOF | | - |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W4

| | | |
|-------------------------------|----------------------------|---------|
| Sampling date | 8-11-79 | 4-10-78 |
| Sampling location | Forestburg Collieries Ltd. | |
| Product name | Stoker | |
| Screen opening, mm | 38 x 13 | |
| ERL number | 4050-79 | 3654-78 |
| Rank of coal | Subbituminous C | |
| Proximate analysis, equil: | | |
| Moisture | % | 25.73 |
| Ash | % | 5.71 |
| Volatile matter | % | 24.32 |
| Fixed carbon | % | 32.24 |
| Sulphur, equil | % | 0.43 |
| Calorific value, equil: | | |
| MJ/kg | | 20.14 |
| Btu/lb | | 8659 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 79.49 |
| Hydrogen | % | 2.51 |
| Sulphur | % | 0.58 |
| Nitrogen | % | 1.84 |
| Ash | % | 7.70 |
| Oxygen, by difference | % | 16.88 |
| Trace mercury | µg/g (ppm) | - |
| | | 0.03 |
| Ash fusibility temperature: | | |
| Initial | °C | 1145 |
| Spherical | °C | 1270 |
| Hemispherical | °C | 1290 |
| Fluid | °C | 1350 |
| Hardgrove grindability index | | 30 |
| Free swelling index | NA | NA |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W⁴

| | | |
|--------------------|----------------------------|---------|
| Sampling date | 8-11-79 | 4-10-78 |
| Sampling location | Forestburg Collieries Ltd. | |
| Product name | Stoker | |
| Screen opening, mm | 38 x 13 | |
| ERL number | 4050-79 | 3654-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.04 | 0.03 |
| Sulfate sulphur | % | 0.00 | 0.00 |
| Organic sulphur | % | 0.54 | 0.48 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|---|
| SiO ₂ | 33.54 | - |
| Al ₂ O ₃ | 18.98 | - |
| Fe ₂ O ₃ | 6.18 | - |
| TiO ₂ | 0.41 | - |
| P ₂ O ₅ | 0.93 | - |
| CaO | 19.50 | - |
| MgO | 2.74 | - |
| SO ₃ | 11.94 | - |
| Na ₂ O | 1.61 | - |
| K ₂ O | 0.53 | - |
| SrO | 0.42 | - |
| BaO | 0.64 | - |
| LOF | 1.87 | - |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W4

| | | |
|-------------------------------|-----------------|-----------------|
| Sampling date | 8-11-79 | 4-10-78 |
| Sampling location | Forestburg | Collieries Ltd. |
| Product name | Slack | |
| Screen opening, mm | Minus 13 | |
| ERL number | 4051-79 | 3655-78 |
| Rank of coal | Subbituminous C | |
| Proximate analysis, equil: | | |
| Moisture | % | 25.18 |
| Ash | % | 5.77 |
| Volatile matter | % | 36.08 |
| Fixed carbon | % | 32.97 |
| Sulphur, equil | % | 0.46 |
| Calorific value, equil: | | |
| MJ/kg | | 19.90 |
| Btu/lb | | 8556 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 70.63 |
| Hydrogen | % | 2.58 |
| Sulphur | % | 0.61 |
| Nitrogen | % | 1.70 |
| Ash | % | 7.72 |
| Oxygen, by difference | % | 16.76 |
| Trace mercury | µg/g (ppm) | 0.02 |
| Ash fusibility temperature: | | |
| Initial | °C | 1150 |
| Spherical | °C | 1275 |
| Hemispherical | °C | 1295 |
| Fluid | °C | 1340 |
| Hardgrove grindability index | 30 | - |
| Free swelling index | NA | NA |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W4

| | | |
|--------------------|----------------------------|---------|
| Sampling date | 8-11-79 | 4-10-78 |
| Sampling location | Forestburg Collieries Ltd. | |
| Product name | Slack | |
| Screen opening, mm | Minus 13 | |
| ERL number | 4051-79 | 3655-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.04 | 0.07 |
| Sulfate sulphur | % | 0.01 | 0.01 |
| Organic sulphur | % | 0.56 | 0.49 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 32.69 | 39.58 |
| Al ₂ O ₃ | | 17.94 | 20.32 |
| Fe ₂ O ₃ | | 6.52 | 5.72 |
| TiO ₂ | | 0.27 | 0.81 |
| P ₂ O ₅ | | 1.03 | 0.65 |
| CaO | | 18.59 | 17.95 |
| MgO | | 2.38 | 2.84 |
| SO ₃ | | 12.68 | 10.47 |
| Na ₂ O | | 1.88 | 0.84 |
| K ₂ O | | 0.54 | 0.86 |
| SrO | | 0.44 | - |
| BaO | | 1.28 | - |
| LOF | | 2.21 | - |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41; R15, W4

| | | |
|--------------------|---|---------|
| Sampling date | 8-11-79 | 4-10-78 |
| Sampling location | Battle River Generating Station Alberta Power Ltd. | |
| Product name | Power Plant Feed | |
| Screen opening, mm | Minus 19 | |
| ERL number | 4046-79 | 3650-78 |

| | | | |
|-------------------------------|-----------------|-------|-------|
| Rank of coal | Subbituminous C | | |
| Proximate analysis, equil: | | | |
| Moisture | % | 26.16 | 25.83 |
| Ash | % | 8.20 | 10.18 |
| Volatile matter | % | 36.50 | 29.18 |
| Fixed carbon | % | 29.14 | 34.81 |
| Sulphur, equil | % | 0.39 | 0.35 |
| Calorific value, equil: | | | |
| MJ/kg | | 18.48 | 18.28 |
| Btu/lb | | 7947 | 7858 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 68.28 | 65.36 |
| Hydrogen | % | 2.18 | 2.01 |
| Sulphur | % | 0.53 | 0.47 |
| Nitrogen | % | 1.75 | 1.61 |
| Ash | % | 11.10 | 13.73 |
| Oxygen, by difference | % | 16.16 | 16.82 |
| Trace mercury | µg/g (ppm) | - | 0.03 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1255 | 1310 |
| Spherical | °C | 1345 | 1350 |
| Hemispherical | °C | 1380 | 1375 |
| Fluid | °C | 1430 | 1475 |
| Hardgrove grindability index | | 31 | 33 |
| Free swelling index | | NA | NA |

Notes:

FORESTBURG COLLIERIES LIMITED (operator)
 Mine No. 1578 (Diplomat); Seams 2 & 3; Battle River Coalfield (CF22)
 Forestburg, Castor Area, Plains Region, Alberta
 Sec 6, Tp 41, R15, W4

| | | |
|-------------------|---|---------|
| Sampling date | 8-11-79 | 4-10-78 |
| Sampling location | Battle River Generating Station Alberta Power Ltd. | |

| | |
|--------------------|------------------|
| Product name | Power Plant Feed |
| Screen opening, mm | Minus 19 |

| | | |
|------------|---------|---------|
| ERL number | 4046-79 | 3650-78 |
|------------|---------|---------|

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.05 | 0.03 |
| Sulfate sulphur | % | 0.01 | 0.00 |
| Organic sulphur | % | 0.47 | 0.44 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 38.21 | 48.98 |
| Al ₂ O ₃ | | 22.09 | 24.55 |
| Fe ₂ O ₃ | | 4.98 | 3.83 |
| TiO ₂ | | 0.30 | 0.52 |
| P ₂ O ₅ | | 1.04 | 0.53 |
| CaO | | 17.23 | 11.63 |
| MgO | | 2.98 | 1.32 |
| SO ₃ | | 8.47 | 6.32 |
| Na ₂ O | | 0.55 | 0.99 |
| K ₂ O | | 0.86 | 1.15 |
| SrO | | 0.76 | - |
| BaO | | 0.40 | - |
| LOF | | 1.64 | - |

Notes:

MANALTA COAL LIMITED (operator)
 Mine No. 1046 (Vesta); Battle River Coalfield (CF22)
 Halkirk, Castor Area, Plains Region, Alberta
 Sec 20, Tp 40; R15, W4

| | | |
|--------------------|---|---------|
| Sampling date | 8-10-79 | 4-10-78 |
| Sampling location | Battle River Generating Station Alberta Power Ltd. | |
| Product name | Power Plant Feed | |
| Screen opening, mm | Minus 19 | |
| ERL number | 4045-79 | 3649-78 |

| | | | |
|-------------------------------|-----------------|-------|-------|
| Rank of coal | Subbituminous C | | |
| Proximate analysis, equil: | | | |
| Moisture | % | 26.11 | 21.40 |
| Ash | % | 8.21 | 9.14 |
| Volatile matter | % | 39.63 | 29.94 |
| Fixed carbon | % | 26.05 | 39.52 |
| Sulphur, equil | % | 0.48 | 0.45 |
| Calorific value, equil: | | | |
| | MJ/kg | 18.64 | 19.90 |
| | Btu/lb | 8014 | 8556 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 73.20 | 63.73 |
| Hydrogen | % | 2.57 | 3.02 |
| Sulphur | % | 0.65 | 0.58 |
| Nitrogen | % | 1.80 | 1.32 |
| Ash | % | 11.11 | 11.63 |
| Oxygen, by difference | % | 10.67 | 19.72 |
| Trace mercury | µg/g (ppm) | 0.00 | - |
| Ash fusibility temperature: | | | |
| Initial | °C | 1170 | 1150 |
| Spherical | °C | 1310 | 1230 |
| Hemispherical | °C | 1415 | 1280 |
| Fluid | °C | 1450+ | 1315 |
| Hardgrove grindability index | | 30 | 30 |
| Free swelling index | | NA | NA |

Notes:

MANALTA COAL LIMITED (operator)
 Mine No. 1046 (Vesta); Battle River Coalfield (CF22)
 Halkirk, Castor Area, Plains Region, Alberta
 Sec 20, Tp 40; R15, W4

| | | |
|--------------------|---|---------|
| Sampling date | 8-10-79 | 4-10-78 |
| Sampling location | Battle River Generating Station Alberta Power Ltd. | |
| Product name | Power Plant Feed | |
| Screen opening, mm | Minus 19 | |
| ERL number | 4045-79 | 3649-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.10 | 0.02 |
| Sulfate sulphur | % | 0.02 | 0.01 |
| Organic sulphur | % | 0.53 | 0.55 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 48.23 | 43.47 |
| Al ₂ O ₃ | 17.11 | 18.85 |
| Fe ₂ O ₃ | 8.31 | 8.07 |
| TiO ₂ | 0.44 | 0.66 |
| P ₂ O ₅ | 0.14 | 0.20 |
| CaO | 9.54 | 12.42 |
| MgO | 1.59 | 1.50 |
| SO ₃ | 7.86 | 10.85 |
| Na ₂ O | 1.76 | 2.46 |
| K ₂ O | 1.23 | 1.51 |
| SrO | 0.14 | - |
| BaO | 1.07 | - |
| LOF | 1.18 | - |

Notes:

MANALTA COAL LIMITED (operator)
 Mine No. 1757 (Whitewood); Seams No. 1 & 3; Wabamun Coalfield (CF39)
 Wabamun, Pembina Area, Plains Region, Alberta
 Sec 29, Tp 52; R4, W5

| | | | |
|-------------------------------|---|--------------|-------|
| Sampling date | 9-8-79 | 20-9-78 | |
| Sampling location | Conveyor to Stockpile | | |
| Product name | Power Plant Feed to Wabamun Generating Station of Calgary Power Ltd. | | |
| Screen opening, mm | Minus 38, sq | Minus 38, sq | |
| ERL number | 3667-79 | 3665-78 | |
| Rank of coal | Subbituminous C | | |
| Proximate analysis, equil: | | | |
| Moisture | % | 21.28 | 20.15 |
| Ash | % | 12.60 | 12.41 |
| Volatile matter | % | 32.40 | 29.27 |
| Fixed carbon | % | 33.72 | 38.17 |
| Sulphur, equil | % | 0.22 | 0.18 |
| Calorific value, equil: | | | |
| MJ/kg | | 18.56 | 19.13 |
| Btu/lb | | 7981 | 8225 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 67.94 | 64.30 |
| Hydrogen | % | 2.43 | 1.72 |
| Sulphur | % | 0.28 | 0.23 |
| Nitrogen | % | 1.31 | 0.88 |
| Ash | % | 16.01 | 15.53 |
| Oxygen, by difference | % | 12.03 | 17.34 |
| Trace mercury | µg/g (ppm) | 0.00 | 0.05 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1275 | 1260 |
| Spherical | °C | 1325 | 1315 |
| Hemispherical | °C | 1415 | 1345 |
| Fluid | °C | 1480+ | 1470 |
| Hardgrove grindability index | | 42 | 46 |
| Free swelling index | NA | NA | |

Notes:

MANALTA COAL LIMITED (operator)
 Mine No. 1757 (Whitewood); Seams No. 1 & 3; Wabamun Coalfield (CF39)
 Wabamun, Pembina Area, Plains Region, Alberta
 Sec 29, Tp 52; R4, W5

| | | |
|--------------------|---|--------------|
| Sampling date | 9-8-79 | 20-9-78 |
| Sampling location | Conveyor to Stockpile | |
| Product name | Power Plant Feed to Wabamun Generating Station of Calgary Power Ltd. | |
| Screen opening, mm | Minus 38, sq | Minus 38, sq |
| ERL number | 3667-79 | 3665-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.11 | 0.08 |
| Sulfate sulphur | % | 0.02 | 0.01 |
| Organic sulphur | % | 0.15 | 0.14 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 54.95 | 53.02 |
| Al ₂ O ₃ | | 19.73 | 22.45 |
| Fe ₂ O ₃ | | 4.08 | 3.69 |
| TiO ₂ | | 0.55 | 0.83 |
| P ₂ O ₅ | | - | 0.22 |
| CaO | | 12.48 | 13.16 |
| MgO | | 2.10 | 2.24 |
| SO ₃ | | 3.99 | 3.32 |
| Na ₂ O | | 0.34 | 0.37 |
| K ₂ O | | 0.78 | 0.73 |
| SrO | | 0.09 | - |
| BaO | | 0.32 | - |
| LOF | | 0.56 | - |

Notes:

MANALTA COAL LIMITED (operator)
 Mine No. 1769 (Highvale); No. 1, 2 & 3 Seams; Wabamun Coalfield (CF39)
 Seba Beach, Pembina Area, Plains Region, Alberta
 Sec 29, Tp 52; R4, W5

| | | |
|-------------------------------|--|--------------|
| Sampling date | 9-8-79 | 9-8-79 |
| Sampling location | Conveyor to Stockpile (Seams No. 2 & 3) | (Seam No. 1) |
| Product name | Feed to Sundance Generating Station of Calgary Power Ltd. | |
| Screen opening, mm | Minus 38, sq | |
| ERL number | 3666-79 | 3666-78 |
| Rank of coal | Subbituminous C | |
| Proximate analysis, equil: | | |
| Moisture | % | 25.72 |
| Ash | % | 11.22 |
| Volatile matter | % | 27.52 |
| Fixed carbon | % | 35.54 |
| Sulphur, equil | % | 0.14 |
| Calorific value, equil: | | |
| MJ/kg | | 20.13 |
| Btu/lb | | 8655 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 67.02 |
| Hydrogen | % | 2.74 |
| Sulphur | % | 0.17 |
| Nitrogen | % | 1.26 |
| Ash | % | 15.11 |
| Oxygen, by difference | % | 13.70 |
| Trace mercury | µg/g (ppm) | 0.00 |
| Ash fusibility temperature: | | |
| Initial | °C | 1070 |
| Spherical | °C | 1330 |
| Hemispherical | °C | 1370 |
| Fluid | °C | 1480 |
| Hardgrove grindability index | | 44 |
| Free swelling index | | NA |

Notes:

MANALTA COAL LIMITED (operator)
 Mine No. 1769 (Highvale); No. 1, 2 & 3 Seams, Wabamun Coalfield (CF39)
 Seba Beach, Pembina Area, Plains Region, Alberta
 Sec 29, Tp 52; R4, W5

| | | |
|--------------------|--|---------|
| Sampling date | 9-8-79 | 9-8-79 |
| Sampling location | Conveyor to Stockpile (Seams No. 2 & 3) (Seam No. 1) | |
| Product name | Feed to Sundance Generating Station of Calgary Power Ltd. | |
| Screen opening, mm | Minus 38, sq | |
| ERL number | 3666-79 | 3666-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.06 | 0.08 |
| Sulfate sulphur | % | 0.00 | 0.00 |
| Organic sulphur | % | 0.11 | 0.14 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 47.20 | 52.19 |
| Al ₂ O ₃ | 24.85 | 24.81 |
| Fe ₂ O ₃ | 5.10 | 3.55 |
| TiO ₂ | 0.68 | 0.73 |
| P ₂ O ₅ | 0.16 | 0.08 |
| CaO | 13.49 | 11.24 |
| MgO | 0.85 | 0.94 |
| SO ₃ | 2.86 | 3.06 |
| Na ₂ O | 2.80 | 2.80 |
| K ₂ O | 0.65 | 0.65 |
| SrO | 0.13 | - |
| BaO | 0.60 | - |
| LOF | 0.06 | - |

Notes:

MANALTA COAL LIMITED
 Mine No. 443 (Roselyn); No. 3 Seam; Sheerness Coalfield (CF37)
 Sheerness, Sheerness Area, Plains Region, Alberta
 Sec 13, Tp 29; R13, W4

| | | | |
|-------------------------------|------------------------------|----------|----------|
| Sampling date | 18-10-78 | 18-10-78 | 18-10-78 |
| Sampling location | Crushing and Screening Plant | | |
| Product name | Lump | Egg | Nut |
| Screen opening, mm | Plus 114 | 114 x 51 | 51 x 32 |
| ERL number | 2803-78 | 3804-78 | 3805-78 |
| Rank of coal | Subbituminous C | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 21.74 | 21.15 |
| Ash | % | 8.22 | 11.27 |
| Volatile matter | % | 30.82 | 29.87 |
| Fixed carbon | % | 39.22 | 37.71 |
| Sulphur, equil | % | 0.39 | 0.42 |
| Calorific value, equil: | | | |
| | MJ/kg | 20.17 | 19.39 |
| | Btu/lb | 8673 | 8335 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 63.98 | 66.90 |
| Hydrogen | % | 3.72 | 1.67 |
| Sulphur | % | 0.50 | 0.53 |
| Nitrogen | % | 1.64 | 1.96 |
| Ash | % | 10.50 | 14.30 |
| Oxygen, by difference | % | 19.66 | 14.64 |
| Trace mercury | µg/g (ppm) | 0.04 | 0.04 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1180 | 1260 |
| Spherical | °C | 1220 | 1350 |
| Hemispherical | °C | 1240 | 1380 |
| Fluid | °C | 1330 | 1400 |
| Hardgrove grindability index | | 26 | 29 |
| Free swelling index | | NA | NA |

Notes:

MANALTA COAL LIMITED
 Mine No. 443 (Roselyn); No. 3 Seam; Sheerness Coalfield (CF37)
 Sheerness, Sheerness Area, Plains Region, Alberta
 Sec 13, Tp 29; R13, W4

| | | | |
|--------------------|------------------------------|----------------------|----------|
| Sampling date | 18-10-78 | 18-10-78 | 18-10-78 |
| Sampling location | Crushing and Screening Plant | | |
| Product name | Lump | Egg | Nut |
| Screen opening, mm | Plus 11 ⁴ | 11 ⁴ x 51 | 51 x 32 |
| ERL number | 2803-78 | 3804-78 | 3805-78 |

Sulphur Forms (dry basis):

| | | | | |
|-----------------------|---|------|------|------|
| Pyritic sulphur | % | 0.05 | 0.05 | 0.09 |
| Sulfate sulphur | % | 0.00 | 0.00 | 0.01 |
| Organic sulphur | % | 0.45 | 0.48 | 0.50 |

Moisture (as rec'd):

| | | | | |
|----------------|---|---|---|---|
| Inherent | % | - | - | - |
| Adherent | % | - | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|-------|-------|-------|
| SiO ₂ | 40.72 | 49.56 | 45.82 |
| Al ₂ O ₃ | 20.30 | 21.43 | 19.52 |
| Fe ₂ O ₃ | 9.34 | 5.57 | 7.83 |
| TiO ₂ | 0.62 | 0.65 | 0.81 |
| P ₂ O ₅ | 0.20 | 0.11 | 0.19 |
| CaO | 13.79 | 10.37 | 11.65 |
| MgO | 1.68 | 1.40 | 1.40 |
| SO ₃ | 9.15 | 6.88 | 8.75 |
| Na ₂ O | 2.90 | 2.12 | 2.44 |
| K ₂ O | 1.41 | 1.98 | 1.61 |
| SrO | - | - | - |
| BaO | - | - | - |
| LOF | - | - | - |

Notes:

MANALTA COAL LIMITED
 Mine No. 443 (Roselyn); No. 3 Seam; Sheerness Coalfield (CF37)
 Sheerness, Sheerness Area, Plains Region, Alberta
 Sec 13, Tp 29; R13, W4

| | | |
|-------------------|------------------------------|----------|
| Sampling date | 18-10-78 | 18-10-78 |
| Sampling location | Crushing and Screening Plant | |

| | | |
|--------------------|---------|----------|
| Product name | Stoker | Slack |
| Screen opening, mm | 32 x 14 | Minus 14 |

| | | |
|------------|---------|---------|
| ERL number | 3806-78 | 3807-78 |
|------------|---------|---------|

| | |
|--------------------|-----------------|
| Rank of coal | Subbituminous C |
|--------------------|-----------------|

Proximate analysis, equil:

| | | | |
|-----------------------|---|-------|-------|
| Moisture | % | 24.26 | 25.49 |
| Ash | % | 9.49 | 11.83 |
| Volatile matter | % | 28.68 | 28.44 |
| Fixed carbon | % | 37.57 | 34.24 |

| | | | |
|----------------------|---|------|------|
| Sulphur, equil | % | 0.36 | 0.50 |
|----------------------|---|------|------|

Calorific value, equil:

| | | |
|--------|-------|-------|
| MJ/kg | 19.26 | 17.86 |
| Btu/lb | 8281 | 7677 |

Ultimate analysis, dry basis:

| | | | |
|----------------------------|---|-------|-------|
| Carbon | % | 61.06 | 57.75 |
| Hydrogen | % | 3.19 | 2.90 |
| Sulphur | % | 0.47 | 0.67 |
| Nitrogen | % | 1.68 | 1.74 |
| Ash | % | 12.53 | 15.88 |
| Oxygen, by difference | % | 21.07 | 21.06 |

| | | | |
|---------------|------------|------|------|
| Trace mercury | µg/g (ppm) | 0.03 | 0.04 |
|---------------|------------|------|------|

Ash fusibility temperature:

| | | | |
|---------------------|----|------|------|
| Initial | °C | 1180 | 1205 |
| Spherical | °C | 1260 | 1280 |
| Hemispherical | °C | 1315 | 1305 |
| Fluid | °C | 1395 | 1370 |

| | | |
|------------------------------|---|---|
| Hardgrove grindability index | - | - |
|------------------------------|---|---|

| | | |
|---------------------------|----|----|
| Free swelling index | NA | NA |
|---------------------------|----|----|

Notes:

MANALTA COAL LIMITED
 Mine No. 443 (Roselyn); No. 3 Seam; Sheerness Coalfield (CF37)
 Sheerness, Sheerness Area, Plains Region, Alberta
 Sec 13, Tp 29; R13, W⁴

| | | |
|--------------------|------------------------------|----------|
| Sampling date | 18-10-78 | 18-10-78 |
| Sampling location | Crushing and Screening Plant | |
| Product name | Stoker | Slack |
| Screen opening, mm | 32 x 14 | Minus 14 |
| ERL number | 3806-78 | 3807-78 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.07 | 0.19 |
| Sulfate sulphur | % | 0.01 | 0.06 |
| Organic sulphur | % | 0.39 | 0.42 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | | |
|--------------------------------|--|-------|-------|
| SiO ₂ | | 47.18 | 49.85 |
| Al ₂ O ₃ | | 21.31 | 18.90 |
| Fe ₂ O ₃ | | 4.72 | 7.36 |
| TiO ₂ | | 0.71 | 1.18 |
| P ₂ O ₅ | | 0.74 | 0.15 |
| CaO | | 10.42 | 9.49 |
| MgO | | 1.25 | 1.50 |
| SO ₃ | | 7.37 | 7.88 |
| Na ₂ O | | 5.42 | 2.13 |
| K ₂ O | | 0.92 | 1.57 |
| SrO | | - | - |
| BaO | | - | - |
| LOF | | - | - |

Notes:

MANALTA COAL LIMITED
 Mine No. 443 (Roselyn); No. 3 Seam; Sheerness Coalfield (CF37)
 Sheerness, Sheerness Area, Plains Region, Alberta
 Sec 13, Tp 29; R13, W4

| | | |
|-------------------------------|-----------------|-----------|
| Sampling date | 5-11-79 | 5-11-79 |
| Sampling location | Stockpile | Stockpile |
| Product name | Thermal Coal | Nut |
| Screen opening, mm | Minus 203 | 50 x 32 |
| ERL number | 4044-79 | 4041-79 |
| Rank of coal | Subbituminous C | |
| Proximate analysis, equil: | | |
| Moisture | % | 24.27 |
| Ash | % | 17.53 |
| Volatile matter | % | 27.67 |
| Fixed carbon | % | 30.53 |
| Sulphur, equil | % | 0.86 |
| Calorific value, equil: | | |
| MJ/kg | 16.61 | 18.85 |
| Btu/lb | 7142 | 8102 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 56.81 |
| Hydrogen | % | 1.20 |
| Sulphur | % | 1.14 |
| Nitrogen | % | 1.27 |
| Ash | % | 23.15 |
| Oxygen, by difference | % | 16.43 |
| Trace mercury | µg/g (ppm) | 0.00 |
| Ash fusibility temperature: | | |
| Initial | °C | 1160 |
| Spherical | °C | 1350 |
| Hemispherical | °C | 1390 |
| Fluid | °C | 1445 |
| Hardgrove grindability index | | 34 |
| Free swelling index | NA | NA |

Notes:

MANALTA COAL LIMITED
 Mine No. 443 (Roselyn); No. 3 Seam; Sheerness Coalfield (CF37)
 Sheerness, Sheerness Area, Plains Region, Alberta
 Sec 13, Tp 29; R13, W4

| | | |
|--------------------|--------------|-----------|
| Sampling date | 5-11-79 | 5-11-79 |
| Sampling location | Stockpile | Stockpile |
| Product name | Thermal Coal | Nut |
| Screen opening, mm | Minus 203 | 50 x 32 |
| ERL number | 4044-79 | 4041-79 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.63 | 0.07 |
| Sulfate sulphur | % | 0.05 | 0.00 |
| Organic sulphur | % | 0.46 | 0.52 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 55.02 | 36.50 |
| Al ₂ O ₃ | 15.10 | 17.05 |
| Fe ₂ O ₃ | 11.59 | 11.03 |
| TiO ₂ | 0.34 | 0.47 |
| P ₂ O ₅ | - | 0.28 |
| CaO | 5.06 | 15.52 |
| MgO | 1.38 | 1.52 |
| SO ₃ | 4.98 | 9.86 |
| Na ₂ O | 3.20 | 2.43 |
| K ₂ O | 0.76 | 0.79 |
| SrO | 0.09 | 0.19 |
| BaO | 0.31 | 0.36 |
| LOF | 0.93 | 2.14 |

Notes:

MANALTA COAL LIMITED
 Mine No. 443 (Roselyn); No. 3 Seam; Sheerness Coalfield (CF37)
 Sheerness, Sheerness Area, Plains Region, Alberta
 Sec 13, Tp 29; R13, W4

| | | |
|--------------------|-------------|-----------|
| Sampling date | 5-11-79 | 5-11-79 |
| Sampling location | Stockpile | Stockpile |
| Product name | Stoker | Slack |
| Screen opening, mm | 32 x 13, sq | Minus 13 |
| ERL number | 4042-79 | 4043-79 |

Rank of coal Subbituminous C

Proximate analysis, equil:

| | | | |
|-----------------------|---|-------|-------|
| Moisture | % | 26.49 | 24.83 |
| Ash | % | 8.96 | 12.08 |
| Volatile matter | % | 39.78 | 40.19 |
| Fixed carbon | % | 24.77 | 22.90 |

| | | | |
|----------------------|---|------|------|
| Sulphur, equil | % | 0.43 | 0.54 |
|----------------------|---|------|------|

Calorific value, equil:

| | | |
|--------|-------|-------|
| MJ/kg | 18.59 | 17.88 |
| Btu/lb | 7993 | 7685 |

Ultimate analysis, dry basis:

| | | | |
|----------------------------|---|-------|-------|
| Carbon | % | 69.33 | 61.45 |
| Hydrogen | % | 1.79 | 1.28 |
| Sulphur | % | 0.58 | 0.72 |
| Nitrogen | % | 1.26 | 1.56 |
| Ash | % | 12.20 | 16.07 |
| Oxygen, by difference | % | 14.84 | 18.92 |

| | | | |
|---------------|------------|------|------|
| Trace mercury | µg/g (ppm) | 0.00 | 0.00 |
|---------------|------------|------|------|

Ash fusibility temperature:

| | | | |
|---------------------|----|------|------|
| Initial | °C | 1155 | 1150 |
| Spherical | °C | 1300 | 1310 |
| Hemispherical | °C | 1310 | 1320 |
| Fluid | °C | 1395 | 1345 |

| | | |
|------------------------------|----|----|
| Hardgrove grindability index | 29 | 31 |
|------------------------------|----|----|

| | | |
|---------------------------|----|----|
| Free swelling index | NA | NA |
|---------------------------|----|----|

Notes:

MANALTA COAL LIMITED
 Mine No. 443 (Roselyn); No. 3 Seam; Sheerness Coalfield (CF37)
 Sheerness, Sheerness Area, Plains Region, Alberta
 Sec 13, Tp 29; R13, W4

| | | |
|--------------------|-------------|-----------|
| Sampling date | 5-11-79 | 5-11-79 |
| Sampling location | Stockpile | Stockpile |
| Product name | Stoker | Slack |
| Screen opening, mm | 32 x 13, sq | Minus 13 |
| ERL number | 4042-79 | 4043-79 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.07 | 0.16 |
| Sulfate sulphur | % | 0.00 | 0.08 |
| Organic sulphur | % | 0.51 | 0.48 |


Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 43.66 | 40.33 |
| Al ₂ O ₃ | 17.55 | 17.90 |
| Fe ₂ O ₃ | 8.81 | 7.17 |
| TiO ₂ | 0.50 | 0.43 |
| P ₂ O ₅ | 0.15 | 0.46 |
| CaO | 12.74 | 14.39 |
| MgO | 1.51 | 2.60 |
| SO ₃ | 8.86 | 10.63 |
| Na ₂ O | 2.03 | 1.31 |
| K ₂ O | 1.07 | 0.82 |
| SrO | 0.17 | 0.25 |
| BaO | 0.28 | 0.79 |
| LOF | 2.04 | 2.04 |

Notes:



COAL ANALYSES - ALBERTA (Bituminous)

THE CANMORE MINES LIMITED
 Mine No. 1775 (Riverside, Wilson No. 3 Mines); Cascade Coalfield (CF44)
 Canmore, Cascade Area, Mountain Region, Alberta
 Sec 1, Tp 24; R10, W5

| Sampling date | 6-9-78 | 6-9-78 | 6-9-78 |
|-------------------------------|------------------------|--------------|------------|
| Sampling location | Coal Preparation Plant | | |
| Product name | Clean Coal | Cobble | Stoker |
| Screen opening, mm | Minus 32, sq | 101 x 32, sq | 32 x 6, sq |
| ERL number | 3622-78 | 3623-78 | 3624-78 |
| Rank of coal | Semi-anthracite | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 3.14 | 3.42 |
| Ash | % | 12.28 | 7.11 |
| Volatile matter | % | 11.19 | 11.47 |
| Fixed carbon | % | 73.39 | 78.00 |
| Sulphur, as rec'd: | % | 0.80 | 0.77 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 30.88 | 31.69 |
| Btu/lb | | 13 274 | 13 626 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 79.12 | 84.98 |
| Hydrogen | % | 3.74 | 3.94 |
| Sulphur | % | 0.82 | 0.80 |
| Nitrogen | % | 1.48 | 1.43 |
| Ash | % | 12.68 | 7.36 |
| Oxygen, by difference | % | 2.16 | 1.49 |
| Trace mercury | µg/g (ppm) | 0.07 | 0.06 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1370 | 1295 |
| Spherical | °C | 1480+ | 1480+ |
| Hemispherical | °C | 1480+ | 1480+ |
| Fluid | °C | 1480+ | 1480+ |
| Hardgrove grindability index | | 80 | 66 |
| Free swelling index | | NA | NA |

Notes:

THE CANMORE MINES LIMITED
 Mine No. 1775 (Riverside, Wilson No. 3 Mines); Cascade Coalfield (CF44)
 Canmore, Cascade Area, Mountain Region, Alberta
 Sec 1, Tp 24; R10, W5

| | | | |
|--------------------|------------------------|--------------|------------|
| Sampling date | 6-9-78 | 6-9-78 | 6-9-78 |
| Sampling location | Coal Preparation Plant | | |
| Product name | Clean Coal | Cobble | Stoker |
| Screen opening, mm | Minus 32, sq | 101 x 32, sq | 32 x 6, sq |
| ERL number | 3622-78 | 3623-78 | 3624-78 |

Sulphur Forms (dry basis):

| | |
|-----------------------|---|
| Pyritic sulphur | % |
| Sulfate sulphur | % |
| Organic sulphur | % |

Moisture (as rec'd):

| | |
|----------------|---|
| Inherent | % |
| Adherent | % |

Ash analysis, %:

| | | | |
|--------------------------------|-------|-------|-------|
| SiO ₂ | 62.65 | 55.31 | 59.20 |
| Al ₂ O ₃ | 26.03 | 28.05 | 28.30 |
| Fe ₂ O ₃ | 3.17 | 8.91 | 5.57 |
| TiO ₂ | 1.52 | 1.32 | 1.35 |
| P ₂ O ₅ | 1.11 | 0.97 | 1.06 |
| CaO | 1.14 | 1.54 | 1.11 |
| MgO | 0.70 | 1.05 | 0.67 |
| SO ₃ | 1.13 | 2.02 | 1.50 |
| Na ₂ O | 0.31 | 0.19 | 0.20 |
| K ₂ O | 2.35 | 0.70 | 1.12 |
| SrO | - | - | - |
| BaO | - | - | - |
| LOF | - | - | - |

Notes:

CARDINAL RIVER COALS LIMITED
 Mine No. 1768 (Cardinal River); Jewell Seam; Mountain Park Coalfield (CF49)
 Hinton, Mountain Park Area, Mountain Region, Alberta
 Sec 15, 16, 22; Tp 47; R24, W5

| | | |
|-------------------------------|----------------------------|------------------------|
| Sampling date | 25-8-79 | 26-6-78 |
| Sampling location | | Coal Preparation Plant |
| Product name | Clean Coal Product | |
| Screen opening, mm | Minus 38, rd | |
| ERL number | 3665-79 | 3156-78 |
| Rank of coal | Medium-volatile bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 1.46 |
| Ash | % | 8.88 |
| Volatile matter | % | 19.86 |
| Fixed carbon | % | 69.80 |
| Sulphur, as rec'd: | % | 0.30 |
| Calorific value, as rec'd: | | |
| MJ/kg | 32.10 | 30.77 |
| Btu/lb | 13 801 | 13 230 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 82.64 |
| Hydrogen | % | 4.57 |
| Sulphur | % | 0.30 |
| Nitrogen | % | 1.39 |
| Ash | % | 9.01 |
| Oxygen, by difference | % | 2.09 |
| Trace mercury | µg/g (ppm) | 0.00 |
| Ash fusibility temperature: | | |
| Initial | °C | 1175 |
| Spherical | °C | 1325 |
| Hemispherical | °C | 1380 |
| Fluid | °C | 1435 |
| Hardgrove grindability index | | 84 |
| Free swelling index | | 3.0 |
| Notes: | | 7.5 |

CARDINAL RIVER COALS LIMITED
 Mine No. 1768 (Cardinal River); Jewell Seam; Mountain Park Coalfield (CF49)
 Hinton, Mountain Park Area, Mountain Region, Alberta
 Sec 15, 16, 22; Tp 47; R24, W5

| | | |
|--------------------|------------------------|---------|
| Sampling date | 25-8-79 | 26-6-78 |
| Sampling location | Coal Preparation Plant | |
| Product name | Clean Coal Product | |
| Screen opening, mm | Minus 38, rd | |
| ERL number | 3665-79 | 3156-78 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 0.07 |
| Sulfate sulphur | % | 0.01 |
| Organic sulphur | % | 0.22 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 47.81 | 52.81 |
| Al ₂ O ₃ | 24.83 | 26.50 |
| Fe ₂ O ₃ | 4.81 | 3.89 |
| TiO ₂ | 0.76 | 1.39 |
| P ₂ O ₅ | 0.36 | 0.79 |
| CaO | 7.33 | 6.30 |
| MgO | 2.15 | 1.97 |
| SO ₃ | 5.24 | 4.55 |
| Na ₂ O | 1.45 | 1.48 |
| K ₂ O | 0.35 | 0.32 |
| SrO | 0.15 | - |
| BaO | 0.64 | - |
| LOF | 3.77 | - |

Notes:

COLEMAN COLLIERIES LIMITED
 Mine No. 1695 (Tent Mountain); Mine No. 1747; Vicary Creek
 Tent Mountain Coalfield (CF56)
 Coleman, Crowsnest Area, Mountain Region, Alberta
 Sec 12, Tp 7; R6, W6

| | | | |
|-------------------------------|----------------------------|------------------------|--------|
| Sampling date | 20-6-79 | 6-6-78 | |
| Sampling location | | Coal Preparation Plant | |
| Product name | Clean Coal Product | | |
| Screen opening, mm | Minus 55, rd | | |
| ERL number | 3669-79 | 3155-78 | |
| Rank of coal | Medium-volatile bituminous | | |
| Proximate analysis, as rec'd: | | | |
| Moisture | % | 1.62 | 6.70 |
| Ash | % | 12.42 | 11.31 |
| Volatile matter | % | 23.57 | 22.11 |
| Fixed carbon | % | 62.39 | 59.88 |
| Sulphur, as rec'd: | % | 0.45 | 0.33 |
| Calorific value, as rec'd: | | | |
| MJ/kg | | 30.36 | 29.00 |
| Btu/lb | | 13 055 | 12 470 |
| Ultimate analysis, dry basis: | | | |
| Carbon | % | 77.07 | 77.30 |
| Hydrogen | % | 4.50 | 4.35 |
| Sulphur | % | 0.46 | 0.35 |
| Nitrogen | % | 1.15 | 1.04 |
| Ash | % | 12.62 | 12.12 |
| Oxygen, by difference | % | 4.20 | 4.84 |
| Trace mercury | µg/g (ppm) | 0.00 | 0.07 |
| Ash fusibility temperature: | | | |
| Initial | °C | 1480+ | 1480+ |
| Spherical | °C | 1480+ | 1400+ |
| Hemispherical | °C | 1480+ | 1480+ |
| Fluid | °C | 1480+ | 1480+ |
| Hardgrove grindability index | | 79 | - |
| Free swelling index | | 3 | 4 |

Notes:

COLEMAN COLLIERIES LIMITED
 Mine No. 1695 (Tent Mountain); Mine No. 1747; Vicary Creek
 Tent Mountain Coalfield (CF56)
 Coleman, Crowsnest Area, Mountain Region, Alberta
 Sec 12, Tp 7; R6, W6

| | | |
|--------------------|------------------------|---------|
| Sampling date | 20-6-79 | 6-6-78 |
| Sampling location | Coal Preparation Plant | |
| Product name | Clean Coal Product | |
| Screen opening, mm | Minus 55, rd | |
| ERL number | 3669-79 | 3155-78 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 0.05 |
| Sulfate sulphur | % | 0.00 |
| Organic sulphur | % | 0.41 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 55.72 | 55.57 |
| Al ₂ O ₃ | 32.36 | 30.32 |
| Fe ₂ O ₃ | 2.58 | 2.57 |
| TiO ₂ | 1.78 | 2.39 |
| P ₂ O ₅ | 0.53 | 1.79 |
| CaO | 2.68 | 2.98 |
| MgO | 0.72 | 1.30 |
| SO ₃ | 1.57 | 2.23 |
| Na ₂ O | 0.19 | 0.27 |
| K ₂ O | 0.91 | 0.58 |
| SrO | 0.11 | - |
| BaO | 0.65 | - |
| LOF | 0.64 | - |

Notes:

MCINTYRE MINES LIMITED
 Mines No. 1765 & 1771 (Smoky River); No. 4 & 11 Seams;
 Smoky River Coalfield (CF55), Grande Cache, Smoky River Area,
 Mountain Region, Alberta

| | | |
|-------------------------------|-------------------------|------------|
| Sampling date | 24-8-79 | 28-6-78 |
| Sampling location | Coal Preparation Plant | |
| Product name | Clean Coal | Clean Coal |
| Screen opening, mm | Minus 38, rd | |
| ERL number | 3664-79 | 3154-78 |
| Rank of coal | Low-volatile bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 1.10 |
| Ash | % | 7.33 |
| Volatile matter | % | 18.41 |
| Fixed carbon | % | 73.18 |
| Sulphur, as rec'd: | % | 0.43 |
| Calorific value, as rec'd: | | |
| MJ/kg | | 32.24 |
| Btu/lb | 14 337 | 13 860 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 84.59 |
| Hydrogen | % | 4.67 |
| Sulphur | % | 0.43 |
| Nitrogen | % | 1.28 |
| Ash | % | 7.41 |
| Oxygen, by difference | % | 1.62 |
| Trace mercury | µg/g (ppm) | - |
| | | 0.10 |
| Ash fusibility temperature: | | |
| Initial | °C | 1450 |
| Spherical | °C | 1480+ |
| Hemispherical | °C | 1480+ |
| Fluid | °C | 1480+ |
| Hardgrove grindability index | | 89 |
| Free swelling index | 5.0 | 8.0 |

Notes:

MCINTYRE MINES LIMITED
 Mines No. 1765 & 1771 (Smoky River); No. 4 & 11 Seams;
 Smoky River Coalfield (CF55), Grande Cache, Smoky River Area,
 Mountain Region, Alberta

| | | |
|--------------------|------------------------|------------|
| Sampling date | 24-8-79 | 28-6-78 |
| Sampling location | Coal Preparation Plant | |
| Product name | Clean Coal | Clean Coal |
| Screen opening, mm | Minus 38, rd | |
| ERL number | 3664-79 | 3154-78 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 0.07 |
| Sulfate sulphur | % | 0.00 |
| Organic sulphur | % | 0.36 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 51.27 | 54.42 |
| Al ₂ O ₃ | 25.72 | 31.07 |
| Fe ₂ O ₃ | 4.11 | 3.88 |
| TiO ₂ | 1.24 | 1.94 |
| P ₂ O ₅ | 1.41 | 1.56 |
| CaO | 3.77 | 3.34 |
| MgO | 0.44 | 0.19 |
| SO ₃ | 1.93 | 1.73 |
| Na ₂ O | 1.14 | 1.13 |
| K ₂ O | 0.52 | 0.74 |
| SrO | 0.29 | - |
| BaO | 0.67 | - |
| LOF | - | - |

Notes:

LUSCAR STERCO (1977) LTD.
 Mine No. 1778 (Coal Valley Mine); Weldwood Pit; Coalspur Coal Field (CF-57)
 Foothills Region, Alberta
 Tp 21; R21; W4

| | |
|--------------------|-------------------|
| Sampling date | 3 & 4-7-79 |
| Sampling location | Coal Valley Plant |
| Product name | Clean Coal |
| Screen opening, mm | Minus 51, sq |
| ERL number | 3794-79 |

Rank of coal High-volatile C bituminous

Proximate analysis, equil:

| | | |
|-----------------------|---|-------|
| Moisture | % | 8.16 |
| Ash | % | 10.33 |
| Volatile matter | % | 27.48 |
| Fixed carbon | % | 54.03 |

Sulphur, equil: % 0.31

Calorific value, equil:

| | |
|--------|--------|
| MJ/kg | 24.75 |
| Btu/lb | 10 639 |

Ultimate analysis, dry basis:

| | | |
|----------------------------|---|-------|
| Carbon | % | 69.44 |
| Hydrogen | % | 3.08 |
| Sulphur | % | 0.34 |
| Nitrogen | % | 0.79 |
| Ash | % | 11.25 |
| Oxygen, by difference | % | 15.10 |

Trace mercury ug/g (ppm) 0.02

Ash fusibility temperature:

| | | |
|---------------------|----|------|
| Initial | °C | 1100 |
| Spherical | °C | 1220 |
| Hemispherical | °C | 1320 |
| Fluid | °C | 1330 |

Hardgrove grindability index 44

Free swelling index N/A

Notes:

LUSCAR STERCO (1977) LTD.
 Mine No. 1778 (Coal Valley Mine); Weldwood Pit; Coalspur Coal Field (CF-57)
 Foothills Region, Alberta
 Tp 21; R21; W4

| | |
|--------------------|-------------------|
| Sampling date | 3 & 4-7-79 |
| Sampling location | Coal Valley Plant |
| Product name | Clean Coal |
| Screen opening, mm | Minus 51, sq |
| ERL number | 3794-79 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 0.11 |
| Sulfate sulphur | % | 0.01 |
| Organic sulphur | % | 0.22 |


Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | |
|--------------------------------|-------|
| SiO ₂ | 49.79 |
| Al ₂ O ₃ | 17.60 |
| Fe ₂ O ₃ | 4.89 |
| TiO ₂ | 0.57 |
| P ₂ O ₅ | 0.31 |
| CaO | 13.44 |
| MgO | 1.94 |
| SO ₃ | 5.00 |
| Na ₂ O | 3.13 |
| K ₂ O | 0.65 |
| SrO | 0.25 |
| BaO | 0.78 |
| LOF | 0.66 |

Notes:



COAL ANALYSES - BRITISH COLUMBIA

BYRON CREEK COLLIERIES LIMITED
 Corbin Mine; Mammoth Seam; Crowsnest Coalfield
 Corbin, Kootenay Mining District, British Columbia

| | | |
|-------------------------------|---------------------------------|---------|
| Sampling date | 18-6-79 | 16-8-78 |
| Sampling location | Automatic Sampler At Wash Plant | |
| Product name | Clean Coal Product | |
| Screen opening, mm | Minus 51 | |
| ERL number | 3668-79 | 3431-78 |
| Rank of coal | Medium-volatile bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 1.23 |
| Ash | % | 14.18 |
| Volatile matter | % | 22.77 |
| Fixed carbon | % | 61.82 |
| Sulphur, as rec'd: | % | 0.17 |
| Calorific value, as rec'd: | | |
| MJ/kg | 29.68 | 29.04 |
| Btu/lb | 12 760 | 12 486 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 75.42 |
| Hydrogen | % | 4.33 |
| Sulphur | % | 0.17 |
| Nitrogen | % | 1.30 |
| Ash | % | 14.36 |
| Oxygen, by difference | % | 4.42 |
| Trace mercury | µg/g (ppm) | 0.00 |
| Ash fusibility temperature: | | |
| Initial | °C | 1405 |
| Spherical | °C | 1480+ |
| Hemispherical | °C | 1480+ |
| Fluid | °C | 1480+ |
| Hardgrove grindability index | | 70 |
| Free swelling index | | 1.5 |
| Notes: | | 1.0 |

BYRON CREEK COLLIERIES LIMITED
 Corbin Mine; Mammoth Seam; Crowsnest Coalfield
 Corbin, Kootenay Mining District, British Columbia

| | | |
|--------------------|---------------------------------|---------|
| Sampling date | 18-6-79 | 16-8-78 |
| Sampling location | Automatic Sampler At Wash Plant | |
| Product name | Clean Coal Product | |
| Screen opening, mm | Minus 51 | |
| ERL number | 3668-79 | 3431-78 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 0.11 |
| Sulfate sulphur | % | 0.02 |
| Organic sulphur | % | 0.04 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 51.82 | 49.25 |
| Al ₂ O ₃ | 29.66 | 31.99 |
| Fe ₂ O ₃ | 3.79 | 2.45 |
| TiO ₂ | 1.56 | 2.06 |
| P ₂ O ₅ | 0.25 | 0.63 |
| CaO | 4.97 | 6.45 |
| MgO | 1.23 | 1.72 |
| SO ₃ | 4.17 | 3.77 |
| Na ₂ O | 0.69 | 1.19 |
| K ₂ O | 0.35 | 0.66 |
| SrO | 0.13 | - |
| BaO | 0.55 | - |
| LOF | 1.20 | - |

Notes:

FORDING COAL LIMITED
 Greenhills, Clode & Taylor Pits; Elk Valley Coalfield
 Elkford, East Kootenay District, British Columbia

| | | |
|--------------------|--|------------------------------------|
| Sampling date | 19-6-79 | 31-5-78 |
| Sampling location | Automatic Train (Composite of 5 trains) | Sampler (Composite of 6 trains) |
| Product name | Clean Coal Product | |
| Screen opening, mm | Minus 38, rd | |
| ERL number | 3673-79 | 3153-78 |

Rank of coal Medium-volatile bituminous

Proximate analysis, as rec'd:

| | | | |
|-----------------------|---|-------|-------|
| Moisture | % | 1.37 | 8.83 |
| Ash | % | 9.65 | 9.31 |
| Volatile matter | % | 23.27 | 19.81 |
| Fixed carbon | % | 65.71 | 62.05 |

Sulphur, as rec'd: % 0.40 0.36

Calorific value, as rec'd:

| | | |
|--------|--------|--------|
| MJ/kg | 31.78 | 29.38 |
| Btu/lb | 13 664 | 12 630 |

Ultimate analysis, dry basis:

| | | | |
|----------------------------|---|-------|-------|
| Carbon | % | 81.17 | 80.65 |
| Hydrogen | % | 4.81 | 4.35 |
| Sulphur | % | 0.41 | 0.40 |
| Nitrogen | % | 1.35 | 1.09 |
| Ash | % | 9.78 | 10.21 |
| Oxygen, by difference | % | 2.48 | 3.30 |

Trace mercury μg/g (ppm) 0.00 0.06

Ash fusibility temperature:

| | | | |
|---------------------|----|-------|-------|
| Initial | °C | 1480+ | 1480+ |
| Spherical | °C | 1480+ | 1400+ |
| Hemispherical | °C | 1480+ | 1480+ |
| Fluid | °C | 1480+ | 1480+ |

Hardgrove grindability index 95 -

Free swelling index 5 8

Notes:

FORDING COAL LIMITED
 Greenhills, Clode & Taylor Pits; Elk Valley Coalfield
 Elkford, East Kootenay District, British Columbia

| | | |
|--------------------|--|------------------------------------|
| Sampling date | 19-6-79 | 31-5-78 |
| Sampling location | Automatic Train (Composite of 5 trains) | Sampler (Composite of 6 trains) |
| Product name | Clean Coal Product | |
| Screen opening, mm | Minus 38, rd | |
| ERL number | 3673-79 | 3153-78 |

Sulphur Forms (dry basis):

| | | |
|-----------------------|---|------|
| Pyritic sulphur | % | 0.07 |
| Sulfate sulphur | % | 0.00 |
| Organic sulphur | % | 0.34 |

Moisture (as rec'd):

| | | |
|----------------|---|---|
| Inherent | % | - |
| Adherent | % | - |

Ash analysis, %:

| | |
|-------------------------|-------|
| SiO_2 | 59.51 |
| Al_2O_3 | 30.66 |
| Fe_2O_3 | 3.77 |
| TiO_2 | 1.85 |
| P_2O_5 | 1.09 |
| CaO | 1.31 |
| MgO | 0.41 |
| SO_3 | 0.39 |
| Na_2O | 0.06 |
| K_2O | 0.95 |
| SrO | - |
| BaO | - |
| LOF | - |

Notes:

KAISER RESOURCES LIMITED
 Harmer Ridge Mine & Michel Colliery; Balmer Seam; Crowsnest Coalfield
 Sparwood, East Kootenay District, British Columbia

| | | |
|-------------------------------|--------------------------------|---------------|
| Sampling date | 10-6-78 | 10-6-78 |
| Sampling location | Elkview Coal Preparation Plant | |
| Product name | Clean Coal | Oxidized Coal |
| Screen opening, mm | Minus 38, sq | Minus 13, sq |
| ERL number | 3151-78 | 3152-78 |
| Rank of coal | Medium-volatile bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 6.88 |
| Ash | % | 9.36 |
| Volatile matter | % | 18.99 |
| Fixed carbon | % | 64.77 |
| Sulphur, as rec'd: | % | 0.32 |
| Calorific value, as rec'd: | | |
| MJ/kg | 30.80 | 28.21 |
| Btu/lb | 13 240 | 12 130 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 81.29 |
| Hydrogen | % | 4.50 |
| Sulphur | % | 0.34 |
| Nitrogen | % | 1.18 |
| Ash | % | 10.05 |
| Oxygen, by difference | % | 2.64 |
| Trace mercury | µg/g (ppm) | 0.06 |
| Ash fusibility temperature: | | |
| Initial | °C | 1400 |
| Spherical | °C | 1480+ |
| Hemispherical | °C | 1480+ |
| Fluid | °C | 1480+ |
| Hardgrove grindability index | - | - |
| Free swelling index | 7.5 | 7.5 |

Notes:

KAISER RESOURCES LIMITED
 Harmer Ridge Mine & Michel Colliery; Balmer Seam; Crowsnest Coalfield
 Sparwood, East Kootenay District, British Columbia

| | | |
|--------------------|--------------------------------|---------------|
| Sampling date | 10-6-78 | 10-6-78 |
| Sampling location | Elkview Coal Preparation Plant | |
| Product name | Clean Coal | Oxidized Coal |
| Screen opening, mm | Minus 38, sq | Minus 13, sq |
| ERL number | 3151-78 | 3152-78 |

Sulphur Forms (dry basis):

| | |
|-----------------------|---|
| Pyritic sulphur | % |
| Sulfate sulphur | % |
| Organic sulphur | % |

Moisture (as rec'd):

| | |
|----------------|---|
| Inherent | % |
| Adherent | % |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 64.75 | 62.96 |
| Al ₂ O ₃ | 26.71 | 30.85 |
| Fe ₂ O ₃ | 2.15 | 0.98 |
| TiO ₂ | 1.74 | 1.73 |
| P ₂ O ₅ | 1.09 | 0.45 |
| CaO | 1.75 | 1.30 |
| MgO | 0.70 | 0.26 |
| SO ₃ | 0.70 | 0.65 |
| Na ₂ O | 0.05 | 0.05 |
| K ₂ O | 0.36 | 0.77 |
| SrO | - | - |
| BaO | - | - |
| LOF | - | - |

Notes:

KAISER RESOURCES LIMITED
 Harmer Ridge Mine & Michel Colliery; Balmer Seam; Crowsnest Coalfield
 Sparwood, East Kootenay District, British Columbia

| | | |
|-------------------------------|----------------------------|---------------------------|
| Sampling date | 12-6-79 | 15-6-78 |
| Sampling location | Elkview Preparation Plant | Composite of 8 train cars |
| Product name | Clean Coal | Oxidized Coal |
| Screen opening, mm | Minus 38, sq | Minus 13, sq |
| ERL number | 3670-79 | 3672-79 |
| Rank of coal | Medium-volatile bituminous | |
| Proximate analysis, as rec'd: | | |
| Moisture | % | 0.98 |
| Ash | % | 9.53 |
| Volatile matter | % | 21.05 |
| Fixed carbon | % | 68.44 |
| Sulphur, as rec'd: | % | 0.31 |
| Calorific value, as rec'd: | | |
| MJ/kg | 32.20 | 28.31 |
| Btu/lb | 13 846 | 12 173 |
| Ultimate analysis, dry basis: | | |
| Carbon | % | 81.43 |
| Hydrogen | % | 4.79 |
| Sulphur | % | 0.31 |
| Nitrogen | % | 1.23 |
| Ash | % | 9.62 |
| Oxygen, by difference | % | 2.62 |
| Trace mercury | µg/g (ppm) | 0.00 |
| Ash fusibility temperature: | | |
| Initial | °C | 1400+ |
| Spherical | °C | 1480+ |
| Hemispherical | °C | 1480+ |
| Fluid | °C | 1480+ |
| Hardgrove grindability index | | 89 |
| Free swelling index | | 4.0 |

Notes:

KAISER RESOURCES LIMITED

Harmer Ridge Mine & Michel Colliery; Balmer Seam; Crowsnest Coalfield
Sparwood, East Kootenay District, British Columbia

| | | |
|--------------------|---------------------------|---------------------------|
| Sampling date | 12-6-79 | 15-6-78 |
| Sampling location | Elkview Preparation Plant | Composite of 8 train cars |
| Product name | Clean Coal | Oxidized Coal |
| Screen opening, mm | Minus 38, sq | Minus 13, sq |
| ERL number | 3670-79 | 3672-79 |

Sulphur Forms (dry basis):

| | | | |
|-----------------------|---|------|------|
| Pyritic sulphur | % | 0.04 | 0.07 |
| Sulfate sulphur | % | 0.00 | 0.00 |
| Organic sulphur | % | 0.27 | 0.24 |

Moisture (as rec'd):

| | | | |
|----------------|---|---|---|
| Inherent | % | - | - |
| Adherent | % | - | - |

Ash analysis, %:

| | | |
|--------------------------------|-------|-------|
| SiO ₂ | 62.45 | 56.57 |
| Al ₂ O ₃ | 27.22 | 29.16 |
| Fe ₂ O ₃ | 3.31 | 5.62 |
| TiO ₂ | 1.58 | 1.73 |
| P ₂ O ₅ | 0.62 | 0.97 |
| CaO | 2.07 | 1.89 |
| MgO | 0.44 | 0.70 |
| SO ₃ | 0.77 | 0.53 |
| Na ₂ O | 0.07 | 0.05 |
| K ₂ O | 0.47 | 0.95 |
| SrO | 0.03 | 0.08 |
| BaO | 0.23 | 0.18 |
| LOF | - | 0.44 |

Notes:

REFERENCES

1. Swartzman, E. "Analysis Directory of Canadian Coals"; 2nd edition; Report 836; EMR, Mines Branch (since renamed CANMET), Fuels Division; 1953.
2. Swartzman, E. and Tibbetts, T.E. ibid, Supplement No. 1; Report 850; EMR, Mines Branch, Fuels Division; 1955.
3. Tibbetts, T.E. and Montgomery, W.J. ibid, Supplement No. 2; Monograph 868; EMR, Mines Branch, Fuels and Mining Practice Division; 1960.
4. Tibbetts, T.E. and Montgomery, W.J. and Faurschou, D.K. "Analysis Directory of Canadian Commercial Coals - Supplement No. 3"; CANMET Report 79-7; CANMET, EMR; December 1978.
5. "Operators list 4, coal mines in Canada"; Energy, Mines and Resources; DSS Cat. No. M36-79/4; January 1979.
6. Bielenstein, H.U., Chrismas, L.P., Latour, B.A. and Tibbetts, T.E. "Coal Resources and Reserves of Canada"; EMR, Report ER 79-9; December 1979.
7. "1976 Assessment of Canada's Coal Resources and Reserves"; EMR, Report EP 77-5 (DSS Cat. No. M23-12/77-5); 1977.

Table 1 - Summary classification of coal by rank

| VM* | FC* | Class | Group(rank) | Calorific value** | |
|-----|------|------------------------------|--------------------------------|-------------------|-------|
| | | | | Btu/lb | MJ/kg |
| 2 | 98 - | | Meta - Anthracite | | |
| 8 | 92 - | Anthracitic ⁽¹⁾ | Anthracite | | |
| 14 | 86 | | Semianthracite | | |
| | | | Low-volatile | | |
| 22 | 78 - | | bituminous | | |
| | | | Medium-volatile | | |
| | | | bituminous | | |
| 31 | 69 - | Bituminous ⁽²⁾ | High-volatile A | | |
| | | | bituminous | 14 000 | 32.6 |
| | | | High-volatile B | | |
| | | | bituminous | 13 000 | 30.2 |
| | | | High-volatile C | | |
| | | | bituminous | 11 500 | 26.7 |
| | | | Subbituminous A ⁽³⁾ | | |
| | | | | 10 500 | 24.4 |
| | | Subbituminous ⁽⁴⁾ | Subbituminous B | 9 500 | 22.1 |
| | | | Subbituminous C | 8 300 | 19.3 |
| | | | Lignite A | | |
| | | | | 6 300 | 14.7 |
| | | Lignite ⁽⁴⁾ | Lignite B | | |

* Dry, mineral-matter-free basis; VM = Volatile matter; FC = Fixed carbon.

** Moist, mineral-matter-free basis.

(1) Nonagglomerating; if agglomerating, classified as low-volatile bituminous.

(2) Commonly agglomerating.

(3) If agglomerating, classified as high-volatile C bituminous.

(4) Nonagglomerating.

Table 2 - Mines sampled and approximate raw coal production for 1978-1981
 (In thousands of tonnes)

| | <u>1978</u> | <u>1979</u> | <u>1980</u> | <u>1981</u> |
|---|-------------|-------------|-------------|-------------|
| <u>NOVA SCOTIA</u> | | | | |
| Sydney Coalfield | | | | |
| Cape Breton Development Corporation (CBDC): | | | | |
| - Lingan Mine (u/g) | 1777 | 1492 | 1690 | 1510 |
| - No. 26 Colliery (u/g) | 800 | 731 | 999 | 718 |
| - Prince Mine (u/g) | 170 | 162 | 219 | 471 |
| Novaco (Point Aconi) (strip) | | | 55 | 184 |
| Thomas Brogan Limited (strip) | 47 | 41 | 69 | 57 |
| Inverness Coalfield | | | | |
| Evans Coal Mines Limited (u/g) | 33 | 31 | 41 | 36 |
| Pictou Coalfield | | | | |
| Thorburn Mining Limited (reclamation) | 40 | 42 | 44 | 27 |
| Joggins Coalfield | | | | |
| River Hébert Coal Company Limited (u/g) | 22 | 22 | | |
| <u>NEW BRUNSWICK</u> | | | | |
| Minto Coalfield | | | | |
| N.B. Coal Limited (strip) | 315 | 310 | 439 | 518 |
| <u>SASKATCHEWAN</u> | | | | |
| Estevan Area | | | | |
| Manalta Coal Limited | | | | |
| - Klimax Mine (strip) | 674 | 559 | 714 | 738 |
| Utility Coals (1978) Ltd. | 1893 | 2102 | 2440 | 2397 |
| Manitoba & Saskatchewan Coal Company Ltd. | | | | |
| - Boundary Dam Mines (strip) | 1700 | 1678 | 1689 | 1422 |
| - Bienfait (strip) | 448 | 342 | 537 | 1141 |
| Saskatchewan Power Corporation | | | | |
| - Souris Valley Coal Mine (strip) | 344 | 331 | 304 | 302 |
| - Poplar River Mine, Coronach (strip) | | | 285 | 798 |

Table 2 cont'd

| | <u>1978</u> | <u>1979</u> | <u>1980</u> | <u>1981</u> |
|---|-------------|-------------|-------------|-------------|
| <u>ALBERTA</u> | | | | |
| Plains Region | | | | |
| Forestburg Collieries Ltd. | | | | |
| - Diplomat Mine, No. 1578 (strip) | 922 | 685 | 815 | 1038 |
| Manalta Coal Ltd. | | | | |
| - Vesta Mine, No. 1046 (strip) | 513 | 811 | 925 | 1110 |
| - Whitewood Mine, No. 1757 (strip) | 1329 | 1769 | 2195 | 1447 |
| - Highvale Mine, No. 1769 (strip) | 4969 | 6041 | 6469 | 7832 |
| - Roselyn Mine, No. 443 (strip) | 438 | 167 | 76 | 69 |
| Mountain Region | | | | |
| Cardinal River Coals Ltd. | | | | |
| - Cardinal River Mine, No. 1768 (strip) | 2472 | 1918 | 2942 | 1501 |
| Coleman Collieries Limited | | | | |
| - Tent Mountain, Mine No. 1695 (strip) | 1020 | 1162 | 865 | - |
| - Vicary Creek, Mine No. 1747 (u/g) | 348 | 91 | | |
| McIntyre Mines Limited | | | | |
| - Smoky River Mines, Grand Cache (strip-u/g) | 1266 | 1156 | 1082 | |
| | 907 | 750 | 1325 | 3205 |
| The Canmore Mines Limited | | | | |
| - Mine No. 1775 (u/g) | 122 | 56 | | |
| Luscar Sterco Ltd. | | | | |
| - Coal Valley Mine (strip) | 1242 | 3227 | 4256 | 4974 |
| <u>BRITISH COLUMBIA</u> | | | | |
| Crowsnest Coalfield | | | | |
| Byron Creek Collieries Limited (strip) | 536 | 893 | 1062 | 530 |
| Kaiser Resources Limited | | | | |
| - Harmer Ridge (strip) | 6600 | | 5966 | |
| | | 8288 | | 9051 |
| - Michel Colliery (u/g) | 796 | | 703 | |
| Elk Valley Coalfield | | | | |
| Fording Coal Limited (strip) | 4300 | 4758 | 5573 | 5825 |

Table 3 - Statistical summary of Canadian commercial coals

192

| | | Ash* | Total sulphur | Pyritic sulphur | Sulphate sulphur | Organic sulphur |
|--|----------------|-------|---------------|-----------------|------------------|-----------------|
| <u>NOVA SCOTIA</u> | | | | | | |
| Inverness Coalfield (High-volatile B bituminous) | | | | | | |
| Evans Coal Mines Limited | No. of samples | 17 | 17 | 6 | 6 | 6 |
| | \bar{x} | 11.09 | 6.73 | 3.19 | 0.16 | 3.37 |
| | S | 2.40 | 0.45 | 0.43 | 0.17 | 0.26 |
| | S_x | 0.58 | 0.11 | 0.18 | 0.07 | 0.11 |
| <u>NEW BRUNSWICK</u> | | | | | | |
| Minto Coalfield (High-volatile A bituminous) | | | | | | |
| N.B. Coal Limited | No. of samples | 28 | 28 | 28 | 28 | 28 |
| and Knox Construction Limited | \bar{x} | 19.68 | 8.54 | 6.99 | 0.28 | 1.28 |
| | S | 3.37 | 1.41 | 1.17 | 0.30 | 0.29 |
| | S_x | 0.64 | 0.27 | 0.22 | 0.06 | 0.05 |
| <u>SASKATCHEWAN</u> | | | | | | |
| Estevan Area (Lignite A) | No. of samples | 18 | 18 | 15 | 15 | 15 |
| | \bar{x} | 14.36 | 0.67 | 0.22 | 0.06 | 0.41 |
| | S | 2.94 | 0.14 | 0.16 | 0.04 | 0.10 |
| | S_x | 0.69 | 0.03 | 0.04 | 0.01 | 0.03 |
| <u>ALBERTA</u> | | | | | | |
| Plains Region (Subbituminous C) | | | | | | |
| Battle River Coalfield | No. of samples | 14 | 14 | 14 | 14 | 14 |
| | \bar{x} | 8.91 | 0.55 | 0.04 | 0.01 | 0.50 |
| | S | 2.15 | 0.05 | 0.02 | 0.01 | 0.04 |
| | S_x | 0.57 | 0.01 | 0.01 | 0.005 | 0.01 |
| Plains Region (Subbituminous C) | No. of samples | 27 | 27 | 27 | 27 | 27 |
| Sheerness, Battle River and Wabamun Coalfields | \bar{x} | 11.75 | 0.53 | 0.09 | 0.01 | 0.44 |
| | S | 3.68 | 0.18 | 0.12 | 0.02 | 0.13 |
| | S_x | 0.71 | 0.03 | 0.02 | 0.005 | 0.025 |

 \bar{x} - mean value

S - standard deviation of the sample (unbiased)

 S_x - standard error of the sample

* - Ash, total sulphur and sulphur forms are presented on a dry basis

OPINION POLL

The opinion of concerned readers may influence the direction of future CANMET research.

We invite your assessment of this report - No. _____

Is it useful? Yes _____ No _____

Is it pertinent to an industry problem? Yes _____ No _____

Is the subject of high priority? Yes _____ No _____

Comments _____

Please mail to: CANMET Editor, EMR, 555 Booth Street,
Ottawa, Ontario, K1A 0G1

A complimentary copy of the CANMET REVIEW describing CANMET research activity will be sent on request.

CANMET REPORTS

Recent CANMET reports presently available or soon to be released through Printing and Publishing, Supply and Services, Canada (addresses on inside front cover), or from CANMET Publications Office, 555 Booth Street, Ottawa, Ontario, K1A 0G1:

Les récents rapports de CANMET, qui sont présentement disponibles ou qui le seront bientôt peuvent être obtenus de la direction de l'Imprimerie et de l'édition, Approvisionnements et Services Canada (adresses au verso de la page couverture), ou du Bureau de vente et distribution de CANMET, 555, rue Booth, Ottawa, Ontario, K1A 0G1:

- 81-13E MA-2: A certified gold reference ore; H.F. Steger and W.S. Bowman;
Cat. No. M38-13/81-13E, ISBN 0-660-11149-7; Price: \$2.50 Canada, \$3.00 other countries.
- 82-1E Silica fume in concrete - preliminary investigation; G.G. Carette and V.M. Malhotra;
Cat. No. M38-13/82-1E, ISBN 0-660-11181-0; Price: \$6.50 Canada, \$7.80 other countries.
- 82-2E Impact of excessive aromatics in oil sand syndrudes on production and quality of middle distillate fuels; M.F. Wilson;
Cat. No. M38-13/82-2E, ISBN 0-660-11157-8; Price: \$2.75 Canada, \$3.30 other countries.
- 82-4E The chemistry, generation and treatment of thiosalts in milling effluents - A non-critical summary of CANMET investigations 1976-1982; edited and compiled by M. Wasserlauf and J.E. Dutrizac;
Cat. No. M38-13/82-4E, ISBN 0-660-11276-0; Price: \$9.00 Canada, \$10.80 other countries.
- 82-6E BL-2a and BL-4a: Certified uranium reference ores; H.F. Steger, W.S. Bowman and G. Zechanowitsch and R. Sutarno;
Cat. No. M38-13/82-6E, ISBN 0-660-11179-9; Price: \$4.95 Canada, \$5.95 other countries.
- 82-7E Small-scale continuous selective flotation of a New Brunswick massive sulphide ore; A.I. Stemerowicz, T.F. Berry, R.H. Bredin and G.W. Leigh;
Cat. No. M38-13/82-7E, ISBN 0-660-11247-7; Price: \$5.50 Canada, \$6.60 other countries.
- 82-8E Canadian R&D studies of partially briquetted coke oven charges; J.T. Price, J.F. Gransden and W.R. Leeder;
Cat. No. M38-13/82-8E, ISBN 0-660-11217-5; Price: \$4.50 Canada, \$5.40 other countries.
- 82-9E CANMET Review 1981-82; Staff of Technology Information Division;
Cat. No. M38-13/82-9E, ISBN 0-660-11310-4; Price: \$5.00 Canada, \$6.00 other countries.
- 82-9F Revue de CANMET 1981-82; Staff of Technology Information Division;
Cat. No. M38-13/82-9F; ISBN 0-660-91054-3; Price: \$5.00 Canada, \$6.00 other countries.
- 82-11E Summaries of CANMET energy research contracts; compiled by T.P. Lanzer;
Cat. No. M38-13/82-11E; ISBN 0-660-11327-9; Price: \$6.75 Canada, \$8.10 other countries.
- 82-14E MP-la: A certified reference ore; H.F. Steger and W.S. Bowman;
Cat. No. M38-13/82-14E; ISBN 0-660-11234-5; Price: \$2.50 Canada, \$3.00 other countries.
- 83-3E Certified reference materials; compiled by H.F. Steger;
Cat. No. M38-13/83-3E; ISBN 0-660-11338-4; Price: \$5.25 Canada, \$6.30 other countries.
- 83-3F Matériaux de référence; compilé par H.F. Steger;
Cat. No. M38-13/83-3F; ISBN 0-660-91047-0; Price: \$5.25 Canada, \$6.30 other countries.

