



Infrastructure  
Canada

Canada

# THE GHG GUIDANCE MODULES



New Buildings v1.0

Infrastructure Canada

Aussi disponible en français sous le titre : Les lignes directrices sur les GES modules : Nouveaux bâtiments v1.0

Information contained in this publication or product may be reproduced, in part or in whole, and by any means, for personal or public non-commercial purposes without charge or further permission, unless otherwise specified. Commercial reproduction and distribution are prohibited except with written permission from Infrastructure Canada.

For more information, contact:

Infrastructure Canada  
180 Kent Street, Suite 1100  
Ottawa, Ontario K1P 0B6  
[info@infcc.gc.ca](mailto:info@infcc.gc.ca)

© His Majesty the King in Right of Canada, as represented by the Minister of Housing, Infrastructure and Communities, 2023.

Cat. No. T94-53/1-2024E-PDF  
ISBN 978-0-660-68122-1

# Disclaimer

This document is intended to be a learning tool for project developers and to introduce greenhouse gas (GHG) quantification and the consideration of GHG mitigation measures into project designs in the context of the Canadian environment. The GHG quantification approach presented in this document is to ensure consistency and comparability of GHG estimates between projects. The quantification processes here are not intended to be applied to crediting mechanisms or emission trading systems. However, specific aspects of this approach (i.e. baselines and mitigation measures) can be modified to demonstrate specific GHG performance in order to realize a program's particular GHG emission objectives or targets.

The scope of the GHG sources presented here is not purported to be a comprehensive life-cycle analysis of the project. Such an exercise can only be done credibly ex-post and with a large amount of information. For instance, GHG emissions resulting from embodied carbon or the decommissioning of the project are not considered. This guidance describes an approach to estimate GHG emissions ex-ante, when minimal information and resources are available. In addition, the methodologies proposed in this document are intended to capture the most significant of emission sources only.

Finally, this document is evergreen – meaning it will be periodically updated to remain aligned with advancing assessment methodologies. Please ensure you consult the Infrastructure Canada website to ensure you have the most recent version of this guidance before undertaking a GHG Assessment.

# Table of Contents

Introduction .....	5
Principles .....	6
GHG basics.....	7
GHG assessment table of contents .....	8
GHG sources & measures .....	9
Step-by-step instructions .....	10
Part 1: project scenario .....	10
Part 2: project operation .....	11
Part 3: baseline scenario .....	15
Part 4: baseline operation .....	16
Part 5: total net GHGs .....	18
ANNEX A - New building GHG activities and related information .....	20
ANNEX B - Average PT grid electricity emission intensities (tonnes/MWh)* .....	22
ANNEX C - References .....	24

# Introduction

---

This GHG Guidance Module provides information to help quantify greenhouse (GHG) emission reductions from **the operation of a new building or facility**. Emission reductions are based on the difference between a building or facility constructed according to relevant Canadian building codes (the baseline) and a building constructed with various energy efficient and GHG mitigation measures that are above and beyond the relevant building codes (the project).

The GHG Guidance Modules provide a simplified, sector-specific approach to GHG quantification for various projects across Canada. They are intended to be used by qualified professionals with expertise related to the project and preferably some level of GHG accounting experience. Each GHG Guidance Module is based on international standards and sets out a pre-determined set of technical elements (i.e. baselines, activities and variables) and other considerations, required to quantify GHG benefits from a specific project type or sector.

The GHG Guidance Modules are built upon the following 3 principles:

1. Integrity – The Modules provide an approach to ensure GHG assessments are developed according to specific standards to ensure they have a consistency, comparability and transparency that allows intended users to make decisions with reasonable confidence.
2. Rationality – The Modules provide guidance that is intended to be straightforward and logical to administer, while ensuring a rigorous commitment to the environmental reliability of the system.
3. Legacy – The Modules build on experience and tools gained from existing project-based programs in jurisdictions across Canada, international standards and existing Canadian projects.

## Definitions:

**New Building/Facility:** The construction of new infrastructure, such as a sports or recreation complex, arena, community centre or library, office building, long-term care facility, etc., that previously did not exist or is replacing end-of life infrastructure and contains energy consuming and GHG releasing components (ex. equipment, systems, processes, technologies).

**GHG Mitigation Measures:** Actions or components of a building or facility that decrease energy consumption, use cleaner forms of energy, or reduce GHG process or fugitive emissions. Ex. Installation of heat pumps, solar panels, green rooftops, LED lighting, avoiding use of HCFCs, etc.

# Principles

---

When developing any type of GHG assessment or inventory, developers should follow relevant GHG standards, guidance documents and methodologies suggested by the specific program authority. However, as the process of GHG quantification has inherent flexibility and room for interpretation, developers of GHG assessments will still be faced with making specific decisions that are outside the scope of any guidance document. On these occasions, developers should make decisions based on the overarching objectives of integrity and credibility. To achieve these objectives, developers should follow a set of common [GHG quantification principles](#), found throughout the many GHG standards, protocols and guidance documents worldwide.

The following principles have been adapted from the [ISO 14064:2](#) Standard and should be followed when developing a GHG assessment of a project:

## Relevance

Selected sources (activities) of GHG emissions, data and methodologies must be appropriate to the project and the needs of the intended user.

## Completeness

Include all relevant GHG emission sources. Include all relevant information to support program criteria and the GHG emission estimates.

## Consistency

Developers should apply estimation methods and assumptions consistently across all aspects of the project and for all individual GHG emission sources. In other words, developers should maintain the same “quantification rules” throughout the GHG assessment.

## Transparency

All assumptions, methods, calculations, and associated uncertainties should be provided in order to allow intended users to make decisions with reasonable confidence and allow for successful validation and verification of the results.

## Accuracy

Estimates and calculations should be unbiased, and uncertainties should be reduced as far as practical. Calculations should be conducted in a manner that minimizes uncertainty.

## Conservativeness

Where there are uncertainties, the values used to quantify GHG emissions should err on the side of underestimating potential reductions.

# GHG basics

---

**Baseline scenario:** The baseline scenario is the “business as usual” or hypothetical reference case against which the GHG performance of the project is measured. A variety of baseline approaches are available to quantify GHG emissions from a project, although not all approaches are applicable to any given project type. The baseline is an important aspect to a GHG quantification reduction, and pending the choice of a baseline, can result in varying estimates of GHG emissions reductions.

**Project scenario:** The project scenario consists of the project activities, which include the GHG mitigation measures that go beyond standard codes and practice and are aimed to reduce energy and GHG emissions. The performance of the project and its mitigation measures are compared to an alternative hypothetical reference case with average energy intensity and GHG performance (i.e. the baseline scenario).

**Sources & sinks:** Under ISO 14064:2, a source is any process or activity that releases a greenhouse gas into the atmosphere, whereas a sink is any process, activity or mechanism that removes a greenhouse gas from the atmosphere. Although there are numerous sources and/or sinks related to a project or baseline scenario, only a few relevant (i.e. significant) activities are typically selected for quantification, as they are likely to result in significant amounts of GHG emissions.

**Elements:** GHG sources and sinks can be further broken down into the specific elements which are responsible for completing the activity and result in GHG emissions. For example, for the activity of heating a building, the associated element will be the stationary combustion unit such as a boiler or furnace. The specifications of an element, including how it operates, are important factors to identify and state in a GHG assessment, as they will impact the overall quantification.

**End variable:** An end variable is the annual input/output or activity level of an element (i.e. the amount of fuel combusted in one year ) and estimated for each year of the project lifetime. End variables are generally calculated using specific data from an element or activity and gathered from various sources. Examples of end variables include: litres (L) of fuel, kilowatt hours (kWh) of electricity or tonnes (T) of hydrofluorocarbons (HFCs).

**Emission factor:** An emission factor is a representative value that relates the quantity of GHGs released with a specific level or output of an activity. Emission factors are based on the unique characteristics of elements or processes, and can also be specific to the location where an activity is placed. A common equation used to estimate GHG emissions from a project or baseline activity involves an end variable and a relevant emission factor, which is typically found in Canada’s National Inventory Report. The equation is structured in the following way:  $\text{GHG Emissions} = \text{End Variable (EV)} \times \text{Emission Factor (EF)}$ .

**Ex ante estimation:** The estimation of GHG emissions prior to the development and operation of a project and actual generation of GHG emissions. As no actual data has yet been generated by the project at this stage, project proponents must look to comparable sources of data such as the following: similar projects completed by the proponent in the past; similar projects completed by others in the surrounding area; contracts, work plans or estimates for the project provided by third party contractors involved; any modeling work performed by project developers, energy consultants, etc.; and estimates developed to the best of the proponent’s ability.

# GHG assessment table of contents

A general GHG assessment provides an estimation of the total GHG emissions and/or reductions resulting from a project and includes important information related to the quantification process such as the scope of the assessment, relevant sources and sinks, calculations and assumptions. Information should be provided in a clear and organized format, to ensure the principles of GHG quantification have been carefully followed and GHG estimates can be easily validated. An assessment is composed of the following main sections as shown in Table 1.0:

Table 1.0 Sample Table of Contents for GHG Assessment of a Project

<b>Project Scenario</b>	<b>Project Description</b>	The project description provides a brief overview of the project activities including the product or service provided by the project and any specific technologies that will be employed.
	<b>Project Location</b>	Provides information on the exact location of the project
	<b>Project Timeline</b>	Provides the project operation start and end date, as well as any potential significant maintenance and refurbishment events
	<b>Project Operation &amp; GHG Emissions</b>	The GHGs from all project activities are identified and quantified in this section.
<b>Baseline Scenario</b>	<b>Baseline Description</b>	The baseline description provides an overview of the alternative scenario that would have happened in the absence of the project and describes how the baseline is functionally equivalent to the project.
	<b>Baseline Operation &amp; GHG Emissions</b>	The GHGs from all baseline activities are identified and quantified in this section.
<b>Total GHG Reductions</b>	<b>Total GHG Reductions</b>	The GHG emissions reductions resulting from the whole project are presented in this section, including annual reductions and cumulative GHG reductions for the lifetime of the project.
<b>ANNEXES</b>	<b>Supporting Information</b>	References, list of documents used in quantification Tables of equipment Equipment specifications



# GHG sources & measures

---

GHG emissions from the buildings sector are the result of a few different activities, namely the use of grid electricity to power building equipment, lighting and provide cooling, the combustion of fossil fuels for heating, and leaks from refrigerants from air conditioners, chillers, and other equipment. Other indirect sources of GHG emissions include the generation and management of waste and wastewater and the embodied carbon of building materials.

There are a variety of GHG mitigation measures that can be implemented to reduce the carbon footprint of a building. Some of the most common measures focus on energy efficiency such as energy efficient equipment and lighting, building automation systems, improved insulation, windows and doors and generation of on-site clean renewable energy. The GHG impact of some measures is directly quantifiable, while others have a more indirect impact on the overall system but are nonetheless important to achieving a low-carbon facility.



**Site Selection:** Selecting brownfield sites, minimizing disturbance of existing vegetation, wetlands, peat and permafrost, assessing optimal building orientation, proximity to public transit and other amenities.



**Design Features & Materials:** Optimizing natural daylight, installing window shading, building up instead of out, using locally sourced materials, recycled or re-usable materials, selecting equipment with less potent refrigerants or alternatives and using an integrated design process.



**Energy Efficiency & Demand:** Installing energy efficient LED lighting, HVAC, heat recovery, building envelope upgrades, heat pumps and other equipment, as well as installing automatic controls for equipment and lighting.



**Transportation Accessibility:** Easy access to public transportation, availability of EV charging stations, active transit pathways (cycling/walking), bicycle storage, bus shelters, etc.



**Natural Infrastructure:** Use of natural vegetation for stormwater drainage, green roofs for insulation and reduced energy use.



**Generation of Renewable Energy:** Generation of cleaner energy on site such as solar, wind or ground source heat.



# Step-by-step instructions

This section provides step-by-step instructions for completing a GHG assessment for a new building or facility. [Annex A](#) provides a list of GHG sources and relevant information to be used along with these step-by-step instructions. For additional supporting information, please refer to the references in [Annex C](#).

## Part 1: project scenario

### 1.1 Project Description

The project description lays out the foundation for the types of activities that may release or reduce GHGs from the project and that will need to be quantified in the assessment.

#### Key Actions

- *Document a brief description of the new building or facility and its main services.*
- *Record the size of the building (floor space area), its maximum operating capacity (and any expected fluctuations in capacity) and expected hours of operation.*
- *Identify any maintenance/repairs that will be needed throughout the operational lifetime of the project.*

### 1.2 Project Geographical Location

The identification of the project site is important as many data values will need to be sourced and obtained from the local area, including emission factors. Validators will need to be able to assess if the proper values representing the area were used in the quantification of the GHG emissions and ensure all GHG sources or sinks have been properly accounted for in the assessment.

#### Key Actions

- *Record the address and/or GPS coordinates of the project.*
- *Document the project location on a map, delineating the project site and boundary of the project, ensuring all relevant components of the project are included.*
- *If applicable, identify whether the project site is currently vegetated, a wetland or a peat bog, on permafrost or is considered a brownfield.*
- *Identify if the project site is accessible by public transit or active transportation (cycling/walking).*

### 1.3 Project Timeline

It is important to know when the project will be constructed and in full operation, including if and when GHG emission reductions will start taking place and for how long. Other important dates are the maintenance and repair schedules which will result in downtimes and interruptions in service, which will also impact any emission reductions.

#### Key Actions

- *Record a detailed project timeline outlining the timing of operational activities. Specifically, the following estimated dates are required:*
  - *Construction start and end dates*
  - *Building commissioning start date*
  - *Operational start and end dates*

- *Dates of any major maintenance/repairs/refurbishments expected.*
- *Expected lifetime of project (30 year default)*
- *Identify any risks that could substantially affect the project’s operational timelines.*

## Part 2: project operation

### 2.1 Identification of Project GHG Activities & Elements

In this section, all the relevant activities for the operation of the project are identified, including all elements.

Project GHG emissions are the estimated amount of GHGs emitted from the building’s consumption of various energy sources and releases of refrigerants once the new building with GHG mitigation measures is constructed and in operation. The most common sources of GHGs in buildings includes electricity use, heating & cooling of the building and fugitive emissions from heat pumps, refrigeration and cooling equipment.

An example of GHG mitigation measures for new buildings can include the use of energy efficient equipment, installation of LED lighting, on-site generation of renewable energy (ex. rooftop solar), building automation systems, green rooftops, enhanced thermal building envelope and building/site design features such as orientation and exterior shading.

#### The project must also follow these requirements:

- Any significant changes in occupancy or use of the building expected to occur in any given year must be accounted for in the building’s energy and GHG profile.
- It is important to note any interactive effects the various activities can have on one another, such as the increased need for heating with the installation of LED lighting (LED lighting releases less heat than incandescent lighting, resulting in higher heating requirements in winter, and lower cooling requirements in summer). Interactive effects should be accounted for in the energy modelling of the building.
- Note that equipment degradation is not currently accounted for under this GHG Guidance Module.

#### Key Actions

- *Using Table 2.0 [Annex A](#) as a guide, select all activities related to the project and document a brief description of each activity.*
- *List and describe all GHG mitigation measures that will be implemented in the new building. How will these measures impact overall energy use or other GHG emissions of the building?*
- *If applicable, identify any interactive effects of the various activities.*
- *If applicable, include the modelling tools used to simulate the energy performance of the building.*
- *Ensure all information is presented in a table or other legible format.*

### 2.2 Quantification of Project Activity 1: Electricity (Grid)

Electricity use during operations of the building are associated with heating, cooling and ventilation, domestic hot water, lights, plug loads and other equipment using electricity.

#### Key Actions

- Identify the amount of electricity (MWh) expected to be used in the building on a yearly basis.
- Estimated electricity use should be available from energy modelling results, or obtained from similar projects in operation. Standard energy use for a similar type of building can be used if no energy modelling information is available.
- Any expected changes in capacity or the use of the building must be reflected in the expected energy demand of the building.
- Obtain the provincial/territorial (P/T) electrical grid emission intensity for your location. Emission intensities should be dynamic and reflect cleaning of P/T grids in future years. P/T Emission intensities can be found in Annex B. For remote communities not connected to a P/T grid, use the emission factor (found in [Canada's National Inventory Report \(2021\)](#)) for the type of energy used to generate electricity in that location (ex. Diesel generators).
- To quantify GHG emissions, apply the following calculation:

$$\text{Energy (MWh/year)} \times \text{P/T Emission Intensity (tonnes CO}_2\text{e/MWh)} = \text{Emissions tonnes CO}_2\text{e /year}$$

Note: If replacing diesel or other fuel, substitute the P/T emission intensity for the respective fuel emission factor.

- The yearly energy use, emission intensities and the associated GHG emissions should be presented in a table or other legible format.
- Document all assumptions and references used to calculate the electricity consumption of the building and the associated GHG emissions.
- Note: Any energy consumption being met by generated on-site renewable energy should be reflected in section 2.5.

### 2.3 Quantification of Project Activity 2: Heating & Cooling (non-electrical)

Especially in Canada with its cold winters, heating of a building results in a large amount of GHG emissions. Heating and cooling of building and facilities can be through the combustion of natural gas, fuel oil, propane, diesel and wood.

#### Key Actions

- Identify the amount of fuel (m<sup>3</sup>/L/kg) of each type expected to be used in the building for heating and cooling on a yearly basis.
- Estimated consumption of fuel(s) for heating and cooling should be available from energy modelling results, or obtained from similar projects in operation. Standard fuel use for a similar type of building can be used if no energy modelling information is available.
- Any expected changes in capacity or the use of the building must be reflected in the expected heating & cooling demand of the building.
- Obtain the relevant emission factors for your fuel type and combustion equipment. Emission factors can be obtained from [Canada's National Inventory Report \(2021\)](#). Note that emission factors are presented for each of the three main gases: CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O. To obtain an emission factor in units of CO<sub>2</sub>e,

multiply each emission factor for CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O by their respective 100 year global warming potentials (1, 25 and 298 respectively) and add all three values together.

- To quantify GHG emissions, apply the following calculation:

**Fuel (m<sup>3</sup>) x Specific fuel combustion emission factor (tonnes/m<sup>3</sup>) = Emissions tonnes CO<sub>2</sub>e/year**  
(Fuel may be in either L or m<sup>3</sup>- ensure the units are consistent with the appropriate emission factor)

- The yearly fuel use, emission factors and the associated GHG emissions should be presented in a table or other legible format.
- List all assumptions and references used to calculate the fuel consumption of the building and the associated GHG emissions and include any relevant equipment specifications.

## 2.4 Quantification of Project Activity 3: Fugitive Emissions

The 2019 Refinement to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories identify air conditioning, refrigeration, and fire suppression equipment and materials as potential sources of fugitive emissions during their life cycle. The fugitive emissions that should be included here are associated with the refrigerants used in heat pumps, air conditioning equipment and refrigeration equipment, including chillers to make ice in recreational complexes.

### Key Actions

- Identify all the various types of equipment that include refrigerants in the building.
- Identify the type and amount of refrigerant (kgs/tonnes) in each piece of equipment and the expected level of operation of the equipment. Estimated cooling capacity and refrigerant capacity(kg) should be available from manufacturer specifications and/or project plans.
- Identify the appropriate annual leakage rates for the various types of equipment (note that leakage rates can vary on the phase of the equipment's life). Leakage rates can be found here: [Table 2: GHG Protocol HFC Tool \(Version 1.0\)](#).
- To quantify GHG emissions, apply the following calculation:

**Refrigerant capacity (kg) x Annual leakage rate (% of capacity) x GWP of refrigerant /1000 = Emissions tonnes CO<sub>2</sub>e/year**

- The type of refrigerant, annual refrigerant leakage rate during operation, and the equipment lifespan should be recorded for each piece of equipment.
- The [EPA GreenChill Calculator](#) can be used to estimate the GHGs associated with refrigerant leaks from refrigeration sources.
- The annual GHG emissions resulting from refrigerant leakage should be presented in a table or other legible format.
- List all assumptions and references used to calculate the refrigerant use/leakage and the associated GHG emissions.

## 2.5 Quantification of Project Activity 4: Renewable Energy Generation on-site (if applicable)

If the building will be generating renewable energy on-site to avoid or minimize using more GHG -intensive grid electricity (or diesel fuel in remote regions), emission reductions resulting from the use of renewable energy can be accounted for in the GHG assessment.

### Key Actions

- Document the type of renewable energy that will be generated on-site including the capacity of the system and when the energy system will be operational.
- Record the expected annual electricity that will be generated by the energy system. For wind and solar systems, ensure local wind and solar capacities are referenced.
- Confirm whether all or a specific % of the on-site renewable energy generation will be used by the building. Any expected changes in the generation or use of the renewable energy must be reflected in the annual energy generation estimates. Drop in annual output due to equipment degradation may be included if values are available.
- Obtain the provincial/territorial (P/T) electrical grid emission intensity for your location. Emission intensities should be dynamic and reflect cleaning of P/T grids in future years. P/T Emission intensities can be found in Annex B. For remote communities not connected to a P/T grid, use the emission factor (found in [Canada's National Inventory Report \(2021\)](#)) for the type of energy used to generate electricity in that location (ex. Diesel generators).
- To quantify GHG emissions, apply the following calculation:

$$\text{Energy generated by system on-site (MWh/year)} \times \text{P/T Emission Intensity (tonnes CO}_2\text{e /MWh)} = \text{Avoided Emissions tonnes CO}_2\text{e /year}$$

Note: If replacing diesel or other fuel, substitute the P/T emission intensity for the respective fuel emission factor.

- Further guidance on how to calculate GHGs from energy generation can be found in **INFC's Renewable Energy GHG Guidance Module**.
- The yearly energy generation, emission intensities and the associated GHG emissions should be presented in a table or other legible format.
- List all assumptions and references used to calculate the electricity generation and associated GHG emissions.

## 2.6 Total Project Operational GHG Emissions

### Key Actions

- For each project activity, input the associated GHG emissions into a Table such as the one below.
- Calculate the total tonnes CO<sub>2</sub>e per year using the following equation:  
**Activity 1 + Activity 2 + Activity 3 – Activity 4 = Total Project Emissions (tonnes CO<sub>2</sub>e/year)**
- Sum all the years to obtain the cumulative tonnes CO<sub>2</sub>e over the project lifetime.

**Table 2.0 Total Project Operational Emissions  
(in tonnes of CO<sub>2</sub>e)**

Year	Activity 1 Electricity	Activity2 Heating/Cooling (Fuel-based)	Activity 3 Fugitive Emissions (Refrigerants)	Activity 4 Renewable Energy Generation	Total Project Emissions
2023					
2024					

<b>2025....</b>					
<b>2030</b>					
<b>2031....</b>					
<b>2050</b>					
<b>TOTAL</b>					

## Part 3: baseline scenario

### 3.1 Baseline Description

The Baseline Scenario is the “business as usual” or hypothetical reference case against which the GHG performance of the project is measured. Under this GHG Guidance Module, the most appropriate baseline scenario for new buildings would be the following:

A similar building or facility constructed according to the standard requirements under the National Building Code (2015) and/or which follows the minimum requirements for energy efficiency as set out in the National Energy Code for Buildings (2017) or the relevant jurisdictional requirements.

The baseline must also follow these requirements:

- Any significant changes in occupancy or use of the building expected to occur in any given year must be accounted for in the building’s energy and GHG profile.
- Capacity/occupancy of the building and any services provided (including any fluctuations over the lifetime of the project) must mirror those found in the project scenario. The level of output or services provided must be the same in the project as in the baseline, to ensure that the project is not reducing GHG emissions solely by producing less product or services.
- Provincial building codes and facility-specific standards may be used for the baseline scenario if more relevant. Justification must be documented.

#### Key Actions

- *Document a description of the baseline scenario, including how it is functionally equivalent to the project scenario, and the relevant codes and standards referenced.*
- *Record the size of the baseline building (floor space area), its maximum operating capacity (and any expected fluctuations in capacity) and expected hours of operation.*
- *If applicable, include the modelling tools used to simulate the energy performance of the baseline building.*
- *Include all assumptions under the baseline scenario as applicable.*

## Part 4: baseline operation

### 4.1 Identification of Baseline GHG Activities & Elements

In this section, all the relevant activities for the operation of the baseline are identified, including all elements.

The most common sources of GHGs related to new buildings includes electricity use, heating & cooling of the building and the use of refrigerants in equipment and building components.

#### Key Actions

- Using Table 2.0 [Annex A](#) as a guide, select all activities related to the baseline and document a brief description of each activity.
- Ensure all information is presented in a table or other legible format.

### 4.2 Quantification of Baseline Activity 1: Electricity (Grid)

Electricity use during operations of the building are associated with heating and cooling, domestic hot water, lights, plug loads and other equipment using electricity.

#### Key Actions

- Identify the amount of electricity (MWh) expected to be used in the baseline on a yearly basis.
- Estimated electricity use should be available from energy modelling results, or obtained from similar projects in operation. Standard energy use for a similar type of building can be used if no energy modelling information is available.
- Any expected changes in capacity or the use of the building as identified in the project scenario, must be reflected in the expected energy demand within the baseline scenario.
- Obtain the provincial/territorial (P/T) electrical grid emission intensity for your location. Emission intensities should be dynamic and reflect cleaning of P/T grids in future years. P/T Emission Intensities can be found in [Annex B](#). For remote communities not connected to a P/T grid, use the emission factor (found in [Canada's National Inventory Report \(2021\)](#)) for the type of energy used to generate electricity in that location (ex. Diesel generators).
- To quantify GHG emissions, apply the following calculation:

$$\text{Energy (MWh/year)} \times \text{P/T Emission Intensity (tonnes CO}_2\text{e/MWh)} = \text{Emissions tonnes CO}_2\text{e /year}$$

- The yearly energy use, emission intensities and the associated GHG emissions should be presented in a table or other legible format.
- Document all assumptions and references used to calculate the electricity consumption of the building and the associated GHG emissions.

### 4.3 Quantification of Baseline Activity 2: Heating & Cooling (non-electrical)

Especially in Canada with its cold winters, heating of a building results in a large amount of GHG emissions. Heating and cooling of building and facilities can be through the combustion of natural gas, fuel oil, propane, diesel and wood.

#### Key Actions



- Identify the amount of fuel (m<sup>3</sup>/L/kg) of each type expected to be used in the building for heating and cooling on a yearly basis.
- Estimated overall consumption of heating and cooling should be available from energy modelling results, or obtained from similar projects in operation. Standard fuel use for a similar type of building can be used if no energy modelling information is available.
- Any expected changes in capacity or the use of the building in the project scenario must be reflected in the expected heating and cooling demand within the baseline scenario.
- Obtain the relevant emission factors for your fuel type and combustion equipment. Emission factors can be obtained from [Canada's National Inventory Report \(2021\)](#). Note that emission factors are presented for each of the three main gases: CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O. To obtain an emission factor in units of CO<sub>2</sub>e, multiply each emission factor for CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O by their respective 100 year global warming potentials (1, 25 and 298 respectively) and add all three values together.
- To quantify GHG emissions, apply the following calculation:

**Fuel (m<sup>3</sup>) x Specific fuel combustion emission factor (tonnes/m<sup>3</sup>) = Emissions tonnes CO<sub>2</sub>e/year**  
 (Fuel may be in either L or m<sup>3</sup>- ensure the units are consistent with the appropriate emission factor)

- The yearly fuel use, emission factors and the associated GHG emissions should be presented in a table or other legible format.
- List all assumptions and references used to calculate the fuel consumption of the building and the associated GHG emissions and include any relevant equipment specifications.

#### 4.4 Quantification of Baseline Activity 3: Fugitive Emissions

The 2019 Refinement to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories identify air conditioning, refrigeration, and fire suppression equipment and materials as potential sources of fugitive emissions during their life cycle. The fugitive emissions that should be included here are associated with the refrigerants used in heat pumps, air conditioning equipment and refrigeration equipment, including chillers to make ice in recreational complexes.

##### Key Actions

- Identify all the various types of equipment that include refrigerants in the building.
- Identify the type and amount of refrigerant (kgs/tonnes) in each piece of equipment and the expected level of operation of the equipment. Estimated cooling capacity and refrigerant capacity(kg) should be available from manufacturer specifications and/or project plans.
- Identify the appropriate annual leakage rates for the various types of equipment (note that leakage rates can vary on the phase of the equipment's life). Leakage rates can be found here : [Table 2: GHG Protocol HFC Tool \(Version 1.0\)](#).
- To quantify GHG emissions, apply the following calculation:

**Refrigerant capacity (kg) x Annual leakage rate (% of capacity) x GWP of refrigerant /1000 = Emissions tonnes CO<sub>2</sub>e/year**

- The type of refrigerant, annual refrigerant leakage rate during operation, and the equipment lifespan should be recorded for each piece of equipment.
- The [EPA GreenChill Calculator](#) can be used to estimate the GHGs associated with refrigerant leaks from refrigeration sources.

- The annual GHG emissions resulting from refrigerant leakage should be presented in a table or other legible format.
- List all assumptions and references used to calculate the refrigerant use/leakage and the associated GHG emissions.

#### 4.5 Total Baseline Operational GHG Emissions

##### Key Actions

- For each project activity, input the associated GHG emissions into a Table such as the one below.
- Calculate the total tonnes CO<sub>2</sub>e per year using the following equation:  
**Activity 1 + Activity 2 + Activity 3 = Total Baseline Emissions (tonnes CO<sub>2</sub>e/year)**
- Sum all the years to obtain the cumulative tonnes CO<sub>2</sub>e over the project lifetime.

**Table 4.0 Total Baseline Operational Emissions  
(in tonnes of CO<sub>2</sub>e)**

Year	Activity 1 Electricity	Activity2 Heating/Cooling (Fuel-based)	Activity 3 Fugitive Emissions (Refrigerants)	Total Baseline Emissions
2023				
2024				
2025....				
<b>2030</b>				
2031....				
2050				
<b>TOTAL</b>				

## Part 5: total net GHGs

### 5.1 Total Net GHG Reductions

The general equation for calculating total GHG emission reductions is:

$$\text{Baseline Emissions} - \text{Project Emissions} = \text{Total GHG Emission Reductions}$$

Emission reductions are calculated per year of the project lifetime, by subtracting the project emissions from the baseline emissions. Then all emission reductions for the given years are summed to obtain the total estimated emission reductions from the implementation of the Project.

##### Key Actions

- Input the project and baseline emission values into a table (sample provided below). Under the Climate Lens, the following values are required to be highlighted: **Total Emission Reductions in 2030** (single year) and **Total Cumulative emissions over the project lifetime**.
- Calculate the total GHG emission reductions by subtracting project emissions from the baseline emissions.

**Table 5.0 Total Net GHG Reductions  
(in tonnes of CO<sub>2</sub>e)**

<b>Year</b>	<b>Baseline Emissions</b>	<b>Project Emissions</b>	<b>Total Reductions</b>
2023			
2024			
2025...			
<b>2030</b>			
2031...			
2050			
<b>TOTAL</b>			

## ANNEX A - New building GHG activities and related information

Activity 1	Description	Elements	Data required	Sources of data	End variables
Electricity Consumption	Consumption of electricity used to operate the building and various equipment	Lighting system	Number/Type of lights Wattage of lights Annual operating hours per year	Internal records Manufacturer information Internal estimates Energy audits Average/default values	Electricity (kWh)
		Space heating and cooling equipment	Number/Type equipment Efficiency of equipment Annual operating hours per year	Internal records Manufacturer information Internal estimates Energy audits Average/default values	Electricity (kWh)
		Plug loads, various equipment (ex. water heaters and industry-specific equipment)	Number/Type equipment Efficiency of equipment Annual operating hours per year	Internal records Manufacturer information Internal estimates Energy audits Average/default values	Electricity (kWh)
Activity 2	Description	Element	Data required	Sources of data	End variables
Heating & Cooling (non-electric)	Consumption of energy for heating and cooling of the building	Furnaces, boilers, air conditioning, heat exchangers, geothermal, heat pumps and humidifiers	Number/Type equipment Efficiency of equipment Annual operating hours per year	Internal records Manufacturer information Internal estimates Energy audits Average/default values	Fuel (L, m <sup>3</sup> )
		District heating System	GJ/MWh consumed (steam, heating water and/or chilled water) System fuel mix and efficiency (default of 65%)	Purchase records Energy bills Metered energy records	Energy (GJ or equivalent)
Activity 3	Description	Element	Data required	Sources of data	End variables
Operation of refrigeration, air conditioning and	Emissions of HFCs and PFCs leak out during the operation of equipment, during specific processes	Commercial air conditioning systems, heat pumps	Type/# of units Types of refrigerants used (ex. R-22)	Internal records Manufacturer information Internal estimates Energy audits	HFCs PFCs  (Kgs/tonnes)

process equipment	(ex. Making of an ice rink) or during maintenance and repair.		Refrigerant charge capacity of each equipment Annual leakage rate or average #lbs refilled in past year	Average/default values IPCC Tables	
		Commercial refrigeration/freezers	Type/# of units Types of refrigerants used Refrigerant charge capacity of each equipment Annual leakage rate or average #lbs refilled in past year	Internal records Manufacturer information Internal estimates Energy audits IPCC Tables Average/default values	HFCs PFCs (Kgs/tonnes)
		Industrial Processes (chillers)	Type/# of units Types of refrigerants used Refrigerant charge capacity of each equipment Annual leakage rate or average #lbs refilled in past year	Internal records Manufacturer information Internal estimates Energy audits Average/default values IPCC Tables	HFCs PFCs (Kgs/tonnes)
<b>Activity 4</b>	<b>Description</b>	<b>Element</b>	<b>Data required</b>	<b>Sources of data</b>	<b>End variables</b>
Renewable Energy Generation	The building can generate its own energy using renewable energy such as wind or solar	Solar panels or wind turbines	Generation Capacity Equipment models/age Equipment efficiency Equipment technical lifetime and degradation rate	Manufacturer specifications, Direct measurement/ metering	Electricity (kWh)
<b>Notes:</b>					
<ul style="list-style-type: none"> <li>Alternative sources: internal records, utilities, local survey data, Statistics Canada, Comprehensive Energy Use Database, Office of Energy Efficiency, Natural Resources Canada, etc.</li> <li>Sources of supporting information: <i>Bill of sale, invoices, contracts of service, engineering drawings, energy audits, energy modelling, electricity permits, building permits and energy bills.</i></li> </ul>					

## ANNEX B - Average PT grid electricity emission intensities (tonnes/MWh)\*

Region	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035
Alberta	0.517	0.446	0.357	0.250	0.232	0.211	0.225	0.223	0.217	0.208	0.207	0.201	0.204	0.203	0.203	0.204
British Columbia	0.004	0.002	0.003	0.003	0.004	0.002	0.002	0.002	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001
Manitoba	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001
New Brunswick	0.276	0.259	0.269	0.268	0.275	0.273	0.274	0.272	0.258	0.252	0.124	0.116	0.124	0.113	0.123	0.114
Newfoundland	0.091	0.068	0.012	0.012	0.012	0.011	0.011	0.011	0.011	0.010	0.010	0.010	0.011	0.010	0.010	0.009
Northwest Territories	0.058	0.067	0.062	0.051	0.017	0.008	0.008	0.008	0.010	0.012	0.014	0.016	0.020	0.014	0.013	0.009
Nova Scotia	0.634	0.562	0.458	0.457	0.463	0.464	0.417	0.401	0.384	0.361	0.118	0.116	0.112	0.109	0.105	0.101
Nunavut	0.747	0.747	0.744	0.712	0.635	0.498	0.480	0.469	0.470	0.455	0.457	0.442	0.435	0.447	0.454	0.458
Ontario	0.034	0.044	0.067	0.065	0.066	0.077	0.093	0.081	0.067	0.064	0.062	0.060	0.058	0.041	0.035	0.030
Prince Edward Island	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001
Quebec	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Saskatchewan	0.410	0.366	0.299	0.306	0.252	0.249	0.253	0.221	0.173	0.167	0.163	0.157	0.146	0.142	0.137	0.133
Yukon Territory	0.045	0.121	0.068	0.077	0.086	0.089	0.099	0.074	0.046	0.029	0.018	0.014	0.018	0.023	0.032	0.041

Region	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050
Alberta	0.206	0.207	0.209	0.210	0.212	0.213	0.215	0.216	0.217	0.219	0.220	0.221	0.221	0.221	0.222
British Columbia	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001
Manitoba	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001
New Brunswick	0.124	0.111	0.118	0.114	0.129	0.129	0.120	0.121	0.122	0.124	0.125	0.126	0.128	0.130	0.131
Newfoundland	0.009	0.009	0.009	0.009	0.008	0.008	0.008	0.008	0.008	0.008	0.007	0.007	0.007	0.007	0.007
Northwest Territories	0.008	0.006	0.006	0.006	0.008	0.025	0.026	0.031	0.020	0.018	0.016	0.017	0.019	0.020	0.022
Nova Scotia	0.094	0.088	0.088	0.086	0.084	0.082	0.081	0.079	0.076	0.074	0.074	0.074	0.074	0.074	0.073
Nunavut	0.470	0.482	0.488	0.488	0.501	0.505	0.515	0.523	0.525	0.529	0.535	0.544	0.547	0.556	0.561
Ontario	0.024	0.021	0.019	0.017	0.016	0.015	0.015	0.015	0.014	0.013	0.011	0.009	0.009	0.011	0.013
Prince Edward Island	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001
Quebec	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Saskatchewan	0.130	0.126	0.123	0.121	0.117	0.115	0.112	0.108	0.105	0.098	0.095	0.092	0.089	0.085	0.082
Yukon Territory	0.054	0.067	0.052	0.039	0.027	0.019	0.013	0.017	0.020	0.026	0.033	0.042	0.050	0.034	0.022

Notes:

1. Grid Emissions intensity is defined as: (utility generation emissions) + (industrial net sales to grid by sector) x (industrial electricity generation emissions factor) *divided by* electricity consumption from the grid.
2. Prince Edward Island: Emissions intensity for PEI production. P.E. uses New Brunswick emissions intensity because PEI production P.E. consists of non-dispatchable wind energy and the rest is imported.
3. British Columbia, Manitoba and Quebec: The power grids of British Columbia, Manitoba and Quebec are zero emissions. The generation of residual emissions is not considered relevant.
4. For alternative emission intensities from B.C. electricity consult the provincial emission intensities found [here](#).
5. Alternative emission intensities from Quebec can be [here](#).

Source: ECCC's Greenhouse Gas Emissions Projections. Link: [Canada's Greenhouse Gas Emissions Projections - Environment and Climate Change Canada Data](#). Last Modified by ECCC: June 2022

**\*Emission intensities will be updated periodically. Please refer to INFC's Climate Lens website for the most recent version of the Power System P/T Average Emissions Intensities Table.**

## ANNEX C - References

---

ECCC. Environment and Climate Change Canada. 2021. *National Inventory Report. 1990-2021: Greenhouse Gas Sources and Sinks in Canada*.

European Investment Bank. December 2018. *EIB Project Carbon Footprint Methodologies, Methodologies for the Assessment of Project GHG Emissions and Emission Variations, Version 11*.

Federation of Canadian Municipalities, ICLEI, Local Governments for Sustainability. 2020. *Guidebook on Quantifying GHG Reductions at the Project Levels*.

International Standards Organization. 2019. *Greenhouse gases- Part 2: Specification with guidance at the Project level for quantification, monitoring and reporting of greenhouse gas emission reductions or removal enhancements*.

The Climate Registry, California. 2019. *General Reporting Protocol, GHG Emissions Quantification Methods, C-1, Version 3.0*.

UNFCCC – Clean Development Mechanism. October 16, 2009. *EB 50, Annex 15, Tool to determine the remaining lifetime of equipment, Version 1*.

U.S. Department of Energy, Office of Policy and International Affairs. March 2006. *Technical Guidelines, Voluntary Reporting of Greenhouse Gases*.

U. S. Environmental Protection Agency. January 2014. *GHG Inventory Guidance, Direct Fugitive Emissions from Refrigeration, Air Conditioning, Fire Suppression and Industrial Gases*.

U. S. Environmental Protection Agency, *GreenChill Store Certification Program [Overview]*. Available online at: <https://www2.epa.gov/greenchill>

U. S. Environmental Protection Agency. *Greenhouse Gas Emissions, Overview of Greenhouse Gases*. <https://www.epa.gov/ghgemissions/overview-greenhouse-gases>

WRI and WBCSD (World Resources Institute and World Business Council for Sustainable Development). 2013. *The GHG Protocol for Project Accounting*.