



Government
of Canada

Gouvernement
du Canada

Canadian General
Standards Board

Office des normes
générales du Canada

Series 1
Série des 1

WITHDRAWAL

October 2011

Selected standards in the series Paints, pigments and related products

These CGSB standards and National Standards of Canada are hereby withdrawn due to limited use and support for their revision.

The Standards Council of Canada requires that accredited Standards Development Organizations, such as the CGSB, regularly review a consensus Standard to determine whether to re-approve, revise or withdraw. The review cycle is normally five years from the publication date of the latest edition of the Standard.

The information contained in these Standards was originally developed pursuant to a voluntary standards development initiative of the CGSB. The information contained therein may no longer represent the most current, reliable, and/or available information on these subjects. CGSB hereby disclaims any and all claims, representation or warranty of scientific validity, or technical accuracy implied or expressed respecting the information therein contained. The CGSB shall not take responsibility nor be held liable for any errors, omissions, inaccuracies or any other liabilities that may arise from the provision or subsequent use of such information. These Standards are

RETRAIT

Octobre 2011

Sélection de normes de la série Peintures, pigments et produits connexes

Ces normes de l'ONGC et ces Normes nationales du Canada sont retirées par le présent avis en raison de leur utilisation limitée et du manque de support pour leur révision.

Le Conseil canadien des normes exige que les organismes accrédités d'élaboration de normes, tel que l'ONGC, effectue régulièrement un examen des normes consensuelles afin de déterminer s'il y a lieu d'en renouveler l'approbation, de les réviser ou de les retirer. Le cycle d'examen d'une norme est généralement de cinq ans à partir de la date de publication de la dernière édition de celle-ci.

L'information contenue dans ces normes a été élaborée initialement en vertu d'une initiative volontaire d'élaboration de normes de l'ONGC. Elle peut ne plus représenter l'information disponible et/ou l'information la plus actuelle ou la plus fiable à ce sujet. L'ONGC décline par la présente toute responsabilité à l'égard de toute affirmation, déclaration ou garantie de validité scientifique ou d'exactitude technique implicite ou explicite relative à l'information contenue dans ces normes. L'ONGC n'assumera aucune responsabilité et ne sera pas tenu responsable quant à toute erreur, omission, inexactitude ou autre conséquence pouvant découler de la fourniture ou de l'utilisation subséquente de

Canada

Experience and excellence

Expérience et excellence

CGSB
ONGC

to be referred to for archival purposes only as their content has been repealed as of the date on this withdrawal notice.

Archived copies of withdrawn standards for historic or archival purposes are still available from the CGSB Sales Centre by telephone at 819-956-0425 or 1-800-665-2472, by fax at 819-956-5740, by Internet at www.tpsgc-pwgsc.gc.ca/ongc-cgsb/, by e-mail at ncr.CGSB-ONGC@tpsgc-pwgsc.gc.ca or by mail at Sales Centre, Canadian General Standards Board, 11 Laurier Street, Gatineau, Canada K1A 1G6.

CAN/CGSB-1.5-M91

Low Flash Petroleum Spirits Thinner
(ICS 87.040)

CAN/CGSB-1.28-98

Exterior Alkyd House Paint (ICS 87.040)

CAN/CGSB-1.36-97

General Purpose Interior Alkyd Varnish
(ICS 87.040)

CAN/CGSB-1.38-2000

Interior Enamel Undercoater (ICS 87.040)

CAN/CGSB-1.40-97

Anticorrosive Structural Steel Alkyd Primer
(ICS 87.040)

CAN/CGSB-1.57-2003

Interior Alkyd Semigloss Enamel
(ICS 87.040)

CAN/CGSB-1.59-97

Alkyd Exterior Gloss Enamel (ICS 87.040)

CAN/CGSB-1.60-97

Interior Alkyd Gloss Enamel (ICS 87.040)

cette information. Ces normes doivent être consultées à des fins archivistiques seulement puisque leur contenu a été révoqué à la date du présent avis de retrait.

Des copies archivées des normes retirées peuvent être obtenues à des fins historiques ou archivistiques auprès du Centre des ventes de l'ONGC. Il suffit d'en faire la demande par téléphone au 819-956-0425 ou 1-800-665-2472, par télécopieur au 819-956-5740, par Internet à : www.tpsgc-pwgsc.gc.ca/ongc-cgsb/, par courriel à ncr.CGSB-ONGC@tpsgc-pwgsc.gc.ca, ou par courrier adressé au Centre des ventes, Office des normes générales du Canada, 11, rue Laurier, Gatineau, Canada K1A 1G6.

CAN/CGSB-1.5-M91

Diluant, essence minérale à faible point d'éclair (ICS 87.040)

CAN/CGSB-1.28-98

Peinture aux résines alkydes d'extérieur pour bâtiments (ICS 87.040)

CAN/CGSB-1.36-97

Vernis d'intérieur aux résines alkydes d'usage général (ICS 87.040)

CAN/CGSB-1.38-2000

Peinture-émail d'intérieur, pour couche de fond (ICS 87.040)

CAN/CGSB-1.40-97

Peinture pour couche primaire anticorrosion, aux résines alkydes, pour acier de construction (ICS 87.040)

CAN/CGSB-1.57-2003

Peinture-émail, d'intérieur, semi-brillante, aux résines alkydes (ICS 87.040)

CAN/CGSB-1.59-97

Peinture-émail, d'extérieur, brillante, aux résines alkydes (ICS 87.040)

CAN/CGSB-1.60-97

Peinture-émail brillante d'intérieur aux résines alkydes (ICS 87.040)

CAN/CGSB-1.61-2004

Exterior and Interior Marine Alkyd Enamel
(ICS 87.040)

CAN/CGSB-1.69-98

Aluminum Paint (ICS 87.040)

1-GP-71 (Oct 1983)

Methods of Testing Paints and Pigments
(ICS 87.040)

1-GP-71

Methods of Testing Paints and Pigments

No. 5-96

Drying Times of Paints and Related
Coatings (ICS 87.040)

No. 38-96

Blushing Resistance of Lacquer
Finishes (ICS 87.040)

No. 73-96

Beilstein Test for Chlorinated Solvents
(ICS 87.040)

CAN/CGSB-1.73-97

Exterior and Interior Enamel for Floors
(ICS 87.040)

CAN/CGSB-1.74-2001

Alkyd Traffic Paint (ICS 87.040)

CAN/CGSB-1.76-2000

Interior and Exterior Heat-Resistant Enamel
(ICS 87.040)

CAN/CGSB-1.81-M90

Air Drying and Baking Alkyd Primer for
Vehicles and Equipment (ICS 87.040)

CAN/CGSB-1.84-M91

Alkyd Primer for Hardwood (ICS 87.040)

CAN/CGSB-1.61-2004

Peinture-émail aux résines alkydes,
d'extérieur et d'intérieur, marine
(ICS 87.040)

CAN/CGSB-1.69-98

Peinture à l'aluminium (ICS 87.040)

1-GP-71 (oct. 1983)

Méthodes d'essai des peintures et pigments
(ICS 87.040)

1-GP-71

Méthodes d'essai des peintures et pigments

N° 5-96

Durée de séchage des peintures et
revêtements apparentés (ICS 87.040)

N° 38-96

Résistance à l'opalescence des
produits-laque de finition (ICS 87.040)

N° 73-96

Détermination de la présence de
solvants chlorés par l'essai de Beilstein
(ICS 87.040)

CAN/CGSB-1.73-97

Peinture-émail d'extérieur et d'intérieur,
pour sols (ICS 87.040)

CAN/CGSB-1.74-2001

Peinture alkyde de démarcation routière
(ICS 87.040)

CAN/CGSB-1.76-2000

Peinture-émail résistant à la chaleur,
d'intérieur et d'extérieur (ICS 87.040)

CAN/CGSB-1.81-M90

Peinture pour couche primaire aux résines
alkydes, séchant à l'air ambiant et au four,
pour véhicules automobiles et équipement
(ICS 87.040)

CAN/CGSB-1.84-M91

Peinture d'impression aux résines alkydes,
pour bois dur (ICS 87.040)

CAN/CGSB-1.88-92

Gloss Alkyd Enamel, Air Drying and Baking
(ICS 87.040)

CAN/CGSB-1.100-99

Interior Flat Latex Paint (ICS 87.040)

CAN/CGSB-1.104-M91

Semigloss Alkyd Air Drying and Baking
Enamel (ICS 87.040)

CAN/CGSB-1.105-M91

Quick-Drying Primer (ICS 87.040)

CAN/CGSB-1.114-M91

Quick-Drying Flat Enamel (ICS 87.040)

CAN/CGSB-1.118-95

Interior Flat Alkyd Finish (ICS 87.040)

CAN/CGSB-1.119-2000

Interior Latex Primer-Sealer (ICS 87.040)

CAN/CGSB-1.122-99

Anticorrosive Vinyl Primer (ICS 87.040)

CAN/CGSB-1.132-M90

Zinc Chromate Primer, Low Moisture
Sensitivity (ICS 87.040)

CAN/CGSB-1.135-99

Flat Alkyd Enamel for Equipment
(ICS 87.040)

CAN/CGSB-1.138-97

Exterior Latex Flat Paint (ICS 87.040)

CAN/CGSB-1.143-98

Silicone Alkyd Heat-Resistant Aluminum
Enamel (ICS 87.040)

CAN/CGSB-1.88-92

Peinture-émail brillante aux résines alkydes,
séchant à l'air ambiant et au four
(ICS 87.040)

CAN/CGSB-1.100-99

Peinture-émulsion mate d'intérieur
(ICS 87.040)

CAN/CGSB-1.104-M91

Peinture-émail semi-brillante aux résines
alkydes séchant à l'air ambiant et au four
(ICS 87.040)

CAN/CGSB-1.105-M91

Peinture pour couche primaire à séchage
rapide (ICS 87.040)

CAN/CGSB-1.114-M91

Peinture-émail mate à séchage rapide
(ICS 87.040)

CAN/CGSB-1.118-95

Peinture de finition mate d'intérieur aux
résines alkydes (ICS 87.040)

CAN/CGSB-1.119-2000

Peinture-émulsion d'impression d'intérieur
(ICS 87.040)

CAN/CGSB-1.122-99

Peinture pour couche primaire, aux résines
vinyliques, anticorrosion (ICS 87.040)

CAN/CGSB-1.132-M90

Peinture pour couche primaire, au chromate
de zinc, à faible sensibilité à l'humidité
(ICS 87.040)

CAN/CGSB-1.135-99

Peinture-émail mate aux résines alkydes
pour équipement (ICS 87.040)

CAN/CGSB-1.138-97

Peinture-émulsion (latex) mate, d'extérieur
(ICS 87.040)

CAN/CGSB-1.143-98

Peinture-émail aux résines silicones-
alkydes résistante à la chaleur (ICS 87.040)

CAN/CGSB-1.145-97

Solvent-Based Pigmented Stain
(ICS 87.040)

CAN/CGSB-1.146-99

Cold Curing, Gloss Epoxy Coating
(ICS 87.040)

CAN/CGSB-1.150-M91

Clear Lacquer for Wood Furniture
(ICS 87.040)

CAN/CGSB-1.153-2000

High-Build, Gloss Epoxy Coating
(ICS 87.040)

CAN/CGSB-1.154-M89

Latex Type Paint for Concrete Floors
(ICS 87.040)

CAN/CGSB-1.158-M89

Cellulose Nitrate Primer, Modified Alkyd
Type (ICS 87.040)

CAN/CGSB-1.159-92

Acrylic Cellulose Nitrate Gloss Lacquer
(ICS 87.040)

CAN/CGSB-1.160-93

Low Gloss Acrylic Cellulose Nitrate
Lacquer (ICS 87.040)

CAN/CGSB-1.162-2004

Emulsion Coating for Stucco and Masonry
(ICS 87.040)

CAN/CGSB-1.165-2004

Cold-Curing Epoxy Primer (ICS 87.040)

CAN/CGSB-1.171-98

Inorganic Zinc Coating (ICS 87.040)

CAN/CGSB-1.175-97

Polyurethane Interior Coating (ICS 87.040)

CAN/CGSB-1.145-97

Teinture pigmentée à base de solvant
(ICS 87.040)

CAN/CGSB-1.146-99

Revêtement aux résines époxydiques,
durcissant à froid, brillant (ICS 87.040)

CAN/CGSB-1.150-M91

Vernis-laque pour meubles en bois
(ICS 87.040)

CAN/CGSB-1.153-2000

Revêtement par peinture aux résines
époxydiques, à pouvoir garnissant élevé,
brillant (ICS 87.040)

CAN/CGSB-1.154-M89

Peinture-émulsion (latex) pour sols en béton
(ICS 87.040)

CAN/CGSB-1.158-M89

Peinture-laque pour couche primaire, au
nitrate de cellulose et aux résines alkydes
modifiées (ICS 87.040)

CAN/CGSB-1.159-92

Produit-laque brillant à la résine acrylique et
au nitrate de cellulose (ICS 87.040)

CAN/CGSB-1.160-93

Peinture-laque aux résines acryliques et au
nitrate de cellulose, peu brillante
(ICS 87.040)

CAN/CGSB-1.162-2004

Revêtement de type émulsion pour stuc et
maçonnerie (ICS 87.040)

CAN/CGSB-1.165-2004

Peinture pour couche primaire aux résines
époxydiques, durcissant à froid
(ICS 87.040)

CAN/CGSB-1.171-98

Enduit au zinc minéral (ICS 87.040)

CAN/CGSB-1.175-97

Revêtement de polyuréthane d'intérieur
(ICS 87.040)

CAN/CGSB-1.176-2000

Interior Clear Moisture-Curing Polyurethane Coating (ICS 87.040)

CAN/CGSB-1.177-M91

Two-Component Polyurethane Coating, Resistant to Chalking and Yellowing (ICS 87.040)

1-GP-180Ma (Feb 1996)

Coating, Polyurethane, Two-Package, General Purpose (ICS 87.040)

CAN/CGSB-1.181-99

Ready-Mixed Organic Zinc-Rich Coating (ICS 87.040)

CAN/CGSB-1.183-99

Zinc-Rich Epoxy Coating (ICS 87.040)

CAN/CGSB-1.184-98

Coal Tar-Epoxy Coating (ICS 87.040)

CAN/CGSB-1.188-2004

Emulsion Filler for Masonry Block (ICS 87.040)

CAN/CGSB-1.189-2000

Exterior Alkyd Primer for Wood (ICS 87.040)

CAN/CGSB-1.190-M90

Sanding Type Primer Surfacer (ICS 87.040)

1-GP-191M (Apr 1980)

Enamel, Automotive Refinishing, Fast Drying, Gloss (ICS 87.040)

1-GP-192Ma (Feb 1985)

Deck Coating, Nonslip, Epoxy (ICS 87.040)

CAN/CGSB-1.176-2000

Revêtement de polyuréthane, d'intérieur, durci à l'humidité, non pigmenté (ICS 87.040)

CAN/CGSB-1.177-M91

Revêtement de polyuréthane, à deux constituants séparés, non jaunissant et non farinant (ICS 87.040)

1-GP-180Ma (févr. 1996)

Revêtement de polyuréthane, à deux constituants séparés, pour utilisation générale (ICS 87.040)

CAN/CGSB-1.181-99

Enduit riche en zinc, organique et préparé (ICS 87.040)

CAN/CGSB-1.183-99

Enduit aux résines époxydiques, riche en zinc (ICS 87.040)

CAN/CGSB-1.184-98

Revêtement à base de goudron de houille-résines époxydiques (ICS 87.040)

CAN/CGSB-1.188-2004

Apprêt-émulsion pour blocs de maçonnerie (ICS 87.040)

CAN/CGSB-1.189-2000

Peinture d'impression, d'extérieur, aux résines alkydes, pour le bois (ICS 87.040)

CAN/CGSB-1.190-M90

Peinture pour couche primaire surfaçante de type ponçable (ICS 87.040)

1-GP-191M (avr. 1980)

Peinture-émail brillante, à séchage rapide, pour le repeinturage des carrosseries de véhicules automobiles (ICS 87.040)

1-GP-192Ma (févr. 1985)

Revêtement de pont, antidérapant, aux résines époxydiques (ICS 87.040)

CAN/CGSB-1.193-99

High-Build Epoxy Marine Coating
(ICS 87.040)

CAN/CGSB-1.195-99

Interior Latex Semigloss Paint (ICS 87.040)

CAN/CGSB-1.198-2001

Cementitious Primer for Galvanized
Surfaces (ICS 87.040)

1-GP-200Ma (Jan 1985)

Deck Coating, Nonslip, Polyurethane
(ICS 87.040)

CAN/CGSB-1.202-2003

Interior Alkyd Low Gloss Enamel
(ICS 87.040)

CAN/CGSB-1.203-2003

Exterior Latex Wood Primer (ICS 87.040)

CAN/CGSB-1.204-98

Exterior Latex Pigmented Stain
(ICS 87.040)

CAN/CGSB-1.205-2003

Sealer for Application to Asbestos-Fibre
Releasing Materials (ICS 87.040)

CAN/CGSB-1.207-98

Low-Temperature Curing Epoxy Coating
(ICS 87.040)

CAN/CGSB-1.208-99

Marine Interior Water-Borne Gloss Enamel
(ICS 87.040)

CAN/CGSB-1.209-2003

Interior Latex Low Gloss Paint (ICS 87.040)

CAN/CGSB-1.210-2003

Quick-Drying Alkyd Primer for Structural
Steel (ICS 87.040)

CAN/CGSB-1.193-99

Revêtement aux résines époxydiques, à
pouvoir garnissant élevé, marin
(ICS 87.040)

CAN/CGSB-1.195-99

Peinture-émulsion semi-brillante d'intérieur
(ICS 87.040)

CAN/CGSB-1.198-2001

Peinture primaire additionnée de ciment,
pour surfaces galvanisées (ICS 87.040)

1-GP-200Ma (janv. 1985)

Revêtement de pont, antidérapant, aux
résines polyuréthanes (ICS 87.040)

CAN/CGSB-1.202-2003

Peinture-émail d'intérieur, aux résines
alkydes, peu brillante (ICS 87.040)

CAN/CGSB-1.203-2003

Peinture-émulsion (latex) d'impression
extérieure, pour bois (ICS 87.040)

CAN/CGSB-1.204-98

Teinture-émulsion pigmentée pour extérieur
(ICS 87.040)

CAN/CGSB-1.205-2003

Peinture d'obturation pour matériaux
renfermant des fibres d'amiant
(ICS 87.040)

CAN/CGSB-1.207-98

Revêtement aux résines époxydiques
durcissant à basse température
(ICS 87.040)

CAN/CGSB-1.208-99

Peinture-émail brillante en suspension
aqueuse, marine, d'intérieur (ICS 87.040)

CAN/CGSB-1.209-2003

Peinture-émulsion d'intérieur peu brillante
(ICS 87.040)

CAN/CGSB-1.210-2003

Peinture primaire aux résines alkydes à
séchage rapide pour acier de charpente
(ICS 87.040)

CAN/CGSB-1.211-95

Coating Systems for Marine Floating Navigational Aids (Buoys) (ICS 87.040)

CAN/CGSB-1.212-2004

Heavy-Metal-Free Marine Primer for Steel and Light-Alloy Surfaces (ICS 87.040)

CAN/CGSB-1.213-2004

Etch Primer (Pretreatment Coating or Tie Coat) for Steel and Aluminum (ICS 87.040)

CAN/CGSB-1.214-2004

Heavy-Metal-Free, Water-Borne, Marine Primer for Steel and Light-Alloy Surfaces (ICS 87.040)

CAN/CGSB-1.215-96

Two-Package Epoxy Blockfiller (ICS 87.040)

CAN/CGSB-1.216-97

Exterior Water-Borne Gloss Enamel (ICS 87.040)

CAN/CGSB-1.219-2001

Lead and Chromate-Free Waterborne Traffic Paint (ICS 87.040)

CAN/CGSB-1.220-2001

Lead and Chromate-Free Alkyd Traffic Paint (ICS 87.040)

CAN/CGSB-1.223-2004

Heavy-Metal-Free, Water-Borne Wash Primer-Tie Coat (ICS 87.040)

CAN/CGSB-1.300-2000

Applied Coating System of Semigloss Baked Finish for Metal Office Furniture (ICS 87.040)

CAN/CGSB-1.500-75

Methods for Test for Toxic Trace Elements in Protective Coatings (ICS 87.040)

CAN/CGSB-1.211-95

Systèmes de revêtement pour aides à la navigation flottantes (bouées) (ICS 87.040)

CAN/CGSB-1.212-2004

Peinture primaire sans métal lourd, marine, pour surfaces en acier et en alliage léger (ICS 87.040)

CAN/CGSB-1.213-2004

Peinture primaire réactive (enduit de traitement préliminaire ou couche de liaison) pour l'acier et l'aluminium (ICS 87.040)

CAN/CGSB-1.214-2004

Peinture primaire, sans métal lourd, en suspension aqueuse, marine, pour surfaces en acier et en alliage léger (ICS 87.040)

CAN/CGSB-1.215-96

Apprêt pour blocs aux résines époxydiques en deux constituants (ICS 87.040)

CAN/CGSB-1.216-97

Peinture-émail brillante d'extérieur en suspension aqueuse (ICS 87.040)

CAN/CGSB-1.219-2001

Peinture à l'eau de démarcation routière sans plomb ni chromate (ICS 87.040)

CAN/CGSB-1.220-2001

Peinture alkyde de démarcation routière sans plomb ni chromate (ICS 87.040)

CAN/CGSB-1.223-2004

Peinture primaire réactive – Couche de liaison, sans métal lourd, en suspension aqueuse (ICS 87.040)

CAN/CGSB-1.300-2000

Système de revêtement de finition semi-brillant, cuit au four, pour meubles métalliques de bureau (ICS 87.040)

CAN/CGSB-1.500-75

Méthodes d'essai des éléments toxiques à l'état de trace dans les revêtements protecteurs (ICS 87.040)

CAN/CGSB-1.501-M89

Method for Permeance of Coated
Wallboard (ICS 87.040)

CAN/CGSB-1.501-M89

Méthode de détermination de la perméance
des panneaux muraux revêtus (ICS 87.040)



Government
of Canada

Gouvernement
du Canada

Canadian General
Standards Board

Office des normes
générales du Canada

CAN/CGSB-1.214-2004

Heavy-Metal-Free, Water-Borne, Marine Primer for Steel and Light-Alloy Surfaces

ICS 87.040

National Standard of Canada

The CANADIAN GENERAL STANDARDS BOARD (CGSB), under whose auspices this National Standard of Canada has been developed is a government agency within Public Works and Government Services Canada. CGSB is engaged in the production of voluntary standards in a wide range of subject areas through the media of standards committees and the consensus process. The standards committees are composed of representatives of relevant interests including producers, consumers and other users, retailers, governments, educational institutions, technical, professional and trade societies, and research and testing organizations. Any given standard is developed on the consensus of views expressed by such representatives.

CGSB has been accredited by the Standards Council of Canada as a national standards-development organization. The standards that it develops and offers as National Standards of Canada conform to the criteria and procedures established for this purpose by the Standards Council of Canada. In addition to standards it publishes as national standards, CGSB produces standards to meet particular needs, in response to requests from a variety of sources in both the public and private sectors. Both CGSB standards and CGSB national standards are developed in conformance with the policies described in the CGSB Policy Manual for the Development and Review of Standards.

CGSB standards are subject to review and revision to ensure that they keep abreast of technological progress. Suggestions for their improvement, which are always welcome, should be brought to the notice of the standards committees concerned. Changes to standards are issued either as separate amendment sheets or in new editions of standards.

An up-to-date listing of CGSB standards, including details on latest issues and amendments, and ordering instructions, is found in the CGSB Catalogue, which is published annually and is available without charge upon request. An electronic version, ECAT, is also available. More information is available about CGSB products and services at our Web site — www.ongc-cgsb.gc.ca.

Although the intended primary application of this standard is stated in its Scope, it is important to note that it remains the responsibility of the users of the standard to judge its suitability for their particular purpose.

The testing and evaluation of a product against this standard may require the use of materials and/or equipment that could be hazardous. This document does not purport to address all the safety aspects associated with its use. Anyone using this standard has the responsibility to consult the appropriate authorities and to establish appropriate health and safety practices in conjunction with any applicable regulatory requirements prior to its use. CGSB neither assumes nor accepts any responsibility for any injury or damage that may occur during or as the result of tests, wherever performed.

Attention is drawn to the possibility that some of the elements of this Canadian standard may be the subject of patent rights. CGSB shall not be held responsible for identifying any or all such patent rights. Users of this standard are expressly advised that determination of the validity of any such patent rights are entirely their own responsibility.

Further information on CGSB and its services and standards may be obtained from:

The Manager
Strategic Standardization Division
Canadian General Standards Board
Gatineau, Canada
K1A 1G6

The STANDARDS COUNCIL OF CANADA is the co-ordinating body of the National Standards System, a federation of independent, autonomous organizations working towards the further development and improvement of voluntary standardization in the national interest.

The principal objectives of the Council are to foster and promote voluntary standardization as a means of advancing the national economy, benefiting the health, safety and welfare of the public, assisting and protecting the consumer, facilitating domestic and international trade, and furthering international co-operation in the field of standards.

A National Standard of Canada is a standard which has been approved by the Standards Council of Canada and one which reflects a reasonable agreement among the views of a number of capable individuals whose collective interests provide, to the greatest practicable extent, a balance of representation of producers, users, consumers and others with relevant interests, as may be appropriate to the subject in hand. It normally is a standard that is capable of making a significant and timely contribution to the national interest.

Approval of a standard as a National Standard of Canada indicates that a standard conforms to the criteria and procedures established by the Standards Council of Canada. Approval does not refer to the technical content of the standard; this remains the continuing responsibility of the accredited standards-development organization.

Those who have a need to apply standards are encouraged to use National Standards of Canada whenever practicable. These standards are subject to periodic review; therefore, users are cautioned to obtain the latest edition from the organization preparing the standard.

The responsibility for approving National Standards of Canada rests with the:

Standards Council of Canada
270 Albert Street
Suite 200
Ottawa, Ontario
K1P 6N7

How to order CGSB Publications:

by telephone — (819) 956-0425 or
— 1-800-665-2472

by fax — (819) 956-5644

by mail — CGSB Sales Centre
Gatineau, Canada
K1A 1G6

in person — Place du Portage
Phase III, 6B1
11 Laurier Street
Gatineau, Quebec

by email — ncr.cgsb-ongc@pwgsc.gc.ca

on the Web — www.ongc-cgsb.gc.ca

HEAVY-METAL-FREE, WATER-BORNE, MARINE PRIMER FOR STEEL AND LIGHT-ALLOY SURFACES

Prepared by the

Canadian General Standards Board 

Approved by the

Standards Council of Canada



Published July 2004 by the
Canadian General Standards Board
Gatineau, Canada K1A 1G6

© HER MAJESTY THE QUEEN IN RIGHT OF CANADA,
as represented by the Minister of Public Works and Government Services,
the Minister responsible for the Canadian General Standards Board, (2004).

No part of this publication may be reproduced in any form without the prior permission of the publisher.

CANADIAN GENERAL STANDARDS BOARD
COMMITTEE ON MARINE PAINTS

(Membership at date of approval)

Benner, H.	<i>Chairman</i>	Consultant
Agnew, D.		Amercoat Canada
Alliston, G.		Specialty Polymer Coatings Inc.
Buchanan, I.		Buchanan Consulting
Cameron, H.		Camcoat Industries
Dunne, R.		Wasser High Tech Coatings
Foster, T.		National Defence
Gauvin, D.		Fisheries and Oceans Canada
Janssen, M.		National Defence
Lepage, F.		National Defence
Lidstone, S.		International Paint
Morton, T.		Consultant
Peabody, S.		National Defence
Pepin, L.		Sico Inc.
Philipp, H.		Consultant
Smith, F.		Fleetway Inc.
Williams, R.		Sherwin-Williams Co.
Craig, W.	<i>Secretary</i>	Canadian General Standards Board

Acknowledgment is made for the translation of this National Standard of Canada by the Translation Bureau of Public Works and Government Services Canada.

CANADIAN GENERAL STANDARDS BOARD

**HEAVY-METAL-FREE, WATER-BORNE, MARINE PRIMER
FOR STEEL AND LIGHT-ALLOY SURFACES****1. SCOPE**

- 1.1 This standard applies to a heavy-metal-free, water-borne primer.
- 1.2 The primer is suitable for use on steel and light-alloy surfaces aboard ships and on other marine structures exposed to intermittent immersion in salt water. The corrosion-inhibiting primer may be used either alone or with a topcoat.
- 1.3 The testing and evaluation of a product against this standard may require the use of materials and/or equipment that could be hazardous. This document does not purport to address all the safety aspects associated with its use. Anyone using this standard has the responsibility to consult the appropriate authorities and to establish appropriate health and safety practices in conjunction with any applicable regulatory requirements prior to its use.

2. REFERENCED PUBLICATIONS

- 2.1 The following publications are referenced in this standard:
- 2.1.1 Canadian General Standards Board (CGSB)
CAN/CGSB-1.61 — Exterior and Interior Marine Alkyd Enamel
1-GP-71 — Methods of Testing Paints and Pigments.
- 2.1.2 Health Canada
Surface Coating Materials Regulations
Consumer Chemicals and Containers Regulations, 2001
Controlled Products Regulations (WHMIS)¹.
- 2.1.3 ASTM International
D 93 — Standard Test Methods for Flash Point by Pensky-Martens Closed Cup Tester
D 1210 — Standard Test Method for Fineness of Dispersion of Pigment-Vehicle Systems by Hegman-Type Gage
D 3960 — Standard Practice For Determining Volatile Organic Compound (VOC) Content Of Paints and Related Coatings
D 5894 — Standard Practice for Cyclic Salt Fog/UV Exposure of Painted Metal, (Alternating Exposures in a Fog/Dry Cabinet and a UV/Condensation Cabinet).
- 2.2 A dated reference in this standard is to the issue specified. An undated reference in this standard is to the latest issue, unless otherwise specified by the authority applying this standard. The sources are given in the Notes section.

3. GENERAL REQUIREMENTS

- 3.1 The primer shall consist of a heavy-metal-free pigment or pigment mixture, adequately dispersed in a suitable vehicle together with the necessary water thinner and water miscible co-solvents.
- 3.2 The primer shall be suitable for application by brush or roller and shall be satisfactory for spraying when reduced with water in accordance with the manufacturer's instructions.

¹ WHMIS: Workplace Hazardous Materials Information System.

- 3.3 The primer shall have good flowing and brushing properties. It shall dry to a smooth uniform matte or low-gloss appearance without wrinkling or sagging.
- 3.4 When stored at temperatures between 5 and 40°C, the primer shall not skin, thicken excessively, gel or cake in the original unopened container for 24 months from the date of shipment. At the end of this time, it shall be readily mixed to a uniform condition by stirring and shall meet the requirements of drying time (par. 4.3).
- 3.5 **Toxic Elements** — The primer shall conform to the requirements of the *Surface Coating Materials Regulations*, the *Consumer Chemicals and Containers Regulations*, 2001, and the *Controlled Products Regulations* (WHMIS), for designated toxic elements.

4. DETAILED REQUIREMENTS

The primer shall comply with the following detailed requirements when tested in accordance with the specified test methods:

		Test Method		
		Min.	Max.	CGSB 1-GP-71 ASTM
4.1	Flash point, Pensky-Martens closed cup °C	40	—	— D 93
4.2	Consistency, Krebs Units	70	—	4.5 —
4.3	Drying time, hard dry, h	—	24	5, Method A —
4.4	60°C gloss units	—	10	13.1 —
4.5	Fineness of grind	6	—	— D 1210
4.6	Volatile Organic Compound (VOC), g/L	—	150	— D 3960
4.7	Salt-spray resistance, d	14	—	— D 5894 ²
4.8	Skinning Properties — When tested in accordance with CGSB standard 1-GP-71, Method 10.1, the primer shall be non-skinning.			
4.9	Flexibility — When tested in accordance with CGSB standard 1-GP-71, Method 119.5, and subjected to the bending test at 23 ± 2°C using a 6.4 mm mandrel, the dried film shall not crack or peel.			
4.10	Behaviour Towards Topcoats — When tested in accordance with CGSB standard 1-GP-71, Method 130.1, the topcoat (enamel conforming to CAN/CGSB-1.61) shall show no blistering, wrinkling, softening, lifting or other defects. The topcoat shall have been applied at a dry film thickness of 50 ± 10 µm over the primer that has been dried for 24 h. When tested in accordance with CGSB standard 1-GP-71, Method 135.1 (knife test), the topcoat that has dried for 48 h shall show no evidence of loss of intercoat adhesion between the primer and the topcoat. The topcoat shall show no flaking, loosening or separation in the area adjacent to the knife cut. The ribbon of coating from the knife test shall be free from crumbling.			
4.11	Adhesion to Metal — When tested in accordance with CGSB standard 1-GP-71, Method 135.1 (knife test), the primer applied to prepared aluminium and steel panels (par. 6.2.1), then dried for 7 d, shall have satisfactory adhesion. The area adjacent to the cut shall be free from flaking or loosening.			
4.12	Water Resistance — When tested in accordance with CGSB standard 1-GP-71, Method 110.1, the primer shall withstand immersion in water at 23 ± 2°C for 24 h without blistering, wrinkling, loosening, checking or peeling. After a 2 h recovery period, the film shall show no softening. When tested in accordance with CGSB standard 1-GP-71, Method 135.1 (after a 2 h recovery period), the film shall show no flaking or loosening in the area adjacent to the knife cut.			

² Allow the panels under test (bare aluminum Q panels) to dry for 7 d before testing.

- 4.12.1 When tested in accordance with CGSB standard 1-GP-71, Method 110.9, the coating systems, as specified in par. 6.2.2, of primer topcoated with enamel shall withstand 24 h immersion in water at $23 \pm 2^\circ\text{C}$ without blistering, lifting, loosening or peeling. When tested in accordance with CGSB standard 1-GP-71, Method 135.1 (after a 2 h recovery period), the topcoat shall produce a ribbon of film free from crumbling and intercoat separation. In the area adjacent to the knife cut, there shall be no flaking or loosening of the film or separation of the coats.

- 4.13 **Applicability and Appearance** — When tested in accordance with CGSB standard 1-GP-71, Method 134.8, and when applied to the surface of a steel or aluminum panel, the primer shall show good hiding, spreading, levelling and brushing properties; ease of lapping; uniform appearance; and freedom from sagging and wrinkling.

5. PREPARATION FOR DELIVERY

- 5.1 Unless otherwise specified (par. 7.1), preparation for delivery shall conform to normal commercial practice.
- 5.2 **Labelling** — In addition to complying with the labelling requirements of any relevant acts or regulations, each container shall be suitably labelled to show the following information:
- Name of material
- Standard number: CAN/CGSB-1.214-2004
- NATO stock number (when required)
- Manufacturer's batch number
- Manufacturer's code number
- Date of manufacture
- Instructions for use:
- thinning instructions
 - instructions for cleaning brushes, spray equipment and tools
- Cautionary notes:
- safety precautions to be taken at time of application.

6. INSPECTION

- 6.1 **Sampling** — Sampling shall be carried out in accordance with CGSB standard 1-GP-71, Method 1.1.
- 6.2 **Testing**
- 6.2.1 **Preparation of Primed Panels** — Spray the primer on $75 \times 150 \times 3.2$ mm aluminum panels (aluminum for tests in par. 4.7, 4.11 and 4.12 and 4.12.1) or steel (steel 1010 or 1040) panels (all other tests), prepared in accordance with CGSB standard 1-GP-71, Method 100.2, at a dry film thickness of $60 \pm 10 \mu\text{m}$. Before application, thin the primer according to the manufacturer's instructions.
- 6.2.2 Where an enamel topcoat is required, it shall consist of one coat of enamel at a dry film thickness of $50 \pm 10 \mu\text{m}$ in accordance with CAN/CGSB-1.61.

7. NOTES

- 7.1 The following option must be specified in the application of this standard:
- a. Preparation for delivery, if other than as specified (par. 5.1).
- 7.2 **Recommended Practices**
- 7.2.1 **Topcoats** — The topcoats specified in CAN/CGSB-1.61, CAN/CGSB-1.88, CAN/CGSB-1.135, CAN/CGSB-1.138, CAN/CGSB-1.208 and CAN/CGSB-1.216 are normally used for this primer.
- 7.3 **Related Publications**
- 7.3.1 Canadian General Standards Board (CGSB)

CAN/CGSB-1.88 — Gloss Alkyd Enamel, Air-Drying and Baking
CAN/CGSB-1.135 — Flat Alkyd Enamel for Equipment
CAN/CGSB-1.138 — Exterior Latex Flat Paint
CAN/CGSB-1.208 — Marine, Interior, Water-borne Gloss Enamel
CAN/CGSB-1.216 — Exterior, Water borne, Gloss Enamel.

7.4 Sources of Referenced Publications

The following addresses were valid at the date of publication.

- 7.4.1 The publications referred to in par. 2.1.1 and 7.3.1 may be obtained from the Canadian General Standards Board, Sales Centre, Gatineau, Canada K1A 1G6. Telephone (819) 956-0425 or 1-800-665-2472. Fax (819) 956-5644. E-mail ncr.cgsb-ongc@pwgsc.gc.ca. Web site www.ongc-cgsb.gc.ca.
- 7.4.2 The publications referred to in par. 2.1.2 may be obtained from Health Canada, Consumer Product Safety Bureau, MacDonald Building, 4th floor, 123 Slater Street, Ottawa, Canada K1A 0K9. Telephone (613) 954-0104. Fax (613) 952-1994. Web site www.hc-sc.gc.ca.
- 7.4.3 The publications referred to in par. 2.1.3 may be obtained from ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959, U.S.A., telephone (610) 832-9585, fax (610) 832-9555, Web site www.astm.org or from IHS Canada, 1 Antares Drive, Suite 200, Ottawa, Ontario K2E 8C4, telephone (613) 237-4250 or 1-800-267-8220, fax (613) 237-4251, Web site www.ihs.com.
-