3-GP-952
3 May 1956
CANCELLATION
September 1969

CANADIAN GOVERNMENT SPECIFICATION BOARD

Specification
for

TOLUENE: FOR PREPARATION OF STANDARD TEST HYDROCARBON FLUID

This specification is cancelled as of September 1969. Reference may be made to ASTM D362, Industrial Grade Toluene.

ARCHIVES COPY

3-GP-952
3 May 1956
CORRECTION NO. 1
19 September 1956

CANADIAN GOVERNMENT SPECIFICATIONS BOARD

Specification
for

TOLUENE; FOR PREPARATION OF STANDARD TEST HYDROCARBON FLUID

Section 4.1.3: In the min. column delete "96.0" and insert "97.0"

Withdrawn/Retirée

NADA

CANADIAN GOVERNMENT SPECIFICATIONS BOARD

SPECIFICATION

FOR

TOLUENE; FOR PREPARATION OF STANDARD TEST HYDROCARBON FLUID

3-GP-952

3 MAY 1956

Withdrawn/Retirée

THIS SPECIFICATION APPLIES TO ONE GRADE OF TOLUENE TO BE USED IN THE PREPARATION OF HYDROCARBON FLUID FOR STANDARD TESTS.

NATIONAL RESEARCH COUNCIL, OTTAWA, CANADA

Price

10 CENTS

For the convenience of those wishing to purchase publications of the Canadian Government Specifications Board, coupons are available in denominations of 5¢, 25¢, and 50¢ and may be obtained by forwarding a remittance to the National Research Council in the form of Bank, Express, or Post Office Money Order, or a cheque made payable at par in Ottawa, to Receiver General of Canada, credit National Research Council (stamps are not acceptable). These coupons can then be used when submitting orders for publications. An Index of Specifications can be obtained on request.

COMMITTEE ON SPECIFICATIONS FOR
PETROLEUM AND ASSOCIATED PRODUCTS

(Membership at date of approval by the Committee
for submission to the CGSB)

Parkin, J.H. (Chairman)	Division of Mechanical Engineering National Research Council
Barton, H.B.	McColl-Frontenac Oil Co. Limited
Black, J.W.	DVD/Department of National Defence
Broughton, J.W.	Division of Mechanical Engineering National Research Council
Campbell, R.O.	British American Oil Co. Limited
Charlesworth, J.S.	Research Council of Alberta
Chisholm, W.H., Major	DST/Department of National Defence
Draper, R.G. (alternate)	Department of Mines & Technical Surveys
Elworthy, R.T.	Department of Trade & Commerce
Keohane, T.J., Lt. Cdr(E)	RCN/Department of National Defence
Kuhring, M.S.	Division of Mechanical Engineering National Research Council
Lamoureux, P.E.	Trans-Canada Air Lines
Laycraft, N.E.	Department of Public Works
Lusk, J.	Shell Oil Co. of Canada Limited
Montgomery, D.S.	Department of Mines & Technical Surveys
Rhodes, D.F.	Canadian Oil Companies Limited
Rugenius, A.V., F/L	AFHQ/Department of National Defence
Showalter, H.A.	IS/Department of National Defence
Udall, P.J.	Division of Mechanical Engineering National Research Council
Whitfield, L.F.	Imperial Oil Limited
Williams, F.D.M.	Orenda Engines Limited
Mitton, H.E. (Secretary)	CGSB/National Research Council

Withdrawn/Retirée

3-GP-952
3 May 1956

CANADIAN GOVERNMENT SPECIFICATIONS BOARD

Specification
for

TOLUENE; FOR PREPARATION OF STANDARD TEST HYDROCARBON FLUID

Withdrawn/Retirée

1. DEFINITION

1.1 This specification applies to one grade of toluene to be used in the preparation of hydrocarbon fluid for standard tests.

1.2 For more detailed information on uses, see Section 6.1 below.

2. APPLICABLE PUBLICATIONS

2.1 Reference, to the extent specified herein, is made in this specification to the following documents:

2.1.1 3-GP-0: CGSB Schedule of Methods of Testing Petroleum and Associated Products.

2.1.2 ASTM Standards on Petroleum Products and Lubricants (and latest supplement unless otherwise specified).

2.1.3 ASTM Standards on Paint, Varnish, Lacquer and Related Products (and latest supplement unless otherwise specified).

2.2 Reference to documents and test methods shall be the issue in effect on the date of invitation to tender, unless otherwise specified.

3. GENERAL REQUIREMENTS

3.1 The toluene shall be obtained from either coal tar or petroleum.

3.2 It shall be clear and free from undissolved water, sediment and suspended matter.

4. DETAIL REQUIREMENTS

NOTE: Requirements contained herein are absolute and not subject to corrections for tolerance of test methods. However, if multiple determinations are made, average results will be used.

The toluene shall comply with the following detail requirements:

		Min.	Max.	Test Method 3-GP-0	Test Method ASTM
4.1	Distillation			-	D1078
4.1.1	Initial Boiling Point, °F	228	-		
4.1.2	Dry Point, °F	-	235		
4.1.3	Total Distillate, percent by volume	96	-		
4.2	Color (Saybolt)	+20	-	-	D156
4.3	Specific Gravity 60/60°F	0.864	0.874	-	D1298
4.4	Total Acid Number	-	Nil	2.8	-
4.5	Aromatics, percent by vol.	96.0	-	-	D875
4.6	Olefins, percent by volume	-	1.0	-	D1019

4.7 Sulfur Compounds - Hydrogen sulfide and sulfur dioxide shall not be present as evidenced by discoloration of the appropriate test papers.

3-GP-0 Method 66.2

4.8 Corrosion - The copper strip shall show no iridescence nor a grey or black discoloration, but a slight uniform tarnish shall not be cause for rejection.

3-GP-0 Method 60.15a

5. ACCEPTANCE TESTS, SAMPLING AND TEST METHODS

5.1 Acceptance Tests - Acceptance tests shall consist of tests for all requirements of this specification.

5.2 Acceptance Test Sample- A sample of not less than one Imperial quart shall be provided for acceptance tests and shall be obtained in accordance with Section 1.1 of Schedule 3-GP-0: Methods of Testing Petroleum and Associated Products.

5.3 Testing - The methods of testing shall be those in CGSB Schedule 3-GP-0, in ASTM Standards on Petroleum Products and Lubricants, or in ASTM Standards on Paint, Varnish, Lacquer and Related Products as specified, using the procedure prescribed with each requirement.

Withdrawn/Retirée

6. NOTES

6.1 Intended Uses - The toluene covered by this specification is intended for use in preparation of standard test hydrocarbon fluid.

6.2 Related CGSB Specifications - There are not other CGSB specifications covering a similar type of toluene.

6.3 Other Related Specifications - At the time of publication, the undernoted documents were corresponding specifications (but not necessarily equivalent);

6.3.1 US Federal Specification TT-T-548a

6.3.2 Joint Army-Navy Specification JAN-T-171(2), Grade B

6.3.3 ASTM Specification D842

6.4 Information regarding items listed in Section 2 may be obtained on application to the CGSB Secretary.

Withdrawn/Retirée

Correspondence regarding this specification should be addressed to the Secretary, Canadian Government Specifications Board, National Research Council, Ottawa, Canada.