

**Technical Information**  
 This map was compiled from data acquired during an airborne electromagnetic survey carried out by Geotech Canada Inc. utilizing Geoscan's VTEM Max Time-Domain Electromagnetic (TDEM) system. The systems were mounted on two Eurocopter AS350 B3 helicopters (registration C-GTCD and C-GTCE) and the survey was carried out between December 19, 2019 and March 10, 2020. The helicopter flight altitude was maintained at an average ground clearance of 80 m, with an average speed of 90 km/h. Aircraft navigation used a Leica NovaRT Novatell dual frequency GPS system. Post-flight differential corrections were applied to finalize the flight path position. A vertically mounted video camera was used to record images of the ground. The radar height was recorded ten times per second using a TRAX3000 altimeter. The magnetic data were recorded 10 times per second using a Geometrics G-822A cesium magnetometer installed in a sled 70 m below the helicopter.

**Electromagnetics**  
 The TDEM system operated at a base frequency of 30 Hz transmits a 7.0 ms half square signal from a 400-turn, 940 m<sup>2</sup> horizontal loop mounted approximately 48 m below and 1.5 m behind the helicopter. This configuration generates a peak dipole moment of 721,920 Am<sup>2</sup>. The response of conductors in the subsurface was recorded at 10 Hz with a sine waveform using a three-axis (X, Y and Z) electromagnetic receiver coincident with the transmitter loop (in-Loop Transmitter-Receiver). The EM receiver recorded data in a continuous stream for each of the three components. The EM receiver directly measures the change in the magnetic field with respect to time (dB/dt) from which the secondary magnetic field (B) is numerically integrated. High-passband background sections from at the start and end of each flight allowed a fast-order removal of system drift.

**Apparent Conductivity**  
 The apparent conductivity values (mS/m) were derived from the electromagnetic decays using selected early channels 4 to 14 (0.021 - 0.096 ms), middle channels 15 to 30 (0.110 - 0.880 ms) and late channels 31 to 46 (1.010 - 8.083 ms) of the off-time signal. The nomogram indicates the correspondence between the value of dB/dt (nT/s) and halfspace conductivity. Forward this time modeling is used to estimate the depth to the top of target (m) for the VTEM™ MAX TDEM system.

**Electromagnetic Decay Constant**  
 Decay constant (Tau) values were obtained by fitting the data from selected early Z channels 4 to 14 (0.021 - 0.096 ms), middle channels 15 to 30 (0.110 - 0.880 ms) and late channels 31 to 46 (1.010 - 8.083 ms) of the off-time signal to a single exponential. In semi-log space, the slope of this function will reflect the exponential decay rate of the transient field and, therefore, the strength of the conductivity. A slow rate of decay, reflecting a high conductivity, will be represented by a high conductivity value.

**Magnetics**  
 The magnetic field was sampled 10 times per second using a cesium vapour magnetometer (frequency = 0.021 Hz) mounted on the EM transmitter loop. Differences in magnetic values at the intersections of control and traverse lines were analysed to obtain a mutually levelled set of flightline magnetic data. The levelled values were then interpolated to a 50 m grid. The International Geomagnetic Reference Field (IGRF) defined as a mean GRS altitude (472 m) for a constant mid-survey date (January 15, 2020) was then removed. Removal of the IGRF, representing the magnetic field of Earth's core, produces a residual component related essentially to magnetizations within Earth's crust.

**The first vertical derivative of the magnetic field is the rate of change of the magnetic field in the vertical direction. Computation of the first vertical derivative removes long-wavelength features of the magnetic field and significantly improves the resolution of closely spaced and superposed anomalies. A property of first vertical derivative maps is the coincidence of the zero-value contour with vertical geologic contacts at high magnetic latitudes (Hood, 1965). The first vertical derivative of the magnetic field was calculated using the fast Fourier transform on the gridded total magnetic field with a grid cell size of 50 m.**

**Availability**  
 This map is available for free download through GEOSCAN (<http://geoscan.nrcan.gc.ca/>). Corresponding digital profile and gridded data as well as similar data for adjacent airborne geophysical surveys can be downloaded, at no charge, from Natural Resources Canada's Geoscience Data Repository for Geophysical Data at [http://gpr.nrcan.gc.ca/index\\_e.html](http://gpr.nrcan.gc.ca/index_e.html). The same products are also available, for a fee, from The Geophysical Data Centre, Geological Survey of Canada, 501 Booth Street, Ottawa, Ontario K1A 0E8. Telephone: 613-995-5326, email: [info@geoscan.gc.ca](mailto:info@geoscan.gc.ca).

**Acknowledgments**  
 The authors thank the Geotech Canada Inc. team: Shauna-Lee Hewitt, Dmitry Danosheko, Zhao He, Emily Data and David Hitz. The authors thank Jim Crayon and Mark Pilkington for helpful comments and suggestions to improve the maps.

**Reference**  
 Hood, P.A., 1965. Gradient measurements in aeromagnetic surveying. *Geophysics*, v. 30, p. 891-902.



**Survey Area Parameters:**

Traverse line azimuth	N0°E
Traverse line spacing	200 m
Traverse line width	N00°E
Traverse line spacing	1000 m
Altitude average clearance	80 m
EM transmitter nominal clearance	50 m
Magnetic sensor nominal clearance	18 m
EM receiver nominal clearance	50 m

**Electromagnetic System Specifications:**

Base frequency	30 Hz
Waveform	Polyphasic
Transmitter pulse width	7 ms
Transmitter area	940 m <sup>2</sup>
Transmitter offset	8.7 m
Transmitter loop diameter	34.6 m
Transmitter peak current	192 A
Dipole moment (peak)	721 920 Am <sup>2</sup> (4 turns)
Minimum data sampling rate	10 Hz

**Receiver:** 3-component induction coil (Z, X, Y)  
**Measured response:** Voltage (dB/dt)  
**Digital recording:** Z: 4-46 channels  
 X, Y: 20-46 channels  
**Off-time Z channel:** Channel 4 at ~0.021 ms after pulse turn off  
**Trx/Rx configuration:** In-loop receiver



**MAP SHEET SUMMARY**

- Sheet 1: Time Decay Constant (Tau-Z) - Early Channels 4 to 14 (0.021 - 0.096 ms)
- Sheet 2: Time Decay Constant (Tau-Z) - Mid Channels 15 to 30 (0.110 - 0.880 ms)
- Sheet 3: Time Decay Constant (Tau-Z) - Late Channels 31 to 46 (1.010 - 8.083 ms)
- Sheet 4: Apparent Conductivity - Early Channels 4 to 14 (0.021 - 0.096 ms)
- Sheet 5: Apparent Conductivity - Mid Channels 15 to 30 (0.110 - 0.880 ms)
- Sheet 6: Apparent Conductivity - Late Channels 31 to 46 (1.010 - 8.083 ms)
- Sheet 7: Residual Total Magnetic Field
- Sheet 8: First Vertical Derivative of the Magnetic Field
- Sheet 9: Interpretation

**PLANIMETRIC SYMBOLS**

- Project Limit
- Drainage
- Topographic Contour
- Building
- Road
- Flight Path

**ZERO VECTOR OF THE FIRST VERTICAL DERIVATIVE OF THE TOTAL MAGNETIC FIELD REDUCED TO THE POLE**



0.0 nT/m

**ELECTROMAGNETIC ANOMALY SYMBOLS**

Anomaly ID	Estimated Depth (m)	Conductivity (S)
▲	> 80	> 80
●	35-60	35-60
○	20-35	20-35
○	10-20	10-20
○	5-10	5-10
○	< 5	< 5
○	Cultural	Cultural

The anomalies identified by a red circle inside are manually picked as a narrow bedrock conductor (category "B"). Otherwise, they are picked as a bedrock conductor (category "A"). Further details can be found in the contractor report.

**Authors:** O. Boulanger, F. Kiss, R. Fortin and O. Mahmoodi  
 Data acquisition and data compilation by Geotech Limited, Aurora, Ontario  
 Contract and project management by the Geological Survey of Canada, Ottawa, Ontario  
 Digital cartography by D. Oneschuk, Geological Survey of Canada  
 Permanent link: <https://doi.org/10.4095/326711>



**GEOLOGICAL SURVEY OF CANADA OPEN FILE 8672**  
**SASKATCHEWAN GEOLOGICAL SURVEY GEOPHYSICAL MAP GP 2020-2**  
**ELECTROMAGNETIC SURVEY OF THE SOUTHERN GLENNIE AREA**  
 SASKATCHEWAN  
 Parts of NTS 73-116 and NTS 73-P01

**INTERPRETATION**  
 Scale 1:50 000

Universal Transverse Mercator Projection  
 World Geodetic System 1984  
 © Her Majesty the Queen in Right of Canada, as represented by the Minister of Natural Resources, 2020  
 Base map at the scale of 1:50 000 from Natural Resources Canada, with modifications  
 Elevations in metres above sea level

**OPEN FILE / DOSSIER PUBLIC**  
**8672**  
 GEOLOGICAL SURVEY OF CANADA  
 COMMISSION GÉOLOGIQUE DU CANADA  
 2020  
 Sheet 9 of 9 / Feuille 9 de 9

**GEOPHYSICAL MAP**  
**CARTE GÉOPHYSIQUE**  
**GP 2020-2**  
 SASKATCHEWAN GEOLOGICAL SURVEY  
 COMMISSION GÉOLOGIQUE DE LA SASKATCHEWAN  
 2020  
 Sheet 9 of 9 / Feuille 9 de 9